
freud Documentation

Release 2.2.0

The Regents of the University of Michigan

Feb 25, 2020

GETTING STARTED

1	Overview	3
2	Resources	5
3	Citation	7
4	Installation	9
5	Examples	11
6	Support and Contribution	13
7	Table of Contents	15
7.1	Introduction	15
7.2	Installation	15
7.3	Quickstart Guide	18
7.4	Tutorial	19
7.5	Examples	28
7.6	Query API	131
7.7	Using freud Efficiently	134
7.8	Reading Simulation Data for freud	135
7.9	Box Module	138
7.10	Cluster Module	143
7.11	Data Module	145
7.12	Density Module	148
7.13	Environment Module	154
7.14	Interface Module	162
7.15	Locality Module	163
7.16	MSD Module	172
7.17	Order Module	174
7.18	Parallel Module	181
7.19	PMFT Module	182
7.20	Development Guide	189
7.21	How to cite freud	202
7.22	References	203
7.23	License	203
7.24	Credits	204
8	Indices and tables	213
	Bibliography	215

Python Module Index	217
Index	219

OVERVIEW

The **freud** Python library provides a simple, flexible, powerful set of tools for analyzing trajectories obtained from molecular dynamics or Monte Carlo simulations. High performance, parallelized C++ is used to compute standard tools such as radial distribution functions, correlation functions, order parameters, and clusters, as well as original analysis methods including potentials of mean force and torque (PMFTs) and local environment matching. The **freud** library supports *many input formats* and outputs *NumPy arrays*, enabling integration with the scientific Python ecosystem for many typical materials science workflows.

RESOURCES

- [Reference Documentation](#): Examples, tutorials, topic guides, and package Python APIs.
- [Installation Guide](#): Instructions for installing and compiling **freud**.
- [freud-users Google Group](#): Ask questions to the **freud** user community.
- [GitHub repository](#): Download the **freud** source code.
- [Issue tracker](#): Report issues or request features.

CITATION

When using **freud** to process data for publication, please [use this citation](#).

INSTALLATION

The easiest ways to install **freud** are using pip:

```
pip install freud-analysis
```

or conda:

```
conda install -c conda-forge freud
```

freud is also available via containers for [Docker](#) or [Singularity](#). If you need more detailed information or wish to install **freud** from source, please refer to the [Installation Guide](#) to compile **freud** from source.

EXAMPLES

The **freud** library is called using Python scripts. Many core features are [demonstrated in the freud documentation](#). The examples come in the form of Jupyter notebooks, which can also be downloaded from the [freud examples repository](#) or [launched interactively on Binder](#). Below is a sample script that computes the radial distribution function for a simulation run with **HOOMD-blue** and saved into a **GSD** file.

```
import freud
import gsd.hoomd

# Create a freud compute object (RDF is the canonical example)
rdf = freud.density.RDF(bins=50, r_max=5)

# Load a GSD trajectory (see docs for other formats)
traj = gsd.hoomd.open('trajectory.gsd', 'rb')
for frame in traj:
    rdf.compute(system=frame, reset=False)

# Get bin centers, RDF data from attributes
r = rdf.bin_centers
y = rdf.rdf
```


SUPPORT AND CONTRIBUTION

Please visit our repository on [GitHub](#) for the library source code. Any issues or bugs may be reported at our [issue tracker](#), while questions and discussion can be directed to our [user forum](#). All contributions to **freud** are welcomed via pull requests!

TABLE OF CONTENTS

7.1 Introduction

The **freud** library is a Python package for analyzing particle simulations. The package is designed to directly use numerical arrays of data, making it easy to use for a wide range of use-cases. The most common use-case of **freud** is for computing quantities from molecular dynamics simulation trajectories, but it can be used for analyzing any type of particle simulation. By operating directly on numerical arrays of data, **freud** allows users to parse custom simulation outputs into a suitable structure for input, rather than relying specific file types or data structures.

The core of **freud** is analysis of periodic systems, which are represented through the `freud.box.Box` class. The `freud.box.Box` supports arbitrary triclinic systems for maximum flexibility, and is used throughout the package to ensure consistent treatment of these systems. The package's many methods are encapsulated in various *compute classes*, which perform computations and populate class attributes for access. Of particular note are the various computations based on nearest neighbor finding in order to characterize particle environments. Such methods are simplified and accelerated through a centralized neighbor finding interface defined in the `freud.locality.NeighborQuery` family of classes in the `freud.locality` module of **freud**.

7.2 Installation

7.2.1 Installing freud

The **freud** library can be installed via `conda` or `pip`, or compiled from source.

Install via conda

The code below will install **freud** from `conda-forge`.

```
conda install -c conda-forge freud
```

Install via pip

The code below will install **freud** from [PyPI](#).

```
pip install freud-analysis
```

Compile from source

The following are **required** for installing **freud**:

- [Python](#) (3.5+ required)
- [NumPy](#)
- [Intel Threading Building Blocks](#) (TBB)

The following are **optional** for installing **freud**:

- [Cython](#) (0.28+ required): The **freud** repository contains Cython-generated `*.cpp` files in the `freud/` directory that can be used directly. However, Cython is necessary if you wish to recompile these files.

For conda users, these requirements can be met by installing the following packages from the [conda-forge channel](#):

```
conda install -c conda-forge tbb tbb-devel numpy cython
```

The code that follows builds **freud** and installs it for all users (append `--user` if you wish to install it to your user site directory):

```
git clone --recurse-submodules https://github.com/glotzerlab/freud.git
cd freud
python setup.py install
```

You can also build **freud** in place so that you can run from within the folder:

```
# Run tests from the tests directory
python setup.py build_ext --inplace
```

Building **freud** in place has certain advantages, since it does not affect your Python behavior except within the **freud** directory itself (where **freud** can be imported after building). Additionally, due to limitations inherent to the distutils/setuptools infrastructure, building extension modules can only be parallelized using the `build_ext` subcommand of `setup.py`, not with `install`. As a result, it will be faster to manually run `build_ext` and then `install` (which normally calls `build_ext` under the hood anyway) the built packages. In general, the following options are available for `setup.py` in addition to the standard setuptools options (notes are included to indicate which options are only available for specific subcommands such as `build_ext`):

- PRINT-WARNINGS** Specify whether or not to print compilation warnings resulting from the build even if the build succeeds with no errors.
- ENABLE-CYTHON** Rebuild the Cython-generated C++ files. If there are any unexpected issues with compiling the C++ shipped with the build, using this flag may help. It is also necessary any time modifications are made to the Cython files.
- j** Compile in parallel. This affects both the generation of C++ files from Cython files and the subsequent compilation of the source files. In the latter case, this option controls the number of Python modules that will be compiled in parallel.
- TBB-ROOT** The root directory where TBB is installed. Useful if TBB is installed in a non-standard location or cannot be located by Python for some other reason. Note that this information can also be provided using

the environment variable `TBB_ROOT`. The options `--TBB-INCLUDE` and `--TBB-LINK` will take precedence over `--TBB-ROOT` if both are specified.

--TBB-INCLUDE The directory where the TBB headers (e.g. `tbb.h`) are located. Useful if TBB is installed in a non-standard location or cannot be located by Python for some other reason. Note that this information can also be provided using the environment variable `TBB_ROOT`. The options `--TBB-INCLUDE` and `--TBB-LINK` will take precedence over `--TBB-ROOT` if both are specified.

--TBB-LINK The directory where the TBB shared library (e.g. `libtbb.so` or `libtbb.dylib`) is located. Useful if TBB is installed in a non-standard location or cannot be located by Python for some other reason. Note that this information can also be provided using the environment variable `TBB_ROOT`. The options `--TBB-INCLUDE` and `--TBB-LINK` will take precedence over `--TBB-ROOT` if both are specified.

The following additional arguments are primarily useful for developers:

--COVERAGE Build the Cython files with coverage support to check unit test coverage.

--NTHREAD Specify the number of threads to allocate to compiling each module. This option is primarily useful for rapid development, particularly when all changes are in one module. While the `-j` option will not help parallelize this case, this option allows compilation of multiple source files belonging to the same module in parallel.

Note: **freud** makes use of git submodules. If you ever wish to manually update these, you can execute:

```
git submodule update --init
```

7.2.2 Unit Tests

The unit tests for **freud** are included in the repository and are configured to be run using the Python `unittest` library:

```
# Run tests from the tests directory
cd tests
python -m unittest discover .
```

Note that because **freud** is designed to require installation to run (i.e. it cannot be run directly out of the build directory), importing **freud** from the root of the repository will fail because it will try and import the package folder. As a result, unit tests must be run from outside the root directory if you wish to test the installed version of **freud**. If you want to run tests within the root directory, you can instead build **freud** in place:

```
# Run tests from the tests directory
python setup.py build_ext --inplace
```

This build will place the necessary files alongside the **freud** source files so that **freud** can be imported from the root of the repository.

7.2.3 Documentation

The documentation for **freud** is hosted online at [ReadTheDocs](#), but you may also build the documentation yourself:

Building the documentation

The following are **required** for building **freud** documentation:

- [Sphinx](#)

You can install sphinx using conda:

```
conda install sphinx
```

or pip:

```
pip install sphinx
```

To build the documentation, run the following commands in the source directory:

```
cd doc
make html
# Then open build/html/index.html
```

To build a PDF of the documentation (requires LaTeX and/or PDFLaTeX):

```
cd doc
make latexpdf
# Then open build/latex/freud.pdf
```

7.3 Quickstart Guide

Once you have *installed freud*, you can start using **freud** with any simulation data that you have on hand. As an example, we'll assume that you have run a simulation using the [HOOMD-blue](#) and used the `hoomd.dump.gsd` command to output the trajectory into a file `trajectory.gsd`. The [GSD file format](#) provides its own convenient Python file reader that offers access to data in the form of NumPy arrays, making it immediately suitable for calculation with **freud**. Many other file readers and data formats are supported, see [Reading Simulation Data for freud](#) for a full list and more examples.

We start by reading the data into a NumPy array:

```
import gsd.hoomd
traj = gsd.hoomd.open('trajectory.gsd', 'rb')
```

We can now immediately calculate important quantities. Here, we will compute the radial distribution function $g(r)$ using the `freud.density.RDF` compute class. Since the radial distribution function is in practice computed as a histogram, we must specify the histogram bin widths and the largest interparticle distance to include in our calculation. To do so, we simply instantiate the class with the appropriate parameters and then perform a computation on the given data:

```
import freud
rdf = freud.density.RDF(bins=50, r_max=5)
rdf.compute(system=traj[-1])
```

We can now access the data through properties of the `rdf` object.

```
r = rdf.bin_centers
y = rdf.rdf
```

Many classes in **freud** natively support plotting their data using *Matplotlib* <<https://matplotlib.org/>>:

```
import matplotlib as plt
fig, ax = plt.subplots()
rdf.plot(ax=ax)
```

You will note that in the above example, we computed $g(r)$ only using the final frame of the simulation trajectory, `traj[-1]`. However, in many cases, radial distributions and other similar quantities may be noisy in simulations due to the natural fluctuations present. In general, what we are interested in are *time-averaged* quantities once a system has equilibrated. To perform such a calculation, we can easily modify our original calculation to take advantage of **freud**'s *accumulation* features. To accumulate, just add the argument `reset=False` with a supported compute object (such as histogram-like computations). Assuming that you have some method for identifying the frames you wish to include in your sample, our original code snippet would be modified as follows:

```
import freud
rdf = freud.density.RDF(bins=50, r_max=5)
for frame in traj:
    rdf.compute(frame, reset=False)
```

You can then access the data exactly as we previously did. And that's it!

Now that you've seen a brief example of reading data and computing a radial distribution function, you're ready to learn more. If you'd like a complete walkthrough please see the [Tutorial](#). The tutorial walks through many of the core concepts in **freud** in greater detail, starting with the basics of the simulation systems we analyze and describing the details of the neighbor finding logic in **freud**. To see specific features of **freud** in action, look through the [Examples](#). More detailed documentation on specific classes and functions can be found in the [API documentation](#).

7.4 Tutorial

This tutorial provides a complete introduction to **freud**. Rather than attempting to touch on all features in **freud**, it focuses on common core concepts that will help understand how **freud** works with data and exposes computations to the user. The tutorial begins by introducing the fundamental concepts of periodic systems as implemented in **freud** and the concept of `Compute` classes, which constitute the primary API for performing calculations with **freud**. The tutorial then discusses the most common calculation performed in **freud**, finding neighboring points in periodic systems. The package's neighbor finding tools are tuned for high performance neighbor finding, which is what enables most of other calculations in **freud**, which typically involve characterizing local environments of points in some way. The next part of the tutorial discusses the role of histograms in **freud**, focusing on the common features and properties that all histograms share. Finally, the tutorial includes a few more complete demonstrations of using **freud** that should provide reasonable templates for use with almost any other features in **freud**.

7.4.1 Periodic Boundary Conditions

The central goal of **freud** is the analysis of simulations performed in periodic boxes. Periodic boundary conditions are ubiquitous in simulations because they permit the simulation of quasi-infinite systems with minimal computational effort. As long as simulation systems are sufficiently large, i.e. assuming that points in the system experience correlations over length scales substantially smaller than the system length scale, periodic boundary conditions ensure that the system appears effectively infinite to all points.

In order to consistently define the geometry of a simulation system with periodic boundaries, **freud** defines the `freud.box.Box` class. The class encapsulates the concept of a triclinic simulation box in a right-handed coordinate system. Triclinic boxes are defined as parallelepipeds: three-dimensional polyhedra where every face is a parallelogram. In general, any such box can be represented by three distinct, linearly independent box vectors. Enforcing the requirement of right-handedness guarantees that the box can be represented by a matrix of the form

$$\mathbf{h} = \begin{pmatrix} L_x & xyL_y & xzL_z \\ 0 & L_y & yzL_z \\ 0 & 0 & L_z \end{pmatrix}$$

where each column is one of the box vectors.

As such, the box is characterized by six parameters: the box vector lengths L_x , L_y , and L_z , and the tilt factors xy , xz , and yz . The tilt factors are directly related to the angles between the box vectors. All computations in **freud** are built around this class, ensuring that they naturally handle data from simulations conducted in non-cubic systems. There is also native support for two-dimensional (2D) systems when setting $L_z = 0$.

Boxes can be constructed in a variety of ways. For simple use-cases, one of the factory functions of the `freud.box.Box` provides the easiest possible interface:

```
# Make a 10x10 square box (for 2-dimensional systems).
freud.box.Box.square(10)

# Make a 10x10x10 cubic box.
freud.box.Box.cube(10)
```

For more complex use-cases, the `freud.box.Box.from_box()` method provides an interface to create boxes from any object that can easily be interpreted as a box.

```
# Create a 10x10 square box from a list of two items.
freud.box.Box.from_box([10, 10])

# Create a 10x10x10 cubic box from a list of three items.
freud.box.Box.from_box([10, 10, 10])

# Create a triclinic box from a list of six items (including tilt factors).
freud.box.Box.from_box([10, 5, 2, 0.1, 0.5, 0.7])

# Create a triclinic box from a dictionary.
freud.box.Box.from_box(dict(Lx=8, Ly=7, Lz=10, xy=0.5, xz=0.7, yz=0.2))

# Directly call the constructor.
freud.box.Box(Lx=8, Ly=7, Lz=10, xy=0.5, xz=0.7, yz=0.2, dimensions=3)
```

More examples on how boxes can be created may be found in the API documentation of the `Box` class.

Note: All **freud** boxes are centered at the origin, so for a given box the range of possible positions is $[-L/2, L/2)$.

7.4.2 Compute Classes

Calculations in **freud** are built around the concept of `Compute` classes, Python objects that encode a given method and expose it through a `compute` method. In general, these methods operate on a system composed of a triclinic box and a NumPy array of particle positions. The box can be provided as any object that can be interpreted as a **freud** box (as demonstrated in the examples above). We can look at the `freud.order.Hexatic` order parameter calculator as an example:

```
import freud
positions = ... # Read positions from trajectory file.
op = freud.order.Hexatic(k=6)
op.compute(
    system=({'Lx': 5, 'Ly': 5, 'dimensions': 2}, positions),
    neighbors=dict(r_max=3)
)

# Plot the value of the order parameter.
from matplotlib import pyplot as plt
plt.hist(np.absolute(op.particle_order))
```

Here, we are calculating the hexatic order parameter, then using Matplotlib to plot. The `freud.order.Hexatic` class constructor accepts a single argument `k`, which represents the periodicity of the calculation. If you're unfamiliar with this order parameter, the most important piece of information here is that many compute methods in **freud** require parameters that are provided when the `Compute` class is constructed.

To calculate the order parameter we call `compute`, which takes two arguments, a `tuple` (`box`, `points`) and a `dict`. We first focus on the first argument. The `box` is any object that can be coerced into a `freud.box.Box` as described in the previous section; in this case, we use a dictionary to specify a square (2-dimensional) box. The `points` must be anything that can be coerced into a 2-dimensional NumPy array of shape $(N, 3)$. In general, the points may be provided as anything that can be interpreted as an $N \times 3$ list of positions; for more details on valid inputs here, see `numpy.asarray()`. Note that because the hexatic order parameter is designed for two-dimensional systems, the points must be provided of the form $[x, y, 0]$ (i.e. the z -component must be 0). We'll go into more detail about the (`box`, `points`) tuple soon, but for now, it's sufficient to just think of it as specifying the system of points we want to work with.

Now let's return to the `neighbors` argument to `compute`, which is a dictionary is used to determine which particle neighbors to use. Many computations in **freud** (such as the hexatic order parameter) involve the bonds in the system (for example, the average length of bonds or the average number of bonds a given point has). However, the concept of a bond is sufficiently variable between different calculations; for instance, should points be considered bonded if they are within a certain distance of each other? Should every point be considered bonded to a fixed number of other points?

To accommodate this variability, **freud** offers a very general framework by which bonds can be specified, and we'll go into more details in the [next section](#). In the example above, we've simply informed the `Hexatic` class that we want it to define bonds as pairs of particles that are less than 3 distance units apart. We then access the computed order parameter as `op.particle_order` (we use `np.absolute()` because the output is a complex number and we just want to see its magnitude).

Accessing Computed Properties

In general, `Compute` classes expose their calculations using [properties](#). Any parameters to the `Compute` object (e.g. `k` in the above example) can typically be accessed as soon as the object is constructed:

```
op = freud.order.Hexatic(k=6)
op.k
```

Computed quantities can also be accessed in a similar manner, but only after the `compute` method is called. For example:

```
op = freud.order.Hexatic(k=6)

# This will raise an exception.
op.particle_order

op.compute(
    system=({'Lx': 5, 'Ly': 5, 'dimensions': 2}, positions),
    neighbors=dict(r_max=3)
)

# Now you can access this.
op.particle_order
```

Note: Most (but not all) of **freud**'s `Compute` classes are Python wrappers around high-performance implementations in C++. As a result, none of the data or the computations is actually stored in the Python object. Instead, the Python object just stores an instance of the C++ object that actually owns all its data, performs calculations, and returns computed quantities to the user. Python properties provide a nice way to hide this logic so that the Python code involves just a few lines.

Compute objects is that they can be used many times to calculate quantities, and the most recently calculated output can be accessed through the property. If you need to perform a series of calculations and save all the data, you can also easily do that:

```
# Recall that lists of length 2 automatically convert to 2D freud boxes.
box = [5, 5]

op = freud.order.Hexatic(k=6)

# Assuming that we have a list of Nx3 NumPy arrays that represents a
# simulation trajectory, we can loop over it and calculate the order
# parameter values in sequence.
trajectory = ... # Read trajectory file into a list of positions by frame.
hexatic_values = []
for points in trajectory:
    op.compute(system=(box, points), neighbors=dict(r_max=3))
    hexatic_values.append(op.particle_order)
```

To make using **freud** as simple as possible, all `Compute` classes are designed to return `self` when `compute` is called. This feature enables a very concise *method-chaining* idiom in **freud** where computed properties are accessed immediately:

```
particle_order = freud.order.Hexatic(k=6).compute(
    system=(box, points)).particle_order
```

7.4.3 Finding Neighbors

Now that you’ve been introduced to the basics of interacting with **freud**, let’s dive into the central feature of **freud**: efficiently and flexibly finding neighbors in periodic systems.


Problem Statement

Neighbor-Based Calculations

As discussed in *the previous section*, a central task in many of the computations in **freud** is finding particles’ neighbors. These calculations typically only involve a limited subset of a particle’s neighbors that are defined as characterizing its local environment. This requirement is analogous to the force calculations typically performed in molecular dynamics simulations, where a cutoff radius is specified beyond which pair forces are assumed to be small enough to neglect. Unlike in simulation, though, many analyses call for different specifications than simply selecting all points within a certain distance.

An important example is the calculation of order parameters, which can help characterize phase transitions. Such parameters can be highly sensitive to the precise way in which neighbors are selected. For instance, if a hard distance cutoff is imposed in finding neighbors for the hexatic order parameter, a particle may only be found to have five neighbors when it actually has six neighbors except the last particle is slightly outside the cutoff radius. To accomodate such differences in a flexible manner, **freud** allows users to specify neighbors in a variety of ways.

Finding Periodic Neighbors



Finding neighbors in periodic systems is significantly more challenging than in aperiodic systems. To illustrate the difference, consider the figure above, where the black dashed line indicates the boundaries of the system. If this system were aperiodic, the three nearest neighbors for point 1 would be points 5, 6, and 7. However, due to periodicity, point 2 is actually closer to point 1 than any of the others if you consider moving straight through the top (or equivalently, the bottom) boundary. Although many tools provide efficient implementations of algorithms for finding neighbors in aperiodic systems, they seldom generalize to periodic systems. Even more rare is the ability to work not just in *cubic* periodic systems, which are relatively tractable, but in arbitrary triclinic geometries as described in *Periodic Boundary Conditions*. This is precisely the type of calculation **freud** is designed for.

Neighbor Querying

To understand how `Compute` classes find neighbors in **freud**, it helps to start by learning about **freud**'s neighbor finding classes directly. Note that much more detail on this topic is available in the [Query API](#) topic guide; in this section we will restrict ourselves to a higher-level overview. For our demonstration, we will make use of the `freud.locality.AABBQuery` class, which implements one fast method for periodic neighbor finding. The primary mode of interfacing with this class (and other neighbor finding classes) is through the `query` interface.

```
import numpy as np
import freud

# As an example, we randomly generate 100 points in a 10x10x10 cubic box.
L = 10
num_points = 100

# We shift all points into the expected range for freud.
points = np.random.rand(num_points)*L - L/2
box = freud.box.Box.cube(L)
aq = freud.locality.AABBQuery(box, points)

# Now we generate a smaller sample of points for which we want to find
# neighbors based on the original set.
query_points = np.random.rand(num_points/10)*L - L/2
distances = []

# Here, we ask for the 4 nearest neighbors of each point in query_points.
for bond in aq.query(query_points, dict(num_neighbors=4)):
    # The returned bonds are tuples of the form
    # (query_point_index, point_index, distance). For instance, a bond
    # (1, 3, 0.2) would indicate that points[3] was one of the 4 nearest
    # neighbors for query_points[1], and that they are separated by a
    # distance of 0.2
    # (i.e. np.linalg.norm(query_points[1] - points[3]) == 2).
    distances.append(bond[2])

avg_distance = np.mean(distances)
```

Let's dig into this script a little bit. Our first step is creating a set of 100 points in a cubic box. Note that the shifting done in the code above could also be accomplished using the `Box.wrap` method like so: `box.wrap(np.random.rand(num_points)*L)`. The result would appear different, because if plotted without considering periodicity, the points would range from $-L/2$ to $L/2$ rather than from 0 to L . However, these two sets of points would be equivalent in a periodic system.

We then generate an additional set of `query_points` and ask for neighbors using the `query` method. This function accepts two arguments: a set of points, and a `dict` of **query arguments**. Query arguments are a central concept in **freud** and represent a complete specification of the set of neighbors to be found. In general, the most common forms of queries are those requesting either a fixed number of neighbors, as in the example above, or those requesting all neighbors within a specific distance. For example, if we wanted to rerun the above example but instead find all bonds of length less than or equal to 2, we would simply replace the for loop above with:

```
for bond in aq.query(query_points, dict(r_max=2)):
    distances.append(bond[2])
```

Query arguments constitute a powerful method for specifying a query request. Many query arguments may be combined for more specific purposes. A common use-case is finding all neighbors within a single set of points (i.e. setting `query_points = points` in the above example). In this situation, however, it is typically not useful for a point to find itself as a neighbor since it is trivially the closest point to itself and falls within any cutoff radius. To avoid this,

we can use the `exclude_ii` query argument:

```
query_points = points
for bond in aq.query(query_points, dict(num_neighbors=4, exclude_ii=True)):
    pass
```

The above example will find the 4 nearest neighbors to each point, excepting the point itself. A complete description of valid query arguments can be found in [Query API](#).

Neighbor Lists

Query arguments provide a simple but powerful language with which to express neighbor finding logic. Used in the manner shown above, `query` can be used to express many calculations in a very natural, Pythonic way. By itself, though, the API shown above is somewhat restrictive because the output of `query` is a [generator](#). If you aren't familiar with generators, the important thing to know is that they can be looped over, *but only once*. Unlike objects like lists, which you can loop over as many times as you like, once you've looped over a generator once, you can't start again from the beginning.

In the examples above, this wasn't a problem because we simply iterated over the bonds once for a single calculation. However, in many practical cases we may need to reuse the set of neighbors multiple times. A simple solution would be to simply store the bonds into a list as we loop over them. However, because this is such a common use-case, **freud** provides its own containers for bonds: the `freud.locality.NeighborList`.

Queries can easily be used to generate `NeighborList` objects using their `toNeighborList` method:

```
query_result = aq.query(query_points, dict(num_neighbors=4, exclude_ii))
nlist = query_result.toNeighborList()
```

The resulting object provides a persistent container for bond data. Using `NeighborLists`, our original example might instead look like this:

```
import numpy as np
import freud

L = 10
num_points = 100

points = np.random.rand(num_points)*L - L/2
box = freud.box.Box.cube(L)
aq = freud.locality.AABBQuery(box, points)

query_points = np.random.rand(num_points/10)*L - L/2
distances = []

# Here, we ask for the 4 nearest neighbors of each point in query_points.
query_result = aq.query(query_points, dict(num_neighbors=4)):
nlist = query_result.toNeighborList()
for (i, j) in nlist:
    # Note that we have to wrap the bond vector before taking the norm;
    # this is the simplest way to compute distances in a periodic system.
    distances.append(np.linalg.norm(box.wrap(query_points[i] - points[j])))

avg_distance = np.mean(distances)
```

Note that in the above example we looped directly over the `nlist` and recomputed distances. However, the `query_result` contained information about distances: here's how we access that through the `nlist`:

```
assert np.all(nlist.distances == distances)
```

The indices are also accessible through properties, or through a NumPy-like slicing interface:

```
assert np.all(nlist.query_point_indices == nlist[:, 0])
assert np.all(nlist.point_indices == nlist[:, 1])
```

Note that the `query_points` are always in the first column, while the `points` are in the second column. `freud.locality.NeighborList` objects also store other properties; for instance, they may assign different weights to different bonds. This feature can be used by, for example, `freud.order.Steinhardt`, which is typically used for calculating [Steinhardt order parameters](#), a standard tool for characterizing crystalline order. When provided appropriately weighted neighbors, however, the class instead computes [Minkowski structure metrics](#), which are much more sensitive measures that can differentiate a wider array of crystal structures.

7.4.4 Pair Computations

Some computations in **freud** do not depend on bonds at all. For example, `freud.density.GaussianDensity` creates a “continuous equivalent” of a system of points by placing normal distributions at each point’s location to smear out its position, then summing the value of these distributions at a set of fixed grid points. This calculation can be quite useful because it allows the application of various analysis tools like fast Fourier transforms, which require regular grids. For the purposes of this tutorial, however, the importance of this class is that it is an example of a calculation where neighbors are unimportant: the calculation is performed on a per-point basis only.

The much more common pattern in **freud**, though, is that calculations involve the local neighborhoods of points. To support efficient, flexible computations of such quantities, various `Compute` classes essentially expose the same API as the query interface demonstrated in the previous section. These `PairCompute` classes are designed to mirror the querying functionality of **freud** as closely as possible.

As an example, let’s consider `freud.density.LocalDensity`, which calculates the density of points in the local neighborhood of each point. Adapting our code from the [previous section](#), the simplest usage of this class would be as follows:

```
import numpy as np
import freud

L = 10
num_points = 100

points = np.random.rand(num_points)*L - L/2
box = freud.box.Box.cube(L)

# r_max specifies how far to search around each point for neighbors
r_max = 2

# For systems where the points represent, for instance, particles with a
# specific size, the diameter is used to add fractional volumes for
# neighbors that would be overlapping the sphere of radius r_max around
# each point.
diameter = 0.001

ld = freud.density.LocalDensity(r_max, diameter)
ld.compute(system=(box, points))

# Access the density.
ld.density
```

Using the same example system we've been working with so far, we've now calculated an estimate for the number of points in the neighborhood of each point. Since we already told the computation how far to search for neighbors based on `r_max`, all we had to do was pass a `tuple` (`box`, `points`) to compute indicate where the points were located.

Binary Systems

Imagine that instead of a single set of points, we actually had two different types of points and we were interested in finding the density of one set of points in the vicinity of the other. In that case, we could modify the above calculation as follows:

```
import numpy as np
import freud
L = 10
num_points = 100
points = np.random.rand(num_points)*L - L/2
query_points = np.random.rand(num_points/10)*L - L/2

r_max = 2
diameter = 0.001

ld = freud.density.LocalDensity(r_max, diameter)
ld.compute(system=(box, points), query_points=query_points)

# Access the density.
ld.density
```

The choice of names here is suggestive of exactly what this calculation is now doing. Internally, `freud.density.LocalDensity` will search for all points that are within the cutoff distance `r_max` of every `query_point` (essentially using the query interface we introduced previously) and use that to calculate `ld.density`. Note that this means that `ld.density` now contains densities for every `query_point`, i.e. it is of length 10, not 100. Moreover, recall that one of the features of the querying API is the specification of whether or not to count particles as their own neighbors. `PairCompute` classes will attempt to make an intelligent determination of this for you; if you do not pass in a second set of `query_points`, they will assume that you are computing with a single set of points and automatically exclude self-neighbors, but otherwise all neighbors will be included.

So far, we have included all points within a fixed radius; however, one might instead wish to consider the density in some shell, such as the density between 1 and 2 distance units away. To address this need, you could simply adapt the call to compute above as follows:

```
ld.compute(system=(box, points), query_points=query_points,
           neighbors=dict(r_max=2, r_min=1))
```

The `neighbors` argument to `PairCompute` classes allows users to specify arbitrary query arguments, making it possible to easily modify **freud** calculations on-the-fly. The `neighbors` argument is actually more general than query arguments you've seen so far: if query arguments are not precise enough to specify the exact set of neighbors you want to compute with, you can instead provide a `NeighborList` directly

```
ld.compute(system=(box, points), query_points=query_points,
           neighbors=nlist)
```

This feature allows users essentially arbitrary flexibility to specify the bonds that should be included in any bond-based computation. A common use-case for this is constructing a `NeighborList` using `freud.locality.Voronoi`; Voronoi constructions provide a powerful alternative method of defining neighbor relationships that can improve the accuracy and robustness of certain calculations in **freud**.

You may have noticed in the last example that all the arguments are specified using keyword arguments. As the previous examples have attempted to show, the `query_points` argument defines a second set of points to be used

when performing calculations on binary systems, while the `neighbors` argument is how users can specify which neighbors to consider in the calculation.

The `system` argument is what, to this point, we have been specifying as a `tuple` (`box`, `points`). However, we don't have to use this tuple. Instead, we can pass in any `freud.locality.NeighborQuery`, the central class in **freud**'s querying infrastructure. In fact, you've already seen examples of `freud.locality.NeighborQuery`: the `freud.locality.AABBQuery` object that we originally used to find neighbors. There are also a number of other input types that can be converted via `freud.locality.NeighborQuery.from_system()`, see also *Reading Simulation Data for freud*. Since these objects all contain a `freud.box.Box` and a set of points, they can be directly passed to computations:

```
aq = freud.locality.AABBQuery(box, points)
ld.compute(system=aq, query_points=query_points, neighbors=nlist)
```

For more information on why you might want to use `freud.locality.NeighborQuery` objects instead of the tuples, see *Using freud Efficiently*. For now, just consider this to be a way in which you can simplify your calls to many **freud** computes in one script by storing (`box`, `points`) into another objects.

You've now covered the most important information needed to use **freud**! To recap, we've discussed how **freud** handles periodic boundary conditions, the structure and usage of `Compute` classes, and methods for finding and performing calculations with pairs of neighbors. For more detailed information on specific methods in **freud**, see the *Examples* page or look at the API documentation for specific modules.

7.5 Examples

Examples are provided as [Jupyter](#) notebooks in a separate [freud-examples](#) repository. These notebooks may be launched [interactively on Binder](#) or downloaded and run on your own system. Visualization of data is done via [Matplotlib](#) and [Bokeh](#), unless otherwise noted.

7.5.1 Key concepts

There are a few critical concepts, algorithms, and data structures that are central to all of **freud**. The `freud.box.Box` class defines the concept of a periodic simulation box, and the `freud.locality` module defines methods for finding nearest neighbors of particles. Since both of these are used throughout **freud**, we recommend reading the *Tutorial* first, before delving into the workings of specific **freud** analysis modules.

freud.box.Box

In this notebook, we demonstrate the basic features of the `Box` class, including wrapping particles back into the box under periodic boundary conditions. For more information, see the [introduction to Periodic Boundary Conditions](#) and the [freud.box documentation](#).

Creating a Box object

Boxes may be constructed explicitly using all arguments. Such construction is useful when performing *ad hoc* analyses involving custom boxes. In general, boxes are assumed to be 3D and `orthorhombic` unless otherwise specified.

```
[1]: import freud.box

# All of the below examples are valid boxes.
box = freud.box.Box(Lx=5, Ly=6, Lz=7, xy=0.5, xz=0.6, yz=0.7, is2D=False)
box = freud.box.Box(1, 3, 2, 0.3, 0.9)
box = freud.box.Box(5, 6, 7)
box = freud.box.Box(5, 6, is2D=True)
box = freud.box.Box(5, 6, xy=0.5, is2D=True)
```

From another Box object

The simplest case is simply constructing one freud box from another.

Note that all forms of creating boxes aside from the explicit method above use methods defined within the Box class rather than attempting to overload the constructor itself.

```
[2]: box = freud.box.Box(1, 2, 3)
box2 = freud.box.Box.from_box(box)
print("The original box: \n\t{}".format(box))
print("The copied box: \n\t{}\n".format(box2))

# Boxes are always copied by value, not by reference
box.Lx = 5
print("The original box is modified: \n\t{}".format(box))
print("The copied box is not: \n\t{}\n".format(box2))

# Note, however, that box assignment creates a new object that
# still points to the original box object, so modifications to
# one are visible on the other.
box3 = box2
print("The new copy: \n\t{}".format(box3))
box2.Lx = 2
print("The new copy after the original is modified: \n\t{}".format(box3))
print("The modified original box: \n\t{}".format(box2))

The original box:
    freud.box.Box(Lx=1.0, Ly=2.0, Lz=3.0, xy=0.0, xz=0.0, yz=0.0, is2D=False)
The copied box:
    freud.box.Box(Lx=1.0, Ly=2.0, Lz=3.0, xy=0.0, xz=0.0, yz=0.0, is2D=False)

The original box is modified:
    freud.box.Box(Lx=5.0, Ly=2.0, Lz=3.0, xy=0.0, xz=0.0, yz=0.0, is2D=False)
The copied box is not:
    freud.box.Box(Lx=1.0, Ly=2.0, Lz=3.0, xy=0.0, xz=0.0, yz=0.0, is2D=False)

The new copy:
    freud.box.Box(Lx=1.0, Ly=2.0, Lz=3.0, xy=0.0, xz=0.0, yz=0.0, is2D=False)
The new copy after the original is modified:
    freud.box.Box(Lx=2.0, Ly=2.0, Lz=3.0, xy=0.0, xz=0.0, yz=0.0, is2D=False)
The modified original box:
    freud.box.Box(Lx=2.0, Ly=2.0, Lz=3.0, xy=0.0, xz=0.0, yz=0.0, is2D=False)
```

From a matrix

A box can be constructed directly from the box matrix representation described above using the `Box.from_matrix` method.

```
[3]: # Matrix representation. Note that the box vectors must represent
# a right-handed coordinate system! This translates to requiring
# that the matrix be upper triangular.
box = freud.box.Box.from_matrix([[1, 1, 0], [0, 1, 0.5], [0, 0, 0.5]])
print("This is a 3D box from a matrix: \n\t{}\n".format(box))

# 2D box
box = freud.box.Box.from_matrix([[1, 0, 0], [0, 1, 0], [0, 0, 0]])
print("This is a 2D box from a matrix: \n\t{}\n".format(box))

# Automatic matrix detection using from_box
box = freud.box.Box.from_box([[1, 1, 0], [0, 1, 0.5], [0, 0, 0.5]])
print("The box matrix was automatically detected: \n\t{}\n".format(box))

# Boxes can be numpy arrays as well
import numpy as np
box = freud.box.Box.from_box(np.array([[1, 1, 0], [0, 1, 0.5], [0, 0, 0.5]]))
print("Using a 3x3 numpy array: \n\t{}\n".format(box))

This is a 3D box from a matrix:
    freud.box.Box(Lx=1.0, Ly=1.0, Lz=0.5, xy=1.0, xz=0.0, yz=1.0, is2D=False)

This is a 2D box from a matrix:
    freud.box.Box(Lx=1.0, Ly=1.0, Lz=0.0, xy=0.0, xz=0.0, yz=0.0, is2D=True)

The box matrix was automatically detected:
    freud.box.Box(Lx=1.0, Ly=1.0, Lz=0.5, xy=1.0, xz=0.0, yz=1.0, is2D=False)

Using a 3x3 numpy array:
    freud.box.Box(Lx=1.0, Ly=1.0, Lz=0.5, xy=1.0, xz=0.0, yz=1.0, is2D=False)
```

From a namedtuple or dict

A box can be also be constructed from any object that provides an attribute for `Lx`, `Ly`, `Lz`, `xy`, `xz`, and `yz` (or some subset), such as a namedtuple. This method is suitable for passing in box objects constructed by some other program, for example.

```
[4]: from collections import namedtuple
MyBox = namedtuple('mybox', ['Lx', 'Ly', 'Lz', 'xy', 'xz', 'yz'])

box = freud.box.Box.from_box(MyBox(Lx=5, Ly=3, Lz=2, xy=0, xz=0, yz=0))
print("Box from named tuple: \n\t{}\n".format(box))

box = freud.box.Box.from_box(MyBox(Lx=5, Ly=3, Lz=0, xy=0, xz=0, yz=0))
print("2D Box from named tuple: \n\t{}\n".format(box))

Box from named tuple:
    freud.box.Box(Lx=5.0, Ly=3.0, Lz=2.0, xy=0.0, xz=0.0, yz=0.0, is2D=False)

2D Box from named tuple:
    freud.box.Box(Lx=5.0, Ly=3.0, Lz=0.0, xy=0.0, xz=0.0, yz=0.0, is2D=True)
```

Similarly, construction is also possible using any object that supports key-value indexing, such as a dict.

```
[5]: box = freud.box.Box.from_box(dict(Lx=5, Ly=3, Lz=2))
print("Box from dict: \n\t{}".format(box))

Box from dict:
    freud.box.Box(Lx=5.0, Ly=3.0, Lz=2.0, xy=0.0, xz=0.0, yz=0.0, is2D=False)
```

From a list

Finally, boxes can be constructed from any simple iterable that provides the elements in the correct order.

```
[6]: box = freud.box.Box.from_box((5, 6, 7, 0.5, 0, 0.5))
print("Box from tuple: \n\t{}\n".format(box))

box = freud.box.Box.from_box([5, 6])
print("2D Box from list: \n\t{}".format(box))

Box from tuple:
    freud.box.Box(Lx=5.0, Ly=6.0, Lz=7.0, xy=0.5, xz=0.0, yz=0.5, is2D=False)

2D Box from list:
    freud.box.Box(Lx=5.0, Ly=6.0, Lz=0.0, xy=0.0, xz=0.0, yz=0.0, is2D=True)
```

Convenience APIs

We also provide convenience constructors for common geometries, namely square (2D) and cubic (3D) boxes.

```
[7]: cube_box = freud.box.Box.cube(L=5)
print("Cubic Box: \n\t{}\n".format(cube_box))

square_box = freud.box.Box.square(L=5)
print("Square Box: \n\t{}\n".format(square_box))

Cubic Box:
    freud.box.Box(Lx=5.0, Ly=5.0, Lz=5.0, xy=0.0, xz=0.0, yz=0.0, is2D=False)

Square Box:
    freud.box.Box(Lx=5.0, Ly=5.0, Lz=0.0, xy=0.0, xz=0.0, yz=0.0, is2D=True)
```

Export

If you want to export or display the box, you can export box objects into their matrix or dictionary representations, which provide completely specified descriptions of the box.

```
[8]: cube_box = freud.box.Box.cube(L=5)
cube_box.to_matrix()

[8]: array([[5., 0., 0.],
           [0., 5., 0.],
           [0., 0., 5.]])

[9]: cube_box.to_dict()
```

```
[9]: {'Lx': 5.0,
      'Ly': 5.0,
      'Lz': 5.0,
      'xy': 0.0,
      'xz': 0.0,
      'yz': 0.0,
      'dimensions': 3}
```

Using boxes

Given a freud box object, you can query it for all its attributes.

```
[10]: box = freud.box.Box.from_matrix([[10, 0, 0], [0, 10, 0], [0, 0, 10]])
print("L_x = {}, L_y = {}, L_z = {}, xy = {}, xz = {}, yz = {}".format(
    box.Lx, box.Ly, box.Lz, box.xy, box.xz, box.yz))

print("The length vector: {}".format(box.L))
print("The inverse length vector: ({:1.2f}, {:1.2f}, {:1.2f})".format(*[L for L in_
↪box.L_inv]))

L_x = 10.0, L_y = 10.0, L_z = 10.0, xy = 0.0, xz = 0.0, yz = 0.0
The length vector: [10. 10. 10.]
The inverse length vector: (0.10, 0.10, 0.10)
```

Boxes also support converting between fractional and absolute coordinates.

Note that the origin in real coordinates is defined at the center of the box. This means the fractional coordinate range $[0, 1]$ maps onto $[-L/2, L/2]$, not $[0, L]$.

```
[11]: # Convert from fractional to absolute coordinates.
print(box.make_absolute([[0, 0, 0], [0.5, 0.5, 0.5], [0.8, 0.3, 1]]))
print()

# Convert from fractional to absolute coordinates and back.
print(box.make_fractional(box.make_absolute([[0, 0, 0], [0.5, 0.5, 0.5], [0.8, 0.3,
↪1]])))

[[-5. -5. -5.]
 [ 0.  0.  0.]
 [ 3. -2.  5.]]

[[0.  0.  0. ]
 [0.5 0.5 0.5]
 [0.8 0.3 1.  ]]
```


Finally (and most critically for enforcing periodicity), boxes support wrapping vectors from outside the box into the box. The concept of periodicity and box wrapping is most easily demonstrated visually.

```
[12]: # Construct the box and get points for plotting
Lx = Ly = 10
xy = 0.5
box = freud.box.Box.from_matrix([[Lx, xy*Ly, 0], [0, Ly, 0], [0, 0, 0]])
box.plot()
```

```
[12]: <matplotlib.axes._subplots.AxesSubplot at 0x7f2729d20518>
```

With periodic boundary conditions, what this actually represents is an infinite set of these boxes tiling space. For example, you can locally picture this box as surrounding by a set of identical boxes.

```
[13]: %matplotlib inline
import matplotlib.pyplot as plt
fig, ax = plt.subplots(figsize=(9, 6))
box.plot(ax=ax)
for image in [[-1, 0, 0], [1, 0, 0], [0, -1, 0], [0, 1, 0]]:
    box.plot(ax=ax, image=image, linestyle='dashed', color='gray')
plt.show()
```



Any particles in the original box will also therefore be seen as existing in all the neighboring boxes.


```
[14]: np.random.seed(0)
fractional_coords = np.zeros((5, 3))
fractional_coords[:, :2] = np.random.rand(5, 2)
particles = box.make_absolute(fractional_coords)
```

```
[15]: fig, ax = plt.subplots(figsize=(9, 6))

# Plot the points in the original box.
box.plot(ax=ax)
ax.scatter(particles[:, 0], particles[:, 1])

# Plot particles in each of the periodic boxes.
for image in [[-1, 0, 0], [1, 0, 0], [0, -1, 0], [0, 1, 0]]:
    box.plot(ax=ax, image=image, linestyle='dashed', color='gray')
    particle_images = box.unwrap(particles, image)
    ax.scatter(particle_images[:, 0], particle_images[:, 1])

plt.show()
```



Box wrapping takes points in the periodic images of a box, and brings them back into the original box. In this context, that means that if we apply wrap to each of the sets of particles plotted above, they should all overlap.


```
[16]: fig, axes = plt.subplots(2, 2, figsize=(12, 8))
      images = [[-1, 0, 0], [1, 0, 0], [0, -1, 0], [0, 1, 0]]

      # Plot particles in each of the periodic boxes.
      for ax, image in zip(axes.flatten(), images):
          box.plot(ax=ax)
          box.plot(ax=ax, image=image, linestyle='dashed', color='gray')
          particle_images = box.unwrap(particles, image)
          ax.scatter(particle_images[:, 0],
                     particle_images[:, 1],
                     label='Images')

          wrapped_particle_images = box.wrap(particle_images)
          ax.scatter(wrapped_particle_images[:, 0],
                     wrapped_particle_images[:, 1],
                     label='Wrapped')

          ax.tick_params(axis="both", which="both", labelsz=14)
          ax.legend()

      plt.show()
```




freud.locality.PeriodicBuffer: Unit Cell RDF

The `PeriodicBuffer` class is meant to replicate points beyond a single image while respecting box periodicity. This example demonstrates how we can use this to compute the radial distribution function from a sample crystal's unit cell.

```
[1]: %matplotlib inline
import freud
import numpy as np
import matplotlib.pyplot as plt
```

Here, we create a box to represent the unit cell and put two points inside. We plot the box and points below.

```
[2]: box = freud.box.Box(Lx=2, Ly=2, xy=np.sqrt(1/3), is2D=True)
points = np.array([[-0.5, -0.5, 0], [0.5, 0.5, 0]])
system = freud.AABBQuery(box, points)
system.plot(ax=plt.gca())
plt.show()
```




Next, we create a `PeriodicBuffer` instance and have it compute the “buffer” points that lie outside the first periodicity. These positions are stored in the `buffer_points` attribute. The corresponding `buffer_ids` array gives a mapping from the index of the buffer particle to the index of the particle it was replicated from, in the original array of points. Finally, the `buffer_box` attribute returns a larger box, expanded from the original box to contain the replicated points.

```
[3]: pbuff = freud.locality.PeriodicBuffer()
      pbuff.compute(system=(box, points), buffer=6, images=True)
      print(pbuff.buffer_points[:10], '...')

[[ 0.65470022  1.5         0.         ]
 [ 1.80940032  3.5         0.         ]
 [ 2.96410179  5.5         0.         ]
 [-3.96410131 -6.5         0.         ]
 [-2.80940104 -4.49999952  0.         ]
 [-1.65470016 -2.50000048  0.         ]
 [ 1.50000024 -0.5         0.         ]
 [ 2.65470076  1.5         0.         ]
 [ 3.80940032  3.5         0.         ]
 [ 4.96410179  5.5         0.         ]] ...
```


Below, we plot the original unit cell and the replicated buffer points and buffer box.

```
[4]: system.plot(ax=plt.gca())
      plt.scatter(pbuff.buffer_points[:, 0], pbuff.buffer_points[:, 1])
      pbuff.buffer_box.plot(ax=plt.gca(), linestyle='dashed', color='gray')
      plt.show()
```



Finally, we can plot the radial distribution function (RDF) of this replicated system, using a value of `r_max` that is larger than the size of the original box. This allows us to see the interaction of the original points with their replicated neighbors from the buffer.

```
[5]: rdf = freud.density.RDF(bins=250, r_max=5)
rdf.compute(system=(pbuff.buffer_box, pbuff.buffer_points), query_points=points)
rdf.plot(ax=plt.gca())
plt.show()
```



freud.locality.Voronoi


The `freud.locality.Voronoi` class uses `voro++` to compute the [Voronoi diagram](#) of a set of points, **while respecting periodic boundary conditions** (which are not handled by `scipy.spatial.Voronoi`, [documentation](#)).

These examples are two-dimensional (with $z = 0$ for all particles) for simplicity, but the `Voronoi` class works for both 2D and 3D data.

```
[1]: import numpy as np
import freud
import matplotlib
import matplotlib.pyplot as plt
```

First, we generate some sample points.

```
[2]: points = np.array([
    [-0.5, -0.5, 0],
    [0.5, -0.5, 0],
    [-0.5, 0.5, 0],
    [0.5, 0.5, 0]])
plt.scatter(points[:, 0], points[:, 1])
plt.title('Points')
plt.xlim((-1, 1))
plt.ylim((-1, 1))
plt.gca().set_aspect('equal')
plt.show()
```



Now we create a box and a `Voronoi` compute object.

```
[3]: L = 2
box = freud.box.Box.square(L)
voro = freud.locality.Voronoi()
```


Next, we use the `compute` method to determine the Voronoi polytopes (cells) and the `polytopes` property to return their coordinates. Note that we use `freud`'s *method chaining* here, where a `compute` method returns the compute object.

```
[4]: cells = voro.compute((box, points)).polytopes
print(cells)
```

```
[array([-1., -1.,  0.],
       [ 0., -1.,  0.],
       [ 0.,  0.,  0.],
       [-1.,  0.,  0.]), array([[ 0., -1.,  0.],
       [ 1., -1.,  0.],
       [ 1.,  0.,  0.],
       [ 0.,  0.,  0.]), array([-1.,  0.,  0.],
       [ 0.,  0.,  0.],
       [ 0.,  1.,  0.],
       [-1.,  1.,  0.]), array([[ 0.,  0.,  0.],
       [ 1.,  0.,  0.],
       [ 1.,  1.,  0.],
       [ 0.,  1.,  0.]])]
```

The Voronoi class has built-in plotting methods for 2D systems.

```
[5]: plt.figure()
ax = plt.gca()
voro.plot(ax=ax)
ax.scatter(points[:, 0], points[:, 1], s=10, c='k')
plt.show()
```



This also works for more complex cases, such as this hexagonal lattice.

```
[6]: def hexagonal_lattice(rows=3, cols=3, noise=0, seed=None):
    if seed is not None:
        np.random.seed(seed)
    # Assemble a hexagonal lattice
    points = []
    for row in range(rows*2):
        for col in range(cols):
            x = (col + (0.5 * (row % 2))) * np.sqrt(3)
            y = row*0.5
            points.append((x, y, 0))
    points = np.asarray(points)
    points += np.random.multivariate_normal(mean=np.zeros(3), cov=np.eye(3)*noise,
    size=points.shape[0])
    # Set z=0 again for all points after adding Gaussian noise
    points[:, 2] = 0
```


(continues on next page)

(continued from previous page)

```
# Wrap the points into the box
box = freud.box.Box(Lx=cols*np.sqrt(3), Ly=rows, is2D=True)
points = box.wrap(points)
return box, points
```

```
[7]: # Compute the Voronoi diagram and plot
box, points = hexagonal_lattice()
voro = freud.locality.Voronoi()
voro.compute((box, points))
voro
```


[7]:



For noisy data, we see that the Voronoi diagram can change substantially. We perturb the positions with 2D Gaussian noise. Coloring by the number of sides of each Voronoi cell, we can see patterns in the defects: 5-gons and 7-gons tend to pair up.


```
[8]: # Compute the Voronoi diagram
box, points = hexagonal_lattice(rows=12, cols=8, noise=0.03, seed=2)
voro = freud.locality.Voronoi()
voro.compute((box, points))

# Plot Voronoi with points and a custom cmap
plt.figure()
ax = plt.gca()
voro.plot(ax=ax, cmap='RdBu')
ax.scatter(points[:, 0], points[:, 1], s=2, c='k')
plt.show()
```



We can also compute the volumes of the Voronoi cells. Here, we plot them as a histogram:

```
[9]: plt.hist(voro.volumes)
plt.title('Voronoi cell volumes')
plt.show()
```




The Voronoi class also computes a `freud.locality.NeighborList`, where particles are neighbors if they share an edge in the Voronoi diagram. The `NeighborList` effectively represents the bonds in the [Delaunay triangulation](#). The neighbors are **weighted** by the length (in 2D) or area (in 3D) between them. The neighbor weights are stored in `voro.nlist.weights`.

```
[10]: nlist = voro.nlist
line_data = np.asarray([[points[i],
                           points[i] + box.wrap(points[j] - points[i])]
                        for i, j in nlist][:, :, :2])
line_collection = matplotlib.collections.LineCollection(line_data, alpha=0.2)
plt.figure()
ax = plt.gca()
voro.plot(ax=ax, cmap='RdBu')
```

(continues on next page)

(continued from previous page)

```
ax.add_collection(line_collection)
plt.show()
```



7.5.2 Analysis Modules

These introductory examples showcase the functionality of specific modules in **freud**, showing how they can be used to perform specific types of analyses of simulations.

freud.cluster.Cluster and **freud.cluster.ClusterProperties**

The `freud.cluster` module determines clusters of points and computes cluster quantities like centers of mass, gyration tensors, and radii of gyration. The example below generates random points, and shows that they form clusters. This case is two-dimensional (with $z = 0$ for all particles) for simplicity, but the cluster module works for both 2D and 3D simulations.

```
[1]: import numpy as np
import freud
import matplotlib.pyplot as plt
```

First, we generate a box and random points to cluster.

```
[2]: box = freud.Box.square(L=6)
points = np.empty(shape=(0, 2))
for center_point in [(-1.8, 0), (1.5, 1.5), (-0.8, -2.8), (1.5, 0.5)]:
    points = np.concatenate(
        (points, np.random.multivariate_normal(mean=center_point, cov=0.08*np.eye(2),
        size=(100,))))
points = np.hstack((points, np.zeros((points.shape[0], 1))))
points = box.wrap(points)
system = freud.AABBQuery(box, points)
system.plot(ax=plt.gca(), s=10)
plt.title('Raw points before clustering', fontsize=20)
plt.gca().tick_params(axis='both', which='both', labels=14, size=8)
plt.show()
```


```
cl = freud.cluster.Cluster()
```

```
cl.compute(system, neighbors={'r_max': 1.0})  
print(cl.cluster_idx)  
  
[[1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1  
 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1  
 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1  
 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0  
 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0  
 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2  
 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2  
 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2  
 2 2 2 2 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0  
 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0  
 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0]]
```

(continues on next page)

(continued from previous page)

There are 100 points in cluster 1.
There are 100 points in cluster 2.



We may also compute the clusters' centers of mass and gyration tensor using the `ClusterProperties` class.

```
[6]: clp = freud.cluster.ClusterProperties()
      clp.compute(system, cl.cluster_idx);
```


Plotting these clusters with their centers of mass, with size proportional to the number of clustered points:

```
[7]: fig, ax = plt.subplots(1, 1, figsize=(9, 6))

for i in range(cl.num_clusters):
    cluster_system = freud.AABBQuery(system.box, system.points[cl.cluster_keys[i]])
    cluster_system.plot(ax=ax, s=10, label="Cluster {}".format(i))

for i, c in enumerate(clp.centers):
    ax.scatter(c[0], c[1], s=len(cl.cluster_keys[i]),
              label="Cluster {} Center".format(i))

plt.title('Center of mass for each cluster', fontsize=20)
plt.legend(loc='best', fontsize=14)
plt.gca().tick_params(axis='both', which='both', labelsiz=14, size=8)
plt.gca().set_aspect('equal')
plt.show()
```



The 3x3 gyration tensors G can also be computed for each cluster. For this two-dimensional case, the z components of the gyration tensor are zero. The gyration tensor can be used to determine the principal axes of the cluster and radius of gyration along each principal axis. Here, we plot the gyration tensor's eigenvectors with length corresponding to the square root of the eigenvalues (the singular values).


```
[8]: fig, ax = plt.subplots(1, 1, figsize=(9, 6))

for i in range(cl.num_clusters):
    cluster_system = freud.AABBQuery(system.box, system.points[cl.cluster_keys[i]])
    cluster_system.plot(ax=ax, s=10, label="Cluster {}".format(i))

for i, c in enumerate(clp.centers):
    ax.scatter(c[0], c[1], s=len(cl.cluster_keys[i]),
               label="Cluster {} Center".format(i))

for cluster_id in range(cl.num_clusters):
    com = clp.centers[cluster_id]
    G = clp.gyrations[cluster_id]
    evals, evecs = np.linalg.eig(G[:2, :2])
    arrows = np.sqrt(evals) * evecs
    for arrow in arrows.T:
        plt.arrow(com[0], com[1], arrow[0], arrow[1], width=0.05, color='k')

plt.title('Eigenvectors of the gyration tensor for each cluster', fontsize=20)
plt.legend(loc='best', fontsize=14)
ax.tick_params(axis='both', which='both', labelsize=14, size=8)
ax.set_aspect('equal')
plt.show()
```



freud.density.CorrelationFunction

Orientalional Ordering in 2D

The `freud.density` module is intended to compute a variety of quantities that relate spatial distributions of particles with other particles. This example shows how [correlation functions](#) can be used to measure orientational order in 2D.

```
[1]: import numpy as np
import freud
import matplotlib.pyplot as plt
import matplotlib.cm
from matplotlib.colors import Normalize
```

This helper function will make plots of the data we generate in this example.

```
[2]: def plot_data(title, points, angles, values, box, cf, s=200):
    cmap = matplotlib.cm.viridis
    norm = Normalize(vmin=-np.pi/4, vmax=np.pi/4)
    plt.figure(figsize=(16, 6))
    plt.subplot(121)
    for point, angle, value in zip(points, angles, values):
        plt.scatter(point[0], point[1], marker=(4, 0, np.rad2deg(angle)+45),
                    edgecolor='k', c=[cmap(norm(angle))], s=s)
    plt.title(title)
    plt.gca().set_xlim([-box.Lx/2, box.Lx/2])
    plt.gca().set_ylim([-box.Ly/2, box.Ly/2])
```

(continues on next page)

(continued from previous page)

```
plt.gca().set_aspect('equal')
sm = plt.cm.ScalarMappable(cmap='viridis', norm=norm)
sm.set_array(angles)
plt.colorbar(sm)
plt.subplot(122)
plt.title('Orientation Spatial Autocorrelation Function')
cf.plot(ax=plt.gca())
plt.xlabel(r'$r$')
plt.ylabel(r'$C(r)$')
plt.show()
```

First, let's generate a 2D structure with perfect orientational order and slight positional disorder (the particles are not perfectly on a grid, but they are perfectly aligned). The color of the particles corresponds to their angle of rotation, so all the particles will be the same color to begin with.

We create a `freud.density.CorrelationFunction` object to compute the correlation functions. Given a particle orientation θ , we compute its complex orientation value (the quantity we are correlating) as $s = e^{4i\theta}$, to account for the fourfold symmetry of the particles. We will compute the correlation function $C(r) = \langle s_1^*(0) \cdot s_2(r) \rangle$ by taking the average over all particle pairs and binning the results into a histogram by the distance r between the particles.

When we compute the correlations between particles, the complex conjugate of the `values` array is used internally for the query points. This way, if θ_1 is close to θ_2 , then we get $(e^{4i\theta_1})^* \cdot (e^{4i\theta_2}) = e^{4i(\theta_2 - \theta_1)} \approx e^0 = 1$.

This system has perfect spatial correlation of the particle orientations, so we see $C(r) = 1$ for all values of r .


```
[3]: def make_particles(L, repeats):
    uc = freud.data.UnitCell.square()
    return uc.generate_system(num_replicas=repeats, scale=L/repeats, sigma_noise=5e-
    → 3*L)

# Make a small system
box, points = make_particles(L=5, repeats=20)

# All the particles begin with their orientation at 0
angles = np.zeros(len(points))
values = np.array(np.exp(angles * 4j))

# Create the CorrelationFunction compute object and compute the correlation function
cf = freud.density.CorrelationFunction(bins=25, r_max=box.Lx/2.01)
cf.compute(system=(box, points), values=values,
           query_points=points, query_values=values)

plot_data('Particles before introducing Orientational Disorder',
          points, angles, values, box, cf)
```




Now we will generate random angles from $-\frac{\pi}{4}$ to $\frac{\pi}{4}$, which orients our squares randomly. The four-fold symmetry of the squares means that the space of unique angles is restricted to a range of $\frac{\pi}{2}$. Again, we compute a complex value for each particle, $s = e^{4i\theta}$.

Because we have purely random orientations, we expect no spatial correlations in the plot above. As we see, $C(r) \approx 0$ for all r .

```
[4]: # Change the angles to values randomly drawn from a uniform distribution
angles = np.random.uniform(-np.pi/4, np.pi/4, size=len(points))
values = np.exp(angles * 4j)

# Recompute the correlation functions
cf.compute(system=(box, points), values=values,
           query_points=points, query_values=values)

plot_data('Particles with Orientational Disorder',
          points, angles, values, box, cf)
```




The plot below shows what happens when we intentionally introduce a correlation length by adding a spatial pattern to the particle orientations. At short distances, the correlation is very high. As r increases, the oppositely-aligned part of the pattern some distance away causes the correlation to drop.

```
[5]: # Use angles that vary spatially in a pattern
angles = np.pi/4 * np.cos(2*np.pi*points[:, 0]/box.Lx)
values = np.exp(angles * 4j)

# Recompute the correlation functions
cf.compute(system=(box, points), values=values,
           query_points=points, query_values=values)

plot_data('Particles with Spatially Correlated Orientations',
          points, angles, values, box, cf)
```




In the larger system shown below, we see the spatial autocorrelation rise and fall with damping oscillations.

```
[6]: # Make a large system
box, points = make_particles(L=10, repeats=40)

# Use angles that vary spatially in a pattern
angles = np.pi/4 * np.cos(8*np.pi*points[:, 0]/box.Lx)
values = np.exp(angles * 4j)

# Create a CorrelationFunction compute object
cf = freud.density.CorrelationFunction(bins=25, r_max=box.Lx/2.01)
cf.compute(system=(box, points), values=values,
           query_points=points, query_values=values)

plot_data('Larger System with Spatially Correlated Orientations',
          points, angles, values, box, cf, s=80)
```




freud.density.GaussianDensity

The `freud.density` module is intended to compute a variety of quantities that relate spatial distributions of particles with other particles. In this notebook, we demonstrate `freud`'s Gaussian density calculation, which provides a way to interpolate particle configurations onto a regular grid in a meaningful way that can then be processed by other algorithms that require regularity, such as a [Fast Fourier Transform](#).

```
[1]: import numpy as np
      from scipy import stats
      import freud
      import matplotlib.pyplot as plt
```


To illustrate the basic concept, consider a toy example: a simple set of point particles with unit mass on a line. For analytical purposes, the standard way to accomplish this would be using [Dirac delta functions](#).

```
[2]: n_p = 10000
      np.random.seed(129)
      x = np.linspace(0, 1, n_p)
      y = np.zeros(n_p)
      points = np.random.rand(10)
      y[(points*n_p).astype('int')] = 1
      plt.plot(x, y);
      plt.show()
```



However, delta functions can be cumbersome to work with, so we might instead want to smooth out these particles. One option is to instead represent particles as Gaussians centered at the location of the points. In that case, the total particle density at any point in the interval $[0, 1]$ represented above would be based on the sum of the densities of those Gaussians at those points.

```
[3]: # Note that we use a Gaussian with a small standard deviation
# to emphasize the differences on this small scale
dists = [stats.norm(loc=i, scale=0.1) for i in points]
y_gaussian = 0
for dist in dists:
    y_gaussian += dist.pdf(x)
plt.plot(x, y_gaussian);
plt.show()
```



The goal of the GaussianDensity class is to perform the same interpolation for points on a 2D or 3D grid, accounting for Box periodicity.

```
[4]: N = 1000 # Number of points
L = 10 # Box length

box, points = freud.data.make_random_system(L, N, is2D=True, seed=0)
```

(continues on next page)


(continued from previous page)

```

aq = freud.AABBQuery(box, points)
gd = freud.density.GaussianDensity(L*L, L/3, 1)
gd.compute(aq)

fig, axes = plt.subplots(1, 2, figsize=(14, 6))
aq.plot(ax=axes[0])
gd.plot(ax=axes[1])
plt.show()

```



The effects are much more striking if we explicitly construct our points to be centered at certain regions.

```


[5]: N = 1000 # Number of points
L = 10 # Box length
box = freud.box.Box.square(L)
centers = np.array([[L/4, L/4, 0],
                    [-L/4, L/4, 0],
                    [L/4, -L/4, 0],
                    [-L/4, -L/4, 0]])

points = []
for center in centers:
    points.append(np.random.multivariate_normal(center, cov=np.diag([1, 1, 0]),
    ↪size=(int(N/4),)))
points = box.wrap(np.concatenate(points))
aq = freud.AABBQuery(box, points)

gd = freud.density.GaussianDensity(L*L, L/3, 1)
gd.compute(aq)

fig, axes = plt.subplots(1, 2, figsize=(14, 6))
aq.plot(ax=axes[0])
gd.plot(ax=axes[1])
plt.show()

```



freud.density.LocalDensity

The `freud.density` module is intended to compute a variety of quantities that relate spatial distributions of particles with other particles. In this notebook, we demonstrate `freud`'s local density calculation, which can be used to characterize the particle distributions in some systems. In this example, we consider a toy example of calculating the particle density in the vicinity of a set of other points. This can be visualized as, for example, billiard balls on a table with certain regions of the table being stickier than others. In practice, this method could be used for analyzing, *e.g.*, binary systems to determine how densely one species packs close to the surface of the other.

```
[1]: import numpy as np
import freud
import matplotlib.pyplot as plt
from matplotlib import patches

[2]: # Define some helper plotting functions.
def add_patches(ax, points, radius=1, fill=False, color="#1f77b4", ls="solid",
               lw=None):
    """Add set of points as patches with radius to the provided axis"""
    for pt in points:
        p = patches.Circle(pt, fill=fill, linestyle=ls, radius=radius,
                           facecolor=color, edgecolor=color, lw=lw)
        ax.add_patch(p)

def plot_lattice(box, points, radius=1, ls="solid", lw=None):
    """Helper function for plotting points on a lattice."""
    fig, ax = plt.subplots(1, 1, figsize=(9, 9))
    box.plot(ax=ax)
    add_patches(ax, points, radius, ls=ls, lw=lw)
    return fig, ax
```

Let us consider a set of regions on a square lattice.

```
[3]: area = 2
radius = np.sqrt(area/np.pi)
spot_area = area*100
```


(continues on next page)

(continued from previous page)

```

spot_radius = np.sqrt(spot_area/np.pi)
num = 6
scale = num*4
uc = freud.data.UnitCell(freud.Box.square(1), [[0.5, 0.5, 0]])
box, spot_centers = uc.generate_system(num, scale=scale)
fig, ax = plot_lattice(box, spot_centers, spot_radius, ls="dashed", lw=2.5)
plt.tick_params(axis="both", which="both", labelsize=14)
plt.show()

```



Now let's add a set of points to this box. Points are added by drawing from a normal distribution centered at each of the regions above. For demonstration, we will assume that each region has some relative "attractiveness," which is represented by the covariance in the normal distributions used to draw points. Specifically, as we go up and to the right, the covariance increases proportional to the distance from the lower right corner of the box.

```

[4]: points = []
fractional_distances_to_corner = np.linalg.norm(box.make_fractional(spot_centers),
↪axis=-1)
cov_basis = 20 * fractional_distances_to_corner
for i, p in enumerate(spot_centers):

```

(continues on next page)

(continued from previous page)

```


np.random.seed(i)
cov = cov_basis[i]*np.diag([1, 1, 0])
points.append(
    np.random.multivariate_normal(p, cov, size=(50,)))
points = box.wrap(np.concatenate(points))

```

```

[5]: fig, ax = plot_lattice(box, spot_centers, spot_radius, ls="dashed", lw=2.5)
plt.tick_params(axis="both", which="both", labelsize=14)
add_patches(ax, points, radius, True, 'k', lw=None)
plt.show()

```



We see that the density decreases as we move up and to the right. In order to compute the actual densities, we can leverage the `LocalDensity` class. The class allows you to specify a set of query points around which the number of other points is computed. These other points can, but need not be, distinct from the query points. In our case, we want to use the blue regions as our query points with the small black dots as our data points.

When we construct the `LocalDensity` class, there are two arguments. The first is the radius from the query points within which particles should be included in the query point's counter. The second is the circumsphere diameter of the **data points**, not the query points. This distinction is critical for getting appropriate density values, since these values


are used to actually check cutoffs and calculate the density.

```
[6]: density = freud.density.LocalDensity(spot_radius, radius)
density.compute(system=(box, points), query_points=spot_centers);

[7]: fig, axes = plt.subplots(1, 2, figsize=(14, 6))

for i, data in enumerate([density.num_neighbors, density.density]):
    poly = np.poly1d(np.polyfit(cov_basis, data, 1))
    axes[i].tick_params(axis="both", which="both", labelsz=14)
    axes[i].scatter(cov_basis, data)
    x = np.linspace(*axes[i].get_xlim(), 30)
    axes[i].plot(x, poly(x), label="Best fit")
    axes[i].set_xlabel("Covariance", fontsize=16)

axes[0].set_ylabel("Number of neighbors", fontsize=16);
axes[1].set_ylabel("Density", fontsize=16);
plt.show()
```



As expected, we see that increasing the variance in the number of points centered at a particular query point decreases the total density at that point. The trend is noisy since we are randomly sampling possible positions, but the general behavior is clear.

freud.density.RDF: Accumulating $g(r)$ for a Fluid

The `freud.density` module is intended to compute a variety of quantities that relate spatial distributions of particles with other particles. This example demonstrates the calculation of the [radial distribution function](#) $g(r)$ for a fluid, averaged over multiple frames.

```
[1]: import numpy as np
import freud
import matplotlib.pyplot as plt

data_path = "data/phi065"
box_data = np.load("{}box_data.npy".format(data_path))
pos_data = np.load("{}pos_data.npy".format(data_path))
```

(continues on next page)

(continued from previous page)


```
def plot_rdf(box_arr, points_arr, prop, r_max=10, bins=100, label=None, ax=None):
    """Helper function for plotting RDFs."""
    if ax is None:
        fig, ax = plt.subplots(1, 1, figsize=(12, 8))
        ax.set_title(prop, fontsize=16)
    rdf = freud.density.RDF(bins, r_max)
    for box, points in zip(box_arr, points_arr):
        rdf.compute(system=(box, points), reset=False)
    if label is not None:
        ax.plot(rdf.bin_centers, getattr(rdf, prop), label=label)
        ax.legend()
    else:
        ax.plot(rdf.bin_centers, getattr(rdf, prop))
    return ax
```

Here, we show the difference between the RDF of one frame and an accumulated (averaged) RDF from several frames. Including more frames makes the plot smoother.

```
[2]: # Compute the RDF for the last frame
box_arr = [box_data[-1].tolist()]
pos_arr = [pos_data[-1]]
ax = plot_rdf(box_arr, pos_arr, 'rdf', label='One frame')

# Compute the RDF for the last 20 frames
box_arr = [box.tolist() for box in box_data[-20:]]
pos_arr = pos_data[-20:]
ax = plot_rdf(box_arr, pos_arr, 'rdf', label='Last 20 frames', ax=ax)

plt.show()
```




The difference between `accumulate` (which should be called on a series of frames) and `compute` (meant for a single frame) is more striking for smaller bin sizes, which are statistically noisier.

```
[3]: # Compute the RDF for the last frame
box_arr = [box_data[-1].tolist()]
pos_arr = [pos_data[-1]]
ax = plot_rdf(box_arr, pos_arr, 'rdf', bins=1000, label='One frame')

# Compute the RDF for the last 20 frames
box_arr = [box.tolist() for box in box_data[-20:]]
pos_arr = pos_data[-20:]
ax = plot_rdf(box_arr, pos_arr, 'rdf', bins=1000, label='Last 20 frames', ax=ax)

plt.show()
```



freud.density.RDF: Choosing Bin Widths

The `freud.density` module is intended to compute a variety of quantities that relate spatial distributions of particles with other particles. This example demonstrates the calculation of the radial distribution function $g(r)$ using different bin sizes.

```
[1]: import numpy as np
import freud
import matplotlib.pyplot as plt

[2]: # Define some helper plotting functions.
def plot_rdf(box, points, prop, r_max=3.5, bins_array=[20, 75, 3000]):
    """Helper function for plotting RDFs."""
    fig, axes = plt.subplots(1, len(bins_array), figsize=(16, 3))
    for i, bins in enumerate(bins_array):
        rdf = freud.density.RDF(bins, r_max)
        rdf.compute(system=(box, points))
        axes[i].plot(rdf.bin_centers, getattr(rdf, prop))
        axes[i].set_title("Bin width: {:.3f}".format(r_max/bins), fontsize=16)
    plt.show()
```


To start, we construct and visualize a set of points sitting on a simple square lattice.

```
[3]: box, points = freud.data.UnitCell.square().generate_system(5, scale=2)
aq = freud.AABBQuery(box, points)
```

(continues on next page)


(continued from previous page)

```
aq.plot(ax=plt.gca())
plt.show()
```



If we try to compute the RDF directly from this, we will get something rather uninteresting since we have a perfect crystal. Indeed, we will observe that as we bin more and more finely, we approach the true behavior of the RDF for perfect crystals, which is a simple delta function.

```
[4]: plot_rdf(box, points, 'rdf')
```



In these RDFs, we see two sharply defined peaks, with the first corresponding to the nearest neighbors on the lattice (which are all at a distance 2 from each other), and the second, smaller peak caused by the particles on the diagonal (which sit at distance $\sqrt{2^2 + 2^2} \approx 2.83$).


However, in more realistic systems, we expect that the lattice will not be perfectly formed. In this case, the RDF will exhibit more features. To demonstrate this fact, we reconstruct the square lattice of points from above, but we now introduce some noise into the system.

```
[5]: box, clean_points = freud.data.UnitCell.square().generate_system(10, scale=2, sigma_
    ↪noise=0)
    box, noisy_points = freud.data.UnitCell.square().generate_system(10, scale=2, sigma_
    ↪noise=0.1)
    aq_clean = freud.AABBQuery(box, clean_points)
    aq_clean.plot(ax=plt.gca(), c='k', s=3)
    aq_noisy = freud.AABBQuery(box, noisy_points)
    deviations = np.linalg.norm(box.wrap(noisy_points-clean_points), axis=-1)
    _, sc = aq_noisy.plot(ax=plt.gca(), c=deviations)
    cbar = plt.colorbar(sc)
```


(continues on next page)

(continued from previous page)

```
cbar.set_label('Distance from lattice site')
plt.show()
```




```
[6]: plot_rdf(box, noisy_points, 'rdf')
```



In this RDF, we see the same rough features as we saw with the perfect lattice. However, the signal is much noisier, and in fact we see that increasing the number of bins essentially leads to overfitting of the data. As a result, we have to be careful with how we choose to bin our data when constructing the RDF object.

An alternative route for avoiding this problem can be using the cumulative RDF instead. The relationship between the cumulative RDF and the RDF is akin to that between a cumulative density and a probability density function, providing a measure of the total density of particles experienced up to some distance rather than the value at that distance. Just as a CDF can help avoid certain mistakes common to plotting a PDF, plotting the cumulative RDF may be helpful in some cases. Here, we see that decreasing the bin size slightly alters the features of the plot, but only in very minor way (*i.e.* decreasing the smoothness of the line due to small jitters).

```
[7]: plot_rdf(box, noisy_points, 'n_r')
```



freud.environment.AngularSeparation

The `freud.environment` module analyzes the local environments of particles. The `freud.environment.AngularSeparation` class enables direct measurement of the relative orientations of particles.

```
[1]: import freud
import numpy as np
import matplotlib.pyplot as plt
plt.rcParams['axes.titlepad'] = 20
from mpl_toolkits.mplot3d import Axes3D
import rowan # for quaternion math, see rowan.readthedocs.io for more information.
```

In order to work with orientations in `freud`, we need to do some math with quaternions. If you are unfamiliar with quaternions, you can read more about [their definition](#) and how they can be used to [represent rotations](#). For the purpose of this tutorial, just consider them as 4D vectors, and know that the set of normalized (*i.e.* unit norm) 4D vectors can be used to represent rotations in 3D. In fact, there is a 1-1 mapping between normalized quaternions and 3x3 rotation matrices. Quaternions are more computationally convenient, however, because they only require storing 4 numbers rather than 9, and they can be much more easily chained together. The `rowan` library ([rowan.readthedocs.io](#)) defines many useful operations using quaternions, such as the rotations of vectors using quaternions instead of matrices.

Neighbor Angles


One usage of the `AngularSeparation` class is to compute angles between neighboring particles. To show how this works, we generate a simple configuration of particles with random orientations associated with each point.

```
[2]: uc = freud.data.UnitCell.sc()
box, positions = uc.generate_system(5)
N = len(positions)

# Generate random, correlated particle orientations by taking identity
# quaternions and slightly rotating them in a random direction
np.random.seed(0)
interpolate_amount = 0.2
identity_quats = np.array([[1, 0, 0, 0]] * N)
ref_orientations = rowan.interpolate.slerp(
    identity_quats, rowan.random.rand(N), interpolate_amount)
orientations = rowan.interpolate.slerp(
    identity_quats, rowan.random.rand(N), interpolate_amount)

[3]: # To show orientations, we use arrows rotated by the quaternions.
ref_arrowheads = rowan.rotate(ref_orientations, np.array([1, 0, 0]))
arrowheads = rowan.rotate(orientations, np.array([1, 0, 0]))


fig = plt.figure(figsize=(12, 6))
ref_ax = fig.add_subplot(121, projection='3d')
ax = fig.add_subplot(122, projection='3d')
ref_ax.quiver3D(positions[:, 0], positions[:, 1], positions[:, 2],
                ref_arrowheads[:, 0], ref_arrowheads[:, 1], ref_arrowheads[:, 2])
ax.quiver3D(positions[:, 0], positions[:, 1], positions[:, 2],
            arrowheads[:, 0], arrowheads[:, 1], arrowheads[:, 2])
ref_ax.set_title("Reference orientations", fontsize=16)
ax.set_title("Orientations", fontsize=16)
plt.show()
```



We can now use the AngularSeparation class to compare the orientations in these two systems.

```
[4]: # For simplicity, we'll assume that our "particles" are completely
# asymmetric, i.e. there are no rotations that map the particle
# back onto itself. If we had a regular polyhedron, then we would
# want to specify all the quaternions that rotate that polyhedron
# onto itself.
equiv_orientations = np.array([[1, 0, 0, 0]])
ang_sep = freud.environment.AngularSeparationNeighbor()
ang_sep.compute(system=(box, positions),
                orientations=orientations,
                query_points=positions,
                query_orientations=ref_orientations,
                equiv_orientations=equiv_orientations,
                neighbors={'num_neighbors': 12})

# Convert angles from radians to degrees and plot histogram
neighbor_angles = np.rad2deg(ang_sep.angles)
plt.hist(neighbor_angles)
plt.title('Histogram of angular separations between neighbors')
plt.xlabel('Angular separation (degrees)')
plt.ylabel('Frequency')
plt.show()
```




Global Angles

Alternatively, the `AngularSeparationGlobal` class can also be used to compute the orientation of all points in the system relative to some global set of orientations. In this case, we simply provide a set of global quaternions that we want to consider. For simplicity, let's consider 180° rotations about each of the coordinate axes, which have very simple quaternion representations.

```
[5]: global_orientations = np.array([[1, 0, 0, 0], [0, 1, 0, 0], [0, 0, 1, 0], [0, 0, 0, 1]])
      ang_sep = freud.environment.AngularSeparationGlobal()
      ang_sep.compute(global_orientations, ref_orientations, equiv_orientations)
      global_angles = np.rad2deg(ang_sep.angles)
```

```
[6]: plt.hist(global_angles[:, 0])
      plt.title('Histogram of angular separation relative to identity quaternion')
      plt.xlabel('Angular separation (degrees)')
      plt.ylabel('Frequency')
      plt.show()
```



As a simple check, we can ensure that for the identity quaternion $(1, 0, 0, 0)$, which performs a 0° rotation, the angles between the reference orientations and that quaternion are equal to the original angles of rotation of those quaternions (*i.e.* how much those orientations were already rotated relative to the identity).

```
[7]: ref_axes, ref_angles = rowan.to_axis_angle(ref_orientations)
      np.allclose(global_angles[:, 0], np.rad2deg(ref_angles), rtol=1e-4)

[7]: True
```

freud.environment.BondOrder

Computing Bond Order Diagrams

The `freud.environment` module analyzes the local environments of particles. In this example, the `freud.environment.BondOrder` class is used to plot the bond order diagram (BOD) of a system of particles.

```
[1]: import numpy as np
      import freud
      import matplotlib.pyplot as plt
      import matplotlib
      from mpl_toolkits.mplot3d import Axes3D
```

Setup

Our sample data will be taken from an face-centered cubic (FCC) structure. The array of points is rather large, so that the plots are smooth. Smaller systems may need to gather data from multiple frames in order to smooth the resulting array's statistics, by computing multiple times with `reset=False`.

```
[2]: uc = freud.data.UnitCell.fcc()
      box, points = uc.generate_system(40, sigma_noise=0.05)
```

Now we create a `BondOrder` compute object and create some arrays useful for plotting.


```
[3]: n_bins_theta = 100
n_bins_phi = 100
bod = freud.environment.BondOrder((n_bins_theta, n_bins_phi))

phi = np.linspace(0, np.pi, n_bins_phi)
theta = np.linspace(0, 2*np.pi, n_bins_theta)
phi, theta = np.meshgrid(phi, theta)
x = np.sin(phi) * np.cos(theta)
y = np.sin(phi) * np.sin(theta)
z = np.cos(phi)
```

Computing the Bond Order Diagram

Next, we use the `compute` method and the `bond_order` property to return the array.

```
[4]: bod_array = bod.compute(system=(box, points), neighbors={'num_neighbors': 12}).bond_
    ↪ order
# Clean up polar bins for plotting
bod_array = np.clip(bod_array, 0, np.percentile(bod_array, 99))
plt.imshow(bod_array.T)
plt.show()
```



Plotting on a sphere

This code shows the bond order diagram on a sphere as the sphere is rotated. The code takes a few seconds to run, so be patient.

```
[5]: fig = plt.figure(figsize=(12, 8))
for plot_num in range(6):
    ax = fig.add_subplot(231 + plot_num, projection='3d')
    ax.plot_surface(x, y, z, rstride=1, cstride=1, shade=False,
                    facecolors=matplotlib.cm.viridis(bod_array / np.max(bod_array)))
    ax.set_xlim(-1, 1)
    ax.set_ylim(-1, 1)
    ax.set_zlim(-1, 1)
    ax.set_axis_off()
```


(continues on next page)

(continued from previous page)

```

# View angles in degrees
view_angle = 0, plot_num*15
ax.view_init(*view_angle)
plt.show()

```




Using Custom Neighbors

We can also use a custom neighbor query to determine bonds. For example, we can filter for a range of bond lengths. Below, we only consider neighbors between $r_{min} = 2.5$ and $r_{max} = 3$ and plot the resulting bond order diagram.

```

[6]: bod_array = bod.compute(system=(box, points), neighbors={'r_max': 3.0, 'r_min': 2.5}).
      ↪bond_order
# Clean up polar bins for plotting
bod_array = np.clip(bod_array, 0, np.percentile(bod_array, 99))
plt.imshow(bod_array.T)
plt.show()

```



freud.environment.EnvironmentCluster

The `freud.environment.EnvironmentCluster` class finds and clusters local environments, as determined by the vectors pointing to neighbor particles. Neighbors can be defined by a cutoff distance or a number of nearest-neighbors, and the resulting `freud.locality.NeighborList` is used to enumerate a set of vectors, defining an “environment.” These environments are compared with the environments of neighboring particles to form spatial clusters, which usually correspond to grains, droplets, or crystalline domains of a system. `EnvironmentCluster` has several parameters that alter its behavior, please see the documentation or helper functions below for descriptions of these parameters.

In this example, we cluster the local environments of hexagons. Clusters with 5 or fewer particles are colored dark gray.

```
[1]: import numpy as np
import freud
from collections import Counter
import matplotlib.pyplot as plt

def get_cluster_arr(system, num_neighbors, threshold,
                    registration=False, global_search=False):
    """Computes clusters of particles' local environments.

    Args:
        system:
            Any object that is a valid argument to
            :class:`freud.locality.NeighborQuery.from_system`.
        num_neighbors (int):
            Number of neighbors to consider in every particle's local environment.
        threshold (float):
            Maximum magnitude of the vector difference between two vectors,
            below which we call them matching.
        global_search (bool):
            If True, do an exhaustive search wherein the environments of
            every single pair of particles in the simulation are compared.
            If False, only compare the environments of neighboring particles.
        registration (bool):
            Controls whether we first use brute force registration to
```

(continues on next page)

(continued from previous page)

```

        orient the second set of vectors such that it minimizes the
        RMSD between the two sets.

Returns:
    tuple(np.ndarray, dict): array of cluster indices for every particle
    and a dictionary mapping from cluster_index keys to vector_array)
    pairs giving all vectors associated with each environment.
    """
    # Perform the env-matching calculation
    neighbors = {'num_neighbors': num_neighbors}
    match = freud.environment.EnvironmentCluster()
    match.compute(system, threshold, neighbors=neighbors,
                  registration=registration, global_search=global_search)
    return match.cluster_idx, match.cluster_environments

def color_by_clust(cluster_index_arr, no_color_thresh=1,
                  no_color='#333333', cmap=plt.get_cmap('viridis')):
    """Takes a cluster_index_array for every particle and returns a
    dictionary of (cluster index, hexcolor) color pairs.

    Args:
        cluster_index_arr (numpy.ndarray):
            The array of cluster indices, one per particle.
        no_color_thresh (int):
            Clusters with this number of particles or fewer will be
            colored with no_color.
        no_color (color):
            What we color particles whose cluster size is below no_color_thresh.
        cmap (color map):
            The color map we use to color all particles whose
            cluster size is above no_color_thresh.
    """
    # Count to find most common clusters
    cluster_counts = Counter(cluster_index_arr)
    # Re-label the cluster indices by size
    color_count = 0
    color_dict = {cluster[0]: counter for cluster, counter in
                  zip(cluster_counts.most_common(),
                      range(len(cluster_counts)))}

    # Don't show colors for clusters below the threshold
    for cluster_id in cluster_counts:
        if cluster_counts[cluster_id] <= no_color_thresh:
            color_dict[cluster_id] = -1
    OP_arr = np.linspace(0.0, 1.0, max(color_dict.values())+1)

    # Get hex colors for all clusters of size greater than no_color_thresh
    for old_cluster_index, new_cluster_index in color_dict.items():
        if new_cluster_index == -1:
            color_dict[old_cluster_index] = no_color
        else:
            color_dict[old_cluster_index] = cmap(OP_arr[new_cluster_index])

    return color_dict

```


We load the simulation data and call the analysis functions defined above. Notice that we use 6 nearest neighbors, since our system is made of hexagons that tend to cluster with 6 neighbors.

```
[2]: ex_data = np.load('data/MatchEnv_Hexagons.npz')
    box = ex_data['box']
    positions = ex_data['positions']
    orientations = ex_data['orientations']
    aq = freud.AABBQuery(box, positions)

    cluster_index_arr, cluster_envs = get_cluster_arr(
        aq, num_neighbors=6, threshold=0.2,
        registration=False, global_search=False)
    color_dict = color_by_clust(cluster_index_arr, no_color_thresh=5)
    colors = [color_dict[i] for i in cluster_index_arr]
```

Below, we plot the resulting clusters. The colors correspond to the cluster size.

```
[3]: plt.figure(figsize=(12, 12), facecolor='white')
    aq.plot(ax=plt.gca(), c=colors, s=20)
    plt.title('Clusters Colored by Particle Local Environment')
    plt.show()
```



freud.environment.LocalDescriptors: Steinhardt Order Parameters from Scratch


The `freud.environment` module analyzes the local environments of particles. The `freud.environment.LocalDescriptors` class is a useful tool for analyzing identifying crystal structures in a rotationally invariant manner using local particle environments. The primary purpose of this class is to compute spherical harmonics between neighboring particles in a way that orients particles correctly relative to their local environment, ensuring that global orientational shifts do not change the output.

```
[1]: import freud
import numpy as np
import matplotlib.pyplot as plt
from mpl_toolkits.mplot3d import Axes3D
```

Computing Spherical Harmonics

To demonstrate the basic application of the class, let's compute the spherical harmonics between neighboring particles. For simplicity, we consider points on a simple cubic lattice.

```
[2]: uc = freud.data.UnitCell.sc()
     box, points = uc.generate_system(5)
     system = freud.AABBQuery(box, points)
     fig = plt.figure(figsize=(8, 6))
     ax = fig.add_subplot(111, projection='3d')
     system.plot(ax=ax)
     ax.set_title("Simple cubic crystal", fontsize=16)
     plt.show()
```



Now, let's use the class to compute an array of spherical harmonics for the system. The harmonics are computed for each bond, where a bond is defined by a pair of particles that are determined to lie within each others' nearest neighbor shells based on a standard neighbor list search. The number of bonds and spherical harmonics to calculate is configurable.

```
[3]: num_neighbors = 6
     l_max = 12

     nlist = system.query(points, {'num_neighbors': num_neighbors, 'exclude_ii': True}).
     ↪toNeighborList()
     ld = freud.environment.LocalDescriptors(l_max, mode='global')
     ld.compute(system, neighbors=nlist);
```

Accessing the Data

The resulting spherical harmonic array has a shape corresponding to the number of neighbors. We can now extract the spherical harmonics corresponding to a particular (l, m) pair using the ordering used by the `LocalDescriptors` class: increasing values of l , and for each l , the nonnegative m values followed by the negative values.

```
[4]: sph_raw = np.mean(ld.sph, axis=0)
count = 0
sph = np.zeros((l_max+1, l_max+1), dtype=np.complex128)
for l in range(l_max+1):
    for m in range(l+1):
        sph[l, m] = sph_raw[count]
        count += 1
    for m in range(-1, 0):
        sph[l, m] = sph_raw[count]
        count += 1
```

Using Spherical Harmonics to Compute Steinhardt Order Parameters

The raw per bond spherical harmonics are not typically useful quantities on their own. However, they can be used to perform sophisticated crystal structure analyses with different methods; for example, the `pythia` library uses machine learning to find patterns in the spherical harmonics computed by this class. In this notebook, we'll use the quantities for a more classical application: the computation of Steinhardt order parameters. The order parameters q_l provide a rotationally invariant measure of the system that can for some structures, provide a unique identifying fingerprint. They are a particularly useful measure for various simple cubic structures such as structures with underlying simple cubic, BCC, or FCC lattices. The `freud` library actually provides additional classes to efficiently calculate these order parameters directly, but they also provide a reasonable demonstration here.

For more information on Steinhardt order parameters, see the [original paper](#) or the `freud.order.Steinhardt` documentation.

```
[5]: def get_ql(num_particles, descriptors, nlist, weighted=False):
    """Given a set of points and a LocalDescriptors object (and the
    underlying NeighborList), compute the per-particle Steinhardt ql
    order parameter for all :math:`l` values up to the maximum quantum
    number used in the computation of the descriptors."""
    qbar_lm = np.zeros((num_particles, descriptors.sph.shape[1]),
                       dtype=np.complex128)
    for i in range(num_particles):
        indices = nlist.query_point_indices == i
        Ylms = descriptors.sph[indices, :]
        if weighted:
            weights = nlist.weights[indices, np.newaxis]
            weights /= np.sum(weights)
            num_neighbors = 1
        else:
            weights = np.ones_like(Ylms)
            num_neighbors = descriptors.sph.shape[0]/num_particles
        qbar_lm[i, :] = np.sum(Ylms * weights, axis=0)/num_neighbors

    ql = np.zeros((qbar_lm.shape[0], descriptors.l_max+1))
    for i in range(ql.shape[0]):
        for l in range(ql.shape[1]):
            for k in range(l**2, (l+1)**2):
                ql[i, l] += np.absolute(qbar_lm[i, k])**2
```

(continues on next page)

(continued from previous page)

```
        ql[i, l] = np.sqrt(4*np.pi/(2*l + 1) * ql[i, l])

    return ql

ld_ql = get_ql(len(points), ld, nlist)
```

Since `freud` provides the ability to calculate these parameter as well, we can directly check that our answers are correct. *Note: More information on the ``Steinhardt`` class can be found in the documentation or in the ``Steinhardt`` example.*


```
[6]: L = 6
      steinhardt = freud.order.Steinhardt(l=L)
      steinhardt.compute(system, neighbors=nlist)
      if np.allclose(steinhardt.ql, ld_ql[:, L]):
          print("Our manual calculation matches the Steinhardt class!")

Our manual calculation matches the Steinhardt class!
```

For a brief demonstration of why the Steinhardt order parameters can be useful, let's look at the result of thermalizing our points and recomputing this measure.

```
[7]: sigmas = [0.03, 0.05, 0.1]
      systems = []
      nlists = []
      for sigma in sigmas:
          box, points = uc.generate_system(5, sigma_noise=sigma)
          system = freud.AABBQuery(box, points)
          systems.append(system)
          nlists.append(
              system.query(
                  points, {'num_neighbors': num_neighbors, 'exclude_ii': True}
              ).toNeighborList()
          )
```


```
[8]: fig = plt.figure(figsize=(14, 6))
      axes = []
      for i, v in enumerate(sigmas):
          ax = fig.add_subplot("1{}{}".format(len(sigmas), i+1), projection='3d')
          systems[i].plot(ax=ax)
          ax.set_title("$\sigma$ = {}".format(v), fontsize=16);
      plt.show()
```



If we recompute the Steinhardt OP for each of these data sets, we see that adding noise has the effect of smoothing the order parameter such that the peak we observed for the perfect crystal is no longer observable.

```
[9]: ld_qls = []
for i, sigma in enumerate(sigmas):
    ld = freud.environment.LocalDescriptors(l_max, mode='global')
    ld.compute(systems[i], neighbors=nlists[i])
    ld_qls.append(get_ql(len(systems[i].points), ld, nlists[i]))

[10]: fig, ax = plt.subplots()
for i, ld_ql in enumerate(ld_qls):
    lim_out = ax.hist(ld_ql[:, L], label="$\\sigma$ = {}".format(sigmas[i]),
    ↪density=True)
    if i == 0:
        # Can choose any element, all are identical in the reference case
        ax.vlines(ld_ql[:, L][0], 0, np.max(lim_out[0]), label='Reference')
ax.set_title("Histogram of $q_{L}$ values".format(L=L), fontsize=16)
ax.set_ylabel("Frequency", fontsize=14)
ax.set_xlabel("$q_{L}$".format(L=L), fontsize=14)
ax.legend(fontsize=14)
plt.show()
```



This type of identification process is what the LocalDescriptors data outputs may be used for. In the case of Steinhardt OPs, it provides a simple fingerprint for comparing thermalized systems to a known ideal structure to measure their similarity.

For reference, we can also check these values against the Steinhardt class again.

```
[11]: for i, (system, nlist) in enumerate(zip(systems, nlists)):
      steinhardt = freud.order.Steinhardt(l=L)
      steinhardt.compute(system, nlist)
      if np.allclose(steinhardt.particle_order, ld_qls[i][:, L]):
          print("Our manual calculation matches the Steinhardt class!")
```

```
Our manual calculation matches the Steinhardt class!
Our manual calculation matches the Steinhardt class!
Our manual calculation matches the Steinhardt class!
```

freud.interface.Interface

Locating Particles on Interfacial Boundaries

The `freud.interface` module compares the distances between two sets of points to determine the interfacial particles.

```
[1]: import freud
      import numpy as np
      import matplotlib.pyplot as plt
```

To make a pretend data set, we create a large number of **blue** (-1) particles on a square grid. Then we place grain centers on a larger grid and draw grain radii from a normal distribution. We color the particles **yellow** (+1) if their distance from a grain center is less than the grain radius.

```
[2]: np.random.seed(0)
      system_size = 100
      num_grains = 4
      uc = freud.data.UnitCell.square()
```


(continues on next page)

(continued from previous page)

```

box, points = uc.generate_system(num_replicas=system_size, scale=1)
_, centroids = uc.generate_system(num_replicas=num_grains, scale=system_size/num_
    ↪grains)
system = freud.AABBQuery(box, points)
values = np.array([-1 for p in points])
grain_radii = np.abs(np.random.normal(size=num_grains**2, loc=5, scale=2))
for center, radius in zip(centroids, grain_radii):
    for i, j, dist in system.query(center, {'r_max': radius}):
        values[j] = 1
plt.figure(figsize=(9, 9))
system.plot(ax=plt.gca(), c=values, cmap='cividis', s=12)
plt.title('System of two particle types')
plt.show()

```



This system is **phase-separated** because the yellow particles are generally near one another, and so are the blue particles.

We can use `freud.interface.InterfaceMeasure` to label the particles on either side of the yellow-blue boundary. The class can tell us how many points are on either side of the interface:

```
[3]: iface = freud.interface.Interface()
    iface.compute((box, points[values > 0]), points[values < 0], neighbors={'r_max': 1.5})

    print('There are {} query points (blue) on the interface.'.format(iface.query_point_
        ↪count))
    print('There are {} points (yellow) on the interface.'.format(iface.point_count))


    There are 856 query points (blue) on the interface.
    There are 724 points (yellow) on the interface.
```

Now we can plot the particles on the interface. We color the outside of the interface dark blue and the inside of the interface yellow.

```
[4]: plt.figure(figsize=(9, 9))

    interface_values = np.zeros(len(points))
    interface_values[np.where(values < 0)[0][iface.query_point_ids]] = -1
    interface_values[np.where(values > 0)[0][iface.point_ids]] = 1

    system.plot(ax=plt.gca(), c=interface_values, cmap='cividis', s=12)
    plt.title('Particles on the interface between types')
    plt.show()
```



freud.order.Hexatic

Hexatic Order Parameter

The hexatic order parameter measures how closely the local environment around a particle resembles perfect k -atic symmetry, *e.g.* how closely the environment resembles hexagonal/hexatic symmetry for $k = 6$. The order parameter is given by:

$$\psi_k(i) = \frac{1}{n} \sum_j^n e^{ki\theta_{ij}}$$

where θ_{ij} is the angle between the vector \vec{r}_{ij} and $(1, 0)$.

The pseudocode is given below:

```
for each particle i:
    neighbors = nearestNeighbors(i, n):
```

(continues on next page)

(continued from previous page)

```

for each particle j in neighbors:
    r_ij = position[j] - position[i]
    theta_ij = arctan2(r_ij.y, r_ij.x)
    psi_array[i] += exp(complex(0, k*theta_ij))

```

The data sets used in this example are a system of hard hexagons, simulated in the NVT thermodynamic ensemble in HOOMD-blue, for a dense fluid of hexagons at packing fraction $\phi = 0.65$ and solids at packing fractions $\phi = 0.75, 0.85$.

```

[1]: import numpy as np
import freud
from bokeh.io import output_notebook
from bokeh.plotting import figure, show
# The following line imports this set of utility functions:
# https://github.com/glotzerlab/freud-examples/blob/master/util.py
import util
output_notebook()

```

Data type cannot be displayed: application/javascript, application/vnd.bokehjs_load.v0+json

```

[2]: def plot_hex_order_param(data_path, title):
    # Create hexatic object
    hex_order = freud.order.Hexatic(k=6)

    # Load the data
    box_data = np.load("{}box_data.npy".format(data_path))
    pos_data = np.load("{}pos_data.npy".format(data_path))
    quat_data = np.load("{}quat_data.npy".format(data_path))

    # Grab data from last frame
    box = box_data[-1].tolist()
    points = pos_data[-1]
    quats = quat_data[-1]
    angles = 2*np.arctan2(quats[:, 3], quats[:, 0])

    # Compute hexatic order for 6 nearest neighbors
    hex_order.compute(system=(box, points), neighbors={'num_neighbors': 6})
    psi_k = hex_order.particle_order
    avg_psi_k = np.mean(psi_k)

    # Create hexagon vertices
    verts = util.make_polygon(sides=6, radius=0.6204)
    # Create array of transformed positions
    patches = util.local_to_global(verts, points[:, :2], angles)
    # Create an array of angles relative to the average
    relative_angles = np.angle(psi_k) - np.angle(avg_psi_k)
    # Plot in bokeh
    p = figure(title=title)
    p.patches(xs=patches[:, :, 0].tolist(), ys=patches[:, :, 1].tolist(),
              fill_color=[util.cubeellipse(x) for x in relative_angles],
              line_color="black")
    util.default_bokeh(p)
    show(p)

```

```
[3]: plot_hex_order_param('data/phi065', 'Hexatic Order Parameter, 0.65 density')
```

Data type cannot be displayed: application/javascript, application/vnd.bokehjs_exec.v0+json

As the density increases to $\phi = 0.75$, the shapes are forced to align more closely so that they may tile space effectively.

```
[4]: plot_hex_order_param('data/phi075', 'Hexatic Order Parameter, 0.75 density')
```

Data type cannot be displayed: application/javascript, application/vnd.bokehjs_exec.v0+json

As the density increases to $\phi = 0.85$, the alignment becomes even stronger and defects are no longer visible.

```
[5]: plot_hex_order_param('data/phi085', 'Hexatic Order Parameter, 0.85 density')
```

Data type cannot be displayed: application/javascript, application/vnd.bokehjs_exec.v0+json

freud.order.Nematic

Nematic Order Parameter

The `freud.order` module provides the tools to calculate various [order parameters](#) that can be used to identify phase transitions. This notebook demonstrates the [nematic order parameter](#), which can be used to identify systems with strong orientational ordering but no translational ordering. For this example, we'll start with a set of random positions in a 3D system, each with a fixed, assigned orientation. Then, we will show how deviations from these orientations are exhibited in the order parameter.


```
[1]: import freud
import numpy as np
import matplotlib.pyplot as plt
from mpl_toolkits.mplot3d import Axes3D
import rowan # for quaternion math, see rowan.readthedocs.io for more information.
```

In order to work with orientations in `freud`, we need to do some math with quaternions. If you are unfamiliar with quaternions, you can read more about [their definition](#) and how they can be used to [represent rotations](#). For the purpose of this tutorial, just consider them as 4D vectors, and know that the set of normalized (*i.e.* unit norm) 4D vectors can be used to represent rotations in 3D. In fact, there is a 1-1 mapping between normalized quaternions and 3x3 rotation matrices. Quaternions are more computationally convenient, however, because they only require storing 4 numbers rather than 9, and they can be much more easily chained together. For our purposes, you can largely ignore the contents of the next cell, other than to note that this is how we perform rotations of vectors using quaternions instead of matrices.

```
[2]: # Random positions are fine for this. Order is measured
# in terms of similarity of orientations, not positions.
L = 10
N = 100
box, points = freud.data.make_random_system(L, N, seed=0)
orientations = np.array([[1, 0, 0, 0]] * N)
```

```
[3]: # To show orientations, we use arrows rotated by the quaternions.
arrowheads = rowan.rotate(orientations, [1, 0, 0])

fig = plt.figure()
ax = fig.add_subplot(111, projection='3d')
ax.quiver3D(points[:, 0], points[:, 1], points[:, 2],
            arrowheads[:, 0], arrowheads[:, 1], arrowheads[:, 2])
ax.set_title("Orientations", fontsize=16);
```



The nematic order parameter provides a measure of how much of the system is aligned with respect to some provided reference vector. As a result, we can now compute the order parameter for a few simple cases. Since our original system is oriented along the x-axis, we can immediately test for that, as well as orientation along any of the other coordinate axes.

```
[4]: nop = freud.order.Nematic([1, 0, 0])
nop.compute(orientations)
print("The value of the order parameter is {}".format(nop.order))


The value of the order parameter is 1.0.
```

In general, the nematic order parameter is defined as the eigenvalue corresponding to the largest eigenvector of the nematic tensor, which is also computed by this class and provides an average over the orientations of all particles in the system. As a result, we can also look at the intermediate results of our calculation and see how they are related. To do so, let's consider a more interesting system with random orientations.

```
[5]: # We rotate identity quaternions slightly, in a random direction
np.random.seed(0)
interpolate_amount = 0.3
identity_quats = np.array([[1, 0, 0, 0]] * N)
orientations = rowan.interpolate.slerp(
    identity_quats, rowan.random.rand(N), interpolate_amount)
```

```
[6]: # To show orientations, we use arrows rotated by the quaternions.
arrowheads = rowan.rotate(orientations, [1, 0, 0])

fig = plt.figure()
ax = fig.add_subplot(111, projection='3d')
ax.quiver3D(points[:, 0], points[:, 1], points[:, 2],
            arrowheads[:, 0], arrowheads[:, 1], arrowheads[:, 2])
ax.set_title("Orientations", fontsize=16);
```



First, we see that for this nontrivial system the order parameter now depends on the choice of director.

```
[7]: axes = [[1, 0, 0], [0, 1, 0], [0, 0, 1], [1, 1, 0], [1, 0, 1], [0, 1, 1], [1, 1, 1]]
for ax in axes:
    nop = freud.order.Nematic(ax)
    nop.compute(orientations)
    print("For axis {}, the value of the order parameter is {:.3f}.".format(ax, nop.
    ↳order))
```

```
For axis [1, 0, 0], the value of the order parameter is 0.600.
For axis [0, 1, 0], the value of the order parameter is 0.586.
For axis [0, 0, 1], the value of the order parameter is 0.587.
For axis [1, 1, 0], the value of the order parameter is 0.591.
For axis [1, 0, 1], the value of the order parameter is 0.589.
For axis [0, 1, 1], the value of the order parameter is 0.573.
For axis [1, 1, 1], the value of the order parameter is 0.578.
```

Furthermore, increasing the amount of variance in the orientations depresses the value of the order parameter even further.

```
[8]: interpolate_amount = 0.4
orientations = rowan.interpolate.slerp(
    identity_quats, rowan.random.rand(N), interpolate_amount)

arrowheads = rowan.rotate(orientations, [1, 0, 0])
fig = plt.figure()
ax = fig.add_subplot(111, projection='3d')
ax.quiver3D(points[:, 0], points[:, 1], points[:, 2],
            arrowheads[:, 0], arrowheads[:, 1], arrowheads[:, 2])
ax.set_title("Orientations", fontsize=16);


axes = [[1, 0, 0], [0, 1, 0], [0, 0, 1], [1, 1, 0], [1, 0, 1], [0, 1, 1], [1, 1, 1]]
for ax in axes:
    nop = freud.order.Nematic(ax)
    nop.compute(orientations)
    print("For axis {}, the value of the order parameter is {:.3f}.".format(ax, nop.
    ↳order))
```

```
For axis [1, 0, 0], the value of the order parameter is 0.451.
For axis [0, 1, 0], the value of the order parameter is 0.351.
```

(continues on next page)

(continued from previous page)

For axis [0, 0, 1], the value of the order parameter is 0.342.
 For axis [1, 1, 0], the value of the order parameter is 0.374.
 For axis [1, 0, 1], the value of the order parameter is 0.391.
 For axis [0, 1, 1], the value of the order parameter is 0.316.
 For axis [1, 1, 1], the value of the order parameter is 0.344.



Finally, we can look at the per-particle quantities and build them up to get the actual value of the order parameter.

```
[9]: # The per-particle values averaged give the nematic tensor
print(np.allclose(np.mean(nop.particle_tensor, axis=0), nop.nematic_tensor))
print("The nematic tensor:")
print(nop.nematic_tensor)

eig = np.linalg.eig(nop.nematic_tensor)
print("The eigenvalues of the nematic tensor:")
print(eig[0])
print("The eigenvectors of the nematic tensor:")
print(eig[1])

# The largest eigenvalue
print("The largest eigenvalue, {:0.3f}, is equal to the order parameter {:0.3f}.".
      ↪format(
          np.max(eig[0]), nop.order))
```

```
True
The nematic tensor:
[[ 0.0115407  0.21569438  0.14729623]
 [ 0.21569438  0.02040018  0.14309749]
 [ 0.14729623  0.14309748 -0.03194092]]
The eigenvalues of the nematic tensor:
[ 0.34387365 -0.20013455 -0.14373913]
The eigenvectors of the nematic tensor:
[[ 0.6173224  0.73592573 -0.27807635]
 [ 0.6237324 -0.6732561 -0.3970945 ]
 [ 0.47944868 -0.07169023  0.87463677]]
The largest eigenvalue, 0.344, is equal to the order parameter 0.344.
```

freud.order.Steinhardt

Steinhardt Order Parameters

The `freud.order` module provides the tools to calculate various [order parameters](#) that can be used to identify phase transitions. In the context of crystalline systems, some of the best known order parameters are the Steinhardt order parameters q_l and w_l . These order parameters are mathematically defined according to certain rotationally invariant combinations of spherical harmonics calculated between particles and their nearest neighbors, so they provide information about local particle environments. As a result, considering distributions of these order parameters across a system can help characterize the overall system's ordering. The primary utility of these order parameters arises from the fact that they often exhibit certain characteristic values for specific crystal structures.

In this notebook, we will use the order parameters to identify certain basic structures: BCC, FCC, and simple cubic. FCC, BCC, and simple cubic structures each exhibit characteristic values of q_l for some l value, meaning that in a perfect crystal all the particles in one of these structures will have the same value of q_l . As a result, we can use these characteristic q_l values to determine whether a disordered fluid is beginning to crystallize into one structure or another. The l values correspond to the l quantum number used in defining the underlying spherical harmonics; for example, the q_4 order parameter would provide a measure of 4-fold ordering.

```
[1]: import freud
import numpy as np
import matplotlib.pyplot as plt
from mpl_toolkits.mplot3d import Axes3D
# Try to plot using KDE if available, otherwise revert to histogram
try:
    from sklearn.neighbors.kde import KernelDensity
    kde = True
except:
    kde = False

np.random.seed(1)
```

We first construct ideal crystals and then extract the characteristic value of q_l for each of these structures. In this case, we know that simple cubic has a coordination number of 6, BCC has 8, and FCC has 12, so we are looking for the values of q_6 , q_8 , and q_{12} , respectively. Therefore, we can also enforce that we require 6, 8, and 12 nearest neighbors to be included in the calculation, respectively.

```
[2]: L = 6
sc = freud.data.UnitCell.sc()
sc_system = sc.generate_system(5)
ql = freud.order.Steinhardt(L)
ql_sc = ql.compute(sc_system, neighbors={'num_neighbors': L}).particle_order
mean_sc = np.mean(ql_sc)
print("The Q{} values computed for simple cubic are {:.3f} +/- {:.3e}".format(
    L, mean_sc, np.std(ql_sc)))

L = 8
bcc = freud.data.UnitCell.bcc()
bcc_system = bcc.generate_system(5, sigma_noise=0)
ql = freud.order.Steinhardt(L)
ql_bcc = ql.compute(bcc_system, neighbors={'num_neighbors': L}).particle_order
mean_bcc = np.mean(ql_bcc)
print("The Q{} values computed for bcc are {:.3f} +/- {:.3e}".format(
    L, mean_bcc, np.std(ql_bcc)))
```

(continues on next page)

(continued from previous page)

```

L = 12
fcc = freud.data.UnitCell.fcc()
fcc_system = fcc.generate_system(5)
ql = freud.order.Steinhardt(L)
ql_fcc = ql.compute(fcc_system, neighbors={'num_neighbors': L}).particle_order
mean_fcc = np.mean(ql_fcc)
print("The Q{} values computed for fcc are {:.3f} +/- {:.3e}".format(
    L, mean_fcc, np.std(ql_fcc)))

```

The Q6 values computed for simple cubic are 0.354 +/- 3.938e-08

The Q8 values computed for bcc are 0.213 +/- 1.137e-12

The Q12 values computed for fcc are 0.600 +/- 1.155e-12

Given that the per-particle order parameter values are essentially identical to within machine precision, we can be confident that we have found the characteristic value of q_l for each of these systems. We can now compare these values to the values of q_l in thermalized systems to determine the extent to which they are exhibiting the ordering expected of one of these perfect crystals.

```

[3]: def make_noisy_replicas(unitcell, sigmas):
    """Given a unit cell, return a noisy system."""
    systems = []
    for sigma in sigmas:
        systems.append(unitcell.generate_system(5, sigma_noise=sigma))
    return systems

[4]: sigmas = [0.01, 0.02, 0.03, 0.05]
sc_systems = make_noisy_replicas(sc, sigmas)
bcc_systems = make_noisy_replicas(bcc, sigmas)
fcc_systems = make_noisy_replicas(fcc, sigmas)

[5]: fig, axes = plt.subplots(1, 3, figsize=(16, 5))

# Zip up the data that will be needed for each structure type.
zip_obj = zip([sc_systems, bcc_systems, fcc_systems], [mean_sc, mean_bcc, mean_fcc],
              [6, 8, 12], ["Simple Cubic", "BCC", "FCC"])

for i, (systems, ref_val, L, title) in enumerate(zip_obj):
    ax = axes[i]
    for j, (system, sigma) in enumerate(zip(systems, sigmas)):
        ql = freud.order.Steinhardt(L)
        ql.compute(system, neighbors={'num_neighbors': L})
        if not kde:
            ax.hist(ql.particle_order, label="$\sigma$ = {}".format(sigma),
                    density=True)
        else:
            padding = 0.02
            N = 50
            bins = np.linspace(np.min(ql.particle_order)-padding,
                               np.max(ql.particle_order)+padding, N)

            kde = KernelDensity(bandwidth=0.004)
            kde.fit(ql.particle_order[:, np.newaxis])
            ql = np.exp(kde.score_samples(bins[:, np.newaxis]))

            ax.plot(bins, ql, label="$\sigma$ = {}".format(sigma))
    ax.set_title(title, fontsize=20)

```


(continues on next page)

(continued from previous page)

```

ax.tick_params(axis='both', which='both', labelsize=14)
if j == 0:
    # Can choose any element, all are identical in the reference case
    ax.vlines(ref_val, 0, np.max(ax.get_ylim()[1]), label='Reference')
fig.legend(*ax.get_legend_handles_labels(), fontsize=18) # Only have one legend
fig.subplots_adjust(right=0.78)

```



From this figure, we can see that for each type of structure, increasing the amount of noise makes the distribution of the order parameter values less peaked at the expected reference value. As a result, we can use this method to identify specific structures. Choosing the appropriate parameterization for the order parameter (which quantum number l to use, how to choose neighbors, etc.) can be very important.

In addition to the q_l parameters demonstrated here, this class can also compute the third-order invariant w_l . The w_l may be better at identifying some structures, so some experimentation and reference to the appropriate literature can be useful (as a starting point, see [Steinhardt, Nelson, and Ronchetti \(1983\)](#)).

By setting `average=True` in the constructor, the `Steinhardt` class will perform an additional level of averaging over the second neighbor shells of particles, to accumulate more information on particle environments (see [Lechner and Dellago \(2008\)](#)). To get a sense for the best method for analyzing a specific system, the best course of action is try out different parameters or to consult the literature to see how these have been used in the past.

freud.pmf.PMFTXY

The PMFT returns the potential energy associated with finding a particle pair in a given spatial (positional and orientational) configuration. The PMFT is computed in the same manner as the RDF. The basic algorithm is described below:

```

for each particle i:
    for each particle j:
        v_ij = position[j] - position[i]
        bin_x, bin_y = convert_to_bin(v_ij)
        pcf_array[bin_y][bin_x]++

```

freud uses spatial data structures and parallelism to optimize this algorithm.

The data sets used in this example are a system of hard hexagons, simulated in the NVT thermodynamic ensemble in HOOMD-blue, for a dense fluid of hexagons at packing fraction $\phi = 0.65$ and solids at packing fractions $\phi = 0.75, 0.85$.

```

[1]: import freud
     freud.set_num_threads(1)

```

(continues on next page)

(continued from previous page)

```

import numpy as np
import matplotlib
import matplotlib.pyplot as plt
# The following line imports this set of utility functions:
# https://github.com/glotzerlab/freud-examples/blob/master/util.py
import util
from scipy.ndimage.filters import gaussian_filter

%matplotlib inline
matplotlib.rcParams.update({'font.size': 20,
                            'axes.titlesize': 20,
                            'axes.labelsize': 20,
                            'xtick.labelsize': 16,
                            'ytick.labelsize': 16,
                            'savefig.pad_inches': 0.025,
                            'lines.linewidth': 2})

```

```

[2]: def plot_pmft(data_path, phi):
    # Create the pmft object
    pmft = freud.pmft.PMFTXY(x_max=3.0, y_max=3.0, bins=300)

    # Load the data
    box_data = np.load("{}box_data.npy".format(data_path))
    pos_data = np.load("{}pos_data.npy".format(data_path))
    quat_data = np.load("{}quat_data.npy".format(data_path))
    n_frames = pos_data.shape[0]

    for i in range(1, n_frames):
        # Read box, position data
        box = box_data[i].tolist()
        points = pos_data[i]
        quats = quat_data[i]
        angles = 2*np.arctan2(quats[:, 3], quats[:, 0]) % (2 * np.pi)
        pmft.compute(system=(box, points), query_orientations=angles, reset=False)

    # Get the value of the PMFT histogram bins
    pmft_arr = pmft.pmft.T

    # Do some simple post-processing for plotting purposes
    pmft_arr[np.isinf(pmft_arr)] = np.nan
    dx = (2.0 * 3.0) / pmft.nbins[0]
    dy = (2.0 * 3.0) / pmft.nbins[1]
    nan_arr = np.where(np.isnan(pmft_arr))
    for i in range(pmft.nbins[0]):
        x = -3.0 + dx * i
        for j in range(pmft.nbins[1]):
            y = -3.0 + dy * j
            if ((x*x + y*y < 1.5) and (np.isnan(pmft_arr[j, i]))):
                pmft_arr[j, i] = 10.0
    w = int(2.0 * pmft.nbins[0] / (2.0 * 3.0))
    center = int(pmft.nbins[0] / 2)

    # Get the center of the histogram bins
    pmft_smooth = gaussian_filter(pmft_arr, 1)
    pmft_image = np.copy(pmft_smooth)
    pmft_image[nan_arr] = np.nan

```

(continues on next page)

(continued from previous page)

```

pmft_smooth = pmft_smooth[center-w:center+w, center-w:center+w]
pmft_image = pmft_image[center-w:center+w, center-w:center+w]
x, y = pmft.bin_centers
reduced_x = x[center-w:center+w]
reduced_y = y[center-w:center+w]

# Plot figures
f = plt.figure(figsize=(12, 5), facecolor='white')
values = [-2, -1, 0, 2]
norm = matplotlib.colors.Normalize(vmin=-2.5, vmax=3.0)
n_values = [norm(i) for i in values]
colors = matplotlib.cm.viridis(n_values)
colors = colors[:, :3]
verts = util.make_polygon(sides=6, radius=0.6204)
lims = (-2, 2)
ax0 = f.add_subplot(1, 2, 1)
ax1 = f.add_subplot(1, 2, 2)
for ax in (ax0, ax1):
    ax.contour(reduced_x, reduced_y, pmft_smooth,
               [9, 10], colors='black')
    ax.contourf(reduced_x, reduced_y, pmft_smooth,
                [9, 10], hatches='X', colors='none')
    ax.plot(verts[:, 0], verts[:, 1], color='black', marker=',')
    ax.fill(verts[:, 0], verts[:, 1], color='black')
    ax.set_aspect('equal')
    ax.set_xlim(lims)
    ax.set_ylim(lims)
    ax.xaxis.set_ticks([i for i in range(lims[0], lims[1]+1)])
    ax.yaxis.set_ticks([i for i in range(lims[0], lims[1]+1)])
    ax.set_xlabel(r'$x$')
    ax.set_ylabel(r'$y$')

ax0.set_title('PMFT Heat Map, $\phi = {}$'.format(phi))
im = ax0.imshow(np.flipud(pmft_image),
                extent=[lims[0], lims[1], lims[0], lims[1]],
                interpolation='nearest', cmap='viridis',
                vmin=-2.5, vmax=3.0)
ax1.set_title('PMFT Contour Plot, $\phi = {}$'.format(phi))
ax1.contour(reduced_x, reduced_y, pmft_smooth,
            [-2, -1, 0, 2], colors=colors)

f.subplots_adjust(right=0.85)
cbar_ax = f.add_axes([0.88, 0.1, 0.02, 0.8])
f.colorbar(im, cax=cbar_ax)
plt.show()

```


65% density

The plot below shows the PMFT of hexagons at 65% density. The hexagons tend to be close to one another, in the darker regions (the lower values of the potential of mean force and torque).

The hatched region near the black hexagon in the center is a region where no data were collected: the hexagons are hard shapes and cannot overlap, so there is an excluded region of space close to the hexagon.

The ring around the hexagon where the PMFT rises and then falls corresponds to the minimum of the radial distribution function – particles tend to not occupy that region, preferring instead to be at close range (in the first neighbor shell) or further away (in the second neighbor shell).


```
[3]: plot_pmft('data/phi065', 0.65)
```



75% density

As the system density is increased to 75%, the propensity for hexagons to occupy the six sites on the faces of their neighbors increases, as seen by the deeper (darker) wells of the PMFT. Conversely, the shapes strongly dislike occupying the yellow regions, and no particle pairs occupied the white region (so there is no data).


```
[4]: plot_pmft('data/phi075', 0.75)
```



85% density

Finally, at 85% density, there is a large region where no neighbors can be found, and hexagons strictly occupy sites near those of the perfect hexagonal lattice, at the first- and second-neighbor shells. The wells are deeper and much more spatially confined than those of the systems at lower densities.

```
[5]: plot_pmft('data/phi085', 0.85)
```



freud.pmft.PMFTXYZ: Shifting Example

This notebook shows how to use the shifting option on PMFTXYZ to get high resolution views of PMFT features that are not centered.

```
[1]: import numpy as np
import freud
import matplotlib.pyplot as plt
```

First we load in our data. The particles used here are implemented with a simple Weeks-Chandler-Andersen isotropic pair potential, so particle orientation is not meaningful.

```
[2]: pos_data = np.load('data/XYZ/positions.npy')
box_data = np.load('data/XYZ/boxes.npy')
```

We calculate the PMFT the same way as shown in other examples first

```
[3]: window = 2**(1/6) # The size of the pmft calculation

bins = 100
pmft = freud.pmft.PMFTXYZ(x_max=window, y_max=window, z_max=window, bins=bins)

# This data is for isotropic particles, so we will just make some unit quaternions
# to use as the orientations
quats = np.zeros((pos_data.shape[1],4)).astype(np.float32)
quats[:,0] = 1

for i in range(10, pos_data.shape[0]):
    box = box_data[i]
    points = pos_data[i]
    pmft.compute((box, points), quats, reset=False)


unshifted = pmft.pmft

x, y, z = pmft.bin_centers
```

When we plot a centered slice of the XYZ pmft, we see that a number of wells are present at some distance from the origin

```
[4]: %matplotlib inline

plt.figure(figsize=(10,10))
plt.imshow(unshifted[int(bins/2),:,:])
plt.colorbar()
plt.show()
```



If we want a closer look at the details of those wells, then we could increase the PMFT resolution. But this will increase the computational cost by a lot, and we are wasting a big percentage of the pixels.

This use case is why the `shiftvec` argument was implemented. Now we will do the same calculation, but we will use a much smaller window centered on one of the wells.

To do this we need to pass a vector into the `PMFTXYZ` construction. The window will be centered on this vector.

```
[5]: shiftvec = [0.82, 0.82, 0]

window = 2*(1/6)/6 # Smaller window for the shifted case

bins = 50

pmft = freud.pmft.PMFTXYZ(x_max=window, y_max=window, z_max=window,
                          bins=50, shiftvec=shiftvec)

# This data is for isotropic particles, so we will just make some unit quaternions
# to use as the orientations
```

(continues on next page)

(continued from previous page)

```
orientations = np.array([[1, 0, 0, 0]] * pos_data.shape[1])


for i in range(10, pos_data.shape[0]):
    box = box_data[i]
    points = pos_data[i]
    pmft.compute(system=(box, points), query_orientations=orientations, reset=False)

shifted = pmft.pmft

x, y, z = pmft.bin_centers
```

Now the PMFT is a high resolution close up of one of the bonding wells. Note that as you increase the sampling resolution, you need to increase your number of samples because there is less averaging in each bin

```
[6]: %matplotlib inline
plt.figure(figsize=(10, 10))
plt.imshow(shifted[int(bins/2), :, :])
plt.colorbar()
plt.show()
```



7.5.3 Example Analyses

The examples below go into greater detail about specific applications of **freud** and use cases that its analysis methods enable, such as user-defined analyses, machine learning, and data visualization.

Implementing Common Neighbor Analysis as a custom method

Researchers commonly wish to implement their own custom analysis methods for particle simulations. Here, we show an example of how to write Common Neighbor Analysis (Honeycutt and Andersen, J. Phys. Chem. 91, 4950) as a custom method using **freud** and the NetworkX package.

NetworkX can be installed with `pip install networkx`.

First, we generate random points and determine which points share neighbors.

```
[1]: import freud
import numpy as np
from collections import defaultdict

[2]: # Use a face-centered cubic (fcc) system
box, points = freud.data.UnitCell.fcc().generate_system(4)
aq = freud.AABBQuery(box, points)
nl = aq.query(points, {'num_neighbors': 12, 'exclude_ii': True}).toNeighborList()

[3]: # Get all sets of common neighbors.
common_neighbors = defaultdict(list)
for i, p in enumerate(points):
    for j in nl.point_indices[nl.query_point_indices == i]:
        for k in nl.point_indices[nl.query_point_indices == j]:
            if i != k:
                common_neighbors[(i, k)].append(j)
```

Next, we use NetworkX to build graphs of common neighbors and compute the Common Neighbor Analysis signatures.

```
[4]: import networkx as nx
from collections import Counter

diagrams = defaultdict(list)
particle_counts = defaultdict(Counter)

for (a, b), neighbors in common_neighbors.items():
    # Build up the graph of connections between the
    # common neighbors of a and b.
    g = nx.Graph()
    for i in neighbors:
        for j in set(nl.point_indices[
            nl.query_point_indices == i]).intersection(neighbors):
            g.add_edge(i, j)

    # Define the identifiers for a CNA diagram:
    # The first integer is 1 if the particles are bonded, otherwise 2
    # The second integer is the number of shared neighbors
    # The third integer is the number of bonds among shared neighbors
    # The fourth integer is an index, just to ensure uniqueness of diagrams
    diagram_type = 2 - int(b in nl.point_indices[nl.query_point_indices == a])
    key = (diagram_type, len(neighbors), g.number_of_edges())
    # If we've seen any neighborhood graphs with this signature,
    # we explicitly check if the two graphs are identical to
    # determine whether to save this one. Otherwise, we add
    # the new graph immediately.
    if key in diagrams:
        isomorphs = [nx.is_isomorphic(g, h) for h in diagrams[key]]
        if any(isomorphs):
            idx = isomorphs.index(True)
        else:
            diagrams[key].append(g)
            idx = diagrams[key].index(g)
    else:
        diagrams[key].append(g)
        idx = diagrams[key].index(g)
```

(continues on next page)

(continued from previous page)

```
cna_signature = key + (idx,)
particle_counts[a].update([cna_signature])
```

Looking at the counts of common neighbor signatures, we see that the first particle of the fcc structure has 12 bonds with signature (1, 4, 2, 0) as we expect.

```
[5]: particle_counts[0]
[5]: Counter({(1, 4, 2, 0): 12,
              (2, 4, 4, 0): 6,
              (2, 1, 0, 0): 12,
              (2, 2, 1, 0): 24})
```

Analyzing simulation data from HOOMD-blue at runtime

The following script shows how to use `freud` to compute the radial distribution function $g(r)$ on data generated by the molecular dynamics simulation engine HOOMD-blue *during a simulation run*.

Generally, most users will want to run analyses as post-processing steps, on the saved frames of a particle trajectory file. However, it is possible to use analysis callbacks in HOOMD-blue to compute and log quantities at runtime, too. By using analysis methods at runtime, it is possible to stop a simulation early or change the simulation parameters dynamically according to the analysis results.

HOOMD-blue can be installed with `conda install -c conda-forge hoomd`.

The simulation script runs a Monte Carlo simulation of spheres, with outputs parsed with `numpy.genfromtxt`.

```
[1]: %matplotlib inline
import hoomd
from hoomd import hpmc
import freud
import numpy as np
import matplotlib.pyplot as plt

[2]: hoomd.context.initialize('')
system = hoomd.init.create_lattice(
    hoomd.lattice.sc(a=1), n=10)
mc = hpmc.integrate.sphere(seed=42, d=0.1, a=0.1)
mc.shape_param.set('A', diameter=0.5)

rdf = freud.density.RDF(bins=50, r_max=4)
w6 = freud.order.Steinhardt(l=6, wl=True)

def calc_rdf(timestep):
    hoomd.util.quiet_status()
    snap = system.take_snapshot()
    hoomd.util.unquiet_status()
    rdf.compute(system=snap, reset=False)

def calc_W6(timestep):
    hoomd.util.quiet_status()
    snap = system.take_snapshot()
    hoomd.util.unquiet_status()
    w6.compute(system=snap, neighbors={'num_neighbors': 12})
    return np.mean(w6.particle_order)
```

(continues on next page)

(continued from previous page)

```
# Equilibrate the system a bit before accumulating the RDF.
```

```
hoomd.run(1e4)
```

```
hoomd.analyze.callback(calc_rdf, period=100)
```

```
logger = hoomd.analyze.log(filename='output.log',
                           quantities=['w6'],
                           period=100,
                           header_prefix='#',
                           overwrite=True)
```

```
logger.register_callback('w6', calc_W6)
```

```
hoomd.run(1e4)
```

```
# Store the computed RDF in a file
```

```
np.savetxt('rdf.csv', np.vstack((rdf.bin_centers, rdf.rdf)).T,
           delimiter=',', header='r, g(r)')
```

```
HOOMD-blue v2.7.0-77-g568406147 DOUBLE HPMC_MIXED MPI TBB SSE SSE2 SSE3 SSE4_1 SSE4_2_
↪AVX AVX2
```

```
Compiled: 10/28/2019
```

```
Copyright (c) 2009-2019 The Regents of the University of Michigan.
```

```
---
```

```
You are using HOOMD-blue. Please cite the following:
```

- * J A Anderson, C D Lorenz, and A Travesset. "General purpose molecular dynamics simulations fully implemented on graphics processing units", Journal of Computational Physics 227 (2008) 5342-5359
- * J Glaser, T D Nguyen, J A Anderson, P Liu, F Spiga, J A Millan, D C Morse, and S C Glotzer. "Strong scaling of general-purpose molecular dynamics simulations on GPUs", Computer Physics Communications 192 (2015) 97-107

```
---
```

```
---
```

```
You are using HPMC. Please cite the following:
```

- * J A Anderson, M E Irrgang, and S C Glotzer. "Scalable Metropolis Monte Carlo for simulation of hard shapes", Computer Physics Communications 204 (2016) 21-30

```
---
```

```
HOOMD-blue is running on the CPU
```

```
notice(2): Group "all" created containing 1000 particles
```

```
** starting run **
```

```
Time 00:00:10 | Step 3878 / 10000 | TPS 387.761 | ETA 00:00:15
```

```
Time 00:00:20 | Step 7808 / 10000 | TPS 392.99 | ETA 00:00:05
```

```
Time 00:00:25 | Step 10000 / 10000 | TPS 398.521 | ETA 00:00:00
```

```
Average TPS: 392.122
```

```
-----
```

```
notice(2): - HPMC stats:
```

```
notice(2): Average translate acceptance: 0.933106
```

```
notice(2): Trial moves per second: 1.56844e+06
```

```
notice(2): Overlap checks per second: 4.07539e+07
```

```
notice(2): Overlap checks per trial move: 25.9838
```

```
notice(2): Number of overlap errors: 0
```

```
** run complete **
```

```
** starting run **
```

```
Time 00:00:35 | Step 13501 / 20000 | TPS 349.776 | ETA 00:00:18
```

```
Time 00:00:45 | Step 17001 / 20000 | TPS 349.699 | ETA 00:00:08
```

```
Time 00:00:54 | Step 20000 / 20000 | TPS 352.224 | ETA 00:00:00
```

```
Average TPS: 350.471
```

(continues on next page)

(continued from previous page)

```


-----
notice(2): - HPMC stats:
notice(2): Average translate acceptance: 0.932846
notice(2): Trial moves per second:      1.40185e+06
notice(2): Overlap checks per second:   3.63552e+07
notice(2): Overlap checks per trial move: 25.9338
notice(2): Number of overlap errors:    0
** run complete **

```

```

[3]: rdf_data = np.genfromtxt('rdf.csv', delimiter=',')
plt.plot(rdf_data[:, 0], rdf_data[:, 1])
plt.title('Radial Distribution Function')
plt.xlabel('$r$')
plt.ylabel('$g(r)$')
plt.show()


```



```

[4]: w6_data = np.genfromtxt('output.log')
plt.plot(w6_data[:, 0], w6_data[:, 1])
plt.title('$w_6$ Order Parameter')
plt.xlabel('$t$')
plt.ylabel('$w_6(t)$')
plt.show()

```



Analyzing data from LAMMPS

The following script shows how to use `freud` to compute the radial distribution function $g(r)$ on data generated by the molecular dynamics simulation engine LAMMPS. The input script runs a Lennard-Jones system, which is then parsed with `numpy.genfromtxt`.

The input script is below. Note that we must dump images with `ix iy iz`, so that the mean squared displacement can be calculated correctly.

```
[1]: !cat lj.in

# From http://utkstair.org/clausius/docs/mse614/text/examples.html
# define units
units      lj

# specify periodic boundary conditions
boundary p p p

# define atom_style
# full covers everything
atom_style full

# define simulation volume
# If I want N = 512 atoms
# and I want a density of rho = 0.5 atoms/lj-sigma^3
# Then I can determine the size of a cube by
# size = (N/rho)^(1/3)
variable side      equal 10
region            boxid block 0.0 ${side} 0.0 ${side} 0.0 ${side}
create_box 1 boxid

# specify initial positions of atoms
# sc = simple cubic
# 0.5 = density in lj units
lattice          sc 0.50
```

(continues on next page)

(continued from previous page)

```

# place atoms of type 1 in boxid
create_atoms      1 box

# define mass of atom type 1
mass              1 1.0

# specify initial velocity of atoms
# group = all
# reduced temperature is T = 1.0 = lj-eps/kb
# seed for random number generator
# distribution is gaussian (e.g. Maxwell-Boltzmann)
velocity         all create 1.0 87287 dist gaussian

# specify interaction potential
# pairwise interaction via the Lennard-Jones potential with a cut-off at 2.5 lj-sigma
pair_style        lj/cut 2.5

# specify parameters between atoms of type 1 with an atom of type 1
# epsilon = 1.0, sigma = 1.0, cutoff = 2.5
pair_coeff        1 1 1.0 1.0 2.5

# add long-range tail correction
pair_modify tail yes

# specify parameters for neighbor list
# rnbr = rcut + 0.3
neighbor         0.3 bin

# specify thermodynamic properties to be output
# pe = potential energy
# ke = kinetic energy
# etotal = pe + ke
# temp = temperature
# press = pressure
# density = number density
# output every thousand steps
# norm = normalize by # of atoms (yes or no)
thermo_style      custom step pe ke etotal temp press density

# report instantaneous thermo values every 100 steps
thermo 100

# normalize thermo properties by number of atoms (yes or no)
thermo_modify norm no

# specify ensemble
# fixid = 1
# atoms = all
# ensemble = nve or nvt
fix              1 all nve

timestep 0.005

# run 1000 steps in the NVE ensemble
# (this equilibrates positions)
run 1000

```

(continues on next page)

(continued from previous page)

```

# stop fix with given fixid
# fixid = 1
unfix 1

# specify ensemble
# fixid = 2
# atoms = all
# ensemble = nvt
# temp = temperature
# initial temperature = 1.0
# final temperature = 1.0
# thermostat controller gain = 0.1 (units of time, bigger is less tight control)
fix      2 all nvt temp 1.0 1.0 0.1

# run 1000 steps in the NVT ensemble
# (this equilibrates thermostat)
run      1000

# save configurations
# dumpid = 1
# all atoms
# atomic symbol is Ar
# save positions every 100 steps
# filename = output.xyz
#
dump      2      all custom 100 output_custom.xyz x y z ix iy iz

# run 1000 more steps in the NVT ensemble
# (this is data production, from which configurations are saved)
run      8000

```

Next, we run LAMMPS to generate the output file. LAMMPS can be installed with `conda install -c conda-forge lammmps`.

```
[2]: !lmp_serial -in lj.in
```

```

LAMMPS (5 Jun 2019)
Created orthogonal box = (0 0 0) to (10 10 10)
  1 by 1 by 1 MPI processor grid
Lattice spacing in x,y,z = 1.25992 1.25992 1.25992
Created 512 atoms
  create_atoms CPU = 0.00122023 secs
Neighbor list info ...
  update every 1 steps, delay 10 steps, check yes
  max neighbors/atom: 2000, page size: 100000
  master list distance cutoff = 2.8
  ghost atom cutoff = 2.8
  binsize = 1.4, bins = 8 8 8
  1 neighbor lists, perpetual/occasional/extra = 1 0 0
  (1) pair lj/cut, perpetual
      attributes: half, newton on
      pair build: half/bin/newton
      stencil: half/bin/3d/newton
      bin: standard
Setting up Verlet run ...
  Unit style      : lj

```

(continues on next page)

(continued from previous page)

```

Current step : 0
Time step    : 0.005
Per MPI rank memory allocation (min/avg/max) = 6.109 | 6.109 | 6.109 Mbytes
Step PotEng KinEng TotEng Temp Press Density
  0    -1804.3284      766.5  -1037.8284          1   -2.1872025      0.512
 100   -1834.8127     774.55302 -1060.2596     1.0105062  -0.32671112     0.512
 200   -1852.2773     789.53605 -1062.7413     1.0300536  -0.30953463     0.512
 300   -1857.4621     795.78772 -1061.6744     1.0382097  -0.22960441     0.512
 400   -1864.766      801.81089 -1062.9551     1.0460677  -0.24901206     0.512
 500   -1860.0198     796.65657 -1063.3633     1.0393432  -0.14280039     0.512
 600   -1859.1835     796.96259 -1062.221      1.0397425  -0.2828161      0.512
 700   -1848.9874     786.01864 -1062.9688     1.0254646  -0.34512435     0.512
 800   -1821.7263     759.86418 -1061.8622     0.9913427  -0.1766353      0.512
 900   -1840.7256     777.68022 -1063.0453     1.0145861  -0.318844       0.512
1000   -1862.6606     799.32963 -1063.3309     1.0428306  -0.25224674     0.512
Loop time of 0.197457 on 1 procs for 1000 steps with 512 atoms

```

Performance: 2187817.275 tau/day, 5064.392 timesteps/s
 99.5% CPU use with 1 MPI tasks x no OpenMP threads

MPI task timing breakdown:

Section	min time	avg time	max time	%varavg	%total
Pair	0.13402	0.13402	0.13402	0.0	67.87
Bond	8.2254e-05	8.2254e-05	8.2254e-05	0.0	0.04
Neigh	0.049226	0.049226	0.049226	0.0	24.93
Comm	0.0084078	0.0084078	0.0084078	0.0	4.26
Output	0.00015664	0.00015664	0.00015664	0.0	0.08
Modify	0.0042217	0.0042217	0.0042217	0.0	2.14
Other		0.001339			0.68

```

Nlocal:    512 ave 512 max 512 min
Histogram: 1 0 0 0 0 0 0 0 0 0
Nghost:    1447 ave 1447 max 1447 min
Histogram: 1 0 0 0 0 0 0 0 0 0
Neighs:    12018 ave 12018 max 12018 min
Histogram: 1 0 0 0 0 0 0 0 0 0

```

```

Total # of neighbors = 12018
Ave neighs/atom = 23.4727
Ave special neighs/atom = 0
Neighbor list builds = 100
Dangerous builds = 100
Setting up Verlet run ...

```

```

Unit style : lj
Current step : 1000
Time step : 0.005
Per MPI rank memory allocation (min/avg/max) = 6.109 | 6.109 | 6.109 Mbytes
Step PotEng KinEng TotEng Temp Press Density
1000  -1862.6606     799.32963 -1063.3309     1.0428306  -0.25224674     0.512
1100  -1853.4242     819.28434 -1034.1399     1.0688641  -0.16446166     0.512
1200  -1840.5875     793.33971 -1047.2477     1.0350159  -0.21578932     0.512
1300  -1838.9016     796.0771  -1042.8245     1.0385872  -0.19354995     0.512
1400  -1848.5392     752.5312  -1096.008     0.98177587  -0.22928676     0.512
1500  -1856.8763     746.44097 -1110.4353     0.97383035  -0.18936813     0.512
1600  -1869.5931     732.08398 -1137.5091     0.95509978  -0.2751998      0.512
1700  -1887.7451     761.66169 -1126.0834     0.99368779  -0.35301947     0.512

```

(continues on next page)

(continued from previous page)

```

1800 -1882.9325 729.51153 -1153.421 0.95174368 -0.33872437 0.512
1900 -1867.9452 763.40829 -1104.5369 0.99596646 -0.30614623 0.512
2000 -1874.4475 752.8181 -1121.6294 0.98215017 -0.30908533 0.512
Loop time of 0.199068 on 1 procs for 1000 steps with 512 atoms

```

Performance: 2170111.968 tau/day, 5023.407 timesteps/s
 99.7% CPU use with 1 MPI tasks x no OpenMP threads

MPI task timing breakdown:

Section	min time	avg time	max time	%varavg	%total
Pair	0.13415	0.13415	0.13415	0.0	67.39
Bond	6.5804e-05	6.5804e-05	6.5804e-05	0.0	0.03
Neigh	0.049349	0.049349	0.049349	0.0	24.79
Comm	0.0079701	0.0079701	0.0079701	0.0	4.00
Output	0.00013518	0.00013518	0.00013518	0.0	0.07
Modify	0.0060918	0.0060918	0.0060918	0.0	3.06
Other		0.001308			0.66

```

Nlocal: 512 ave 512 max 512 min
Histogram: 1 0 0 0 0 0 0 0 0 0
Nghost: 1464 ave 1464 max 1464 min
Histogram: 1 0 0 0 0 0 0 0 0 0
Neighs: 11895 ave 11895 max 11895 min
Histogram: 1 0 0 0 0 0 0 0 0 0

```

```

Total # of neighbors = 11895
Ave neighs/atom = 23.2324
Ave special neighs/atom = 0
Neighbor list builds = 100
Dangerous builds = 100
Setting up Verlet run ...
Unit style : lj
Current step : 2000
Time step : 0.005

```

Per MPI rank memory allocation (min/avg/max) = 7.383 | 7.383 | 7.383 Mbytes

Step	PotEng	KinEng	TotEng	Temp	Press	Density
2000	-1874.4475	752.8181	-1121.6294	0.98215017	-0.30908533	0.512
2100	-1858.3201	763.1433	-1095.1768	0.99562074	-0.25351893	0.512
2200	-1866.9213	770.43352	-1096.4878	1.0051318	-0.27646217	0.512
2300	-1879.7957	721.28174	-1158.514	0.94100683	-0.31881659	0.512
2400	-1886.0524	740.29981	-1145.7526	0.96581841	-0.36988824	0.512
2500	-1862.4955	731.77932	-1130.7162	0.95470231	-0.23656666	0.512
2600	-1847.542	748.14185	-1099.4002	0.97604938	-0.22297358	0.512
2700	-1863.1603	715.01181	-1148.1485	0.93282689	-0.27535839	0.512
2800	-1858.9263	711.64082	-1147.2855	0.92842899	-0.31272288	0.512
2900	-1862.0527	788.4678	-1073.5849	1.0286599	-0.20135611	0.512
3000	-1848.1516	797.66227	-1050.4894	1.0406553	-0.27353978	0.512
3100	-1883.8621	793.05475	-1090.8073	1.0346442	-0.29972206	0.512
3200	-1890.4065	791.32467	-1099.0819	1.032387	-0.35642545	0.512
3300	-1859.2997	745.34089	-1113.9588	0.97239516	-0.26722308	0.512
3400	-1869.8929	762.57135	-1107.3216	0.99487457	-0.14226646	0.512
3500	-1879.6557	732.72846	-1146.9273	0.95594058	-0.21775981	0.512
3600	-1899.0227	766.18046	-1132.8422	0.99958312	-0.2798366	0.512
3700	-1872.6895	817.06218	-1055.6273	1.065965	-0.23193326	0.512
3800	-1891.1356	802.56843	-1088.5672	1.047056	-0.23387156	0.512
3900	-1840.088	753.28729	-1086.8007	0.98276228	-0.21465531	0.512

(continues on next page)

(continued from previous page)

4000	-1882.7617	803.22857	-1079.5332	1.0479172	-0.31896543	0.512
4100	-1873.9061	787.05281	-1086.8533	1.0268138	-0.26608644	0.512
4200	-1871.6627	832.59728	-1039.0655	1.0862326	-0.29040189	0.512
4300	-1865.3725	819.61212	-1045.7603	1.0692917	-0.22592305	0.512
4400	-1875.5306	806.71297	-1068.8176	1.0524631	-0.31604788	0.512
4500	-1857.109	828.16158	-1028.9474	1.0804456	-0.2464398	0.512
4600	-1857.8912	729.7257	-1128.1655	0.9520231	-0.31385004	0.512
4700	-1842.205	734.17836	-1108.0267	0.95783217	-0.27130372	0.512
4800	-1864.7696	776.14641	-1088.6232	1.012585	-0.31668109	0.512
4900	-1858.1103	793.41913	-1064.6911	1.0351195	-0.16583366	0.512
5000	-1867.7818	815.23276	-1052.5491	1.0635783	-0.28680645	0.512
5100	-1838.0477	725.412	-1112.6357	0.9463953	-0.28647867	0.512
5200	-1810.7731	731.9772	-1078.7959	0.95496047	-0.16033508	0.512
5300	-1837.5311	749.48424	-1088.0469	0.97780071	-0.20281441	0.512
5400	-1873.1094	764.60064	-1108.5088	0.99752204	-0.41358648	0.512
5500	-1888.9361	748.61774	-1140.3184	0.97667025	-0.36938658	0.512
5600	-1869.9513	762.05258	-1107.8988	0.99419776	-0.4223791	0.512
5700	-1858.339	746.55871	-1111.7803	0.97398396	-0.42269281	0.512
5800	-1863.2613	749.34951	-1113.9118	0.97762493	-0.38710722	0.512
5900	-1873.7293	773.93107	-1099.7982	1.0096948	-0.26021895	0.512
6000	-1873.456	787.00426	-1086.4518	1.0267505	-0.22677264	0.512
6100	-1856.3965	789.71834	-1066.6782	1.0302914	-0.23662444	0.512
6200	-1868.1487	781.09973	-1087.0489	1.0190473	-0.13471937	0.512
6300	-1873.9941	740.70637	-1133.2877	0.96634882	-0.26089329	0.512
6400	-1879.5293	758.83006	-1120.6993	0.98999355	-0.40717493	0.512
6500	-1873.208	730.21233	-1142.9956	0.95265797	-0.33679524	0.512
6600	-1893.088	738.17171	-1154.9163	0.96304202	-0.34898503	0.512
6700	-1854.9994	735.97428	-1119.0252	0.96017518	-0.28228204	0.512
6800	-1841.9759	797.06384	-1044.9121	1.0398745	-0.19145452	0.512
6900	-1850.4935	786.14747	-1064.3461	1.0256327	-0.29327665	0.512
7000	-1845.6749	797.15417	-1048.5207	1.0399924	-0.45867335	0.512
7100	-1831.03	827.34343	-1003.6866	1.0793782	-0.179498	0.512
7200	-1888.1042	749.22706	-1138.8771	0.97746518	-0.53010406	0.512
7300	-1859.9233	754.0352	-1105.8881	0.98373803	-0.39545192	0.512
7400	-1851.9183	787.60897	-1064.3093	1.0275394	-0.37094061	0.512
7500	-1848.0739	759.73299	-1088.3409	0.99117155	-0.34780329	0.512
7600	-1853.6532	764.84642	-1088.8067	0.99784269	-0.098590718	0.512
7700	-1876.6886	756.38707	-1120.3016	0.98680636	-0.17912577	0.512
7800	-1857.6403	719.20424	-1138.4361	0.93829647	-0.32247855	0.512
7900	-1891.2369	707.44358	-1183.7933	0.92295314	-0.44928961	0.512
8000	-1930.5545	747.85472	-1182.6997	0.97567478	-0.2607688	0.512
8100	-1931.3403	744.07929	-1187.261	0.97074924	-0.36763161	0.512
8200	-1920.9036	757.0399	-1163.8637	0.98765806	-0.29103201	0.512
8300	-1904.5561	747.57535	-1156.9807	0.9753103	-0.38464012	0.512
8400	-1844.7405	820.31281	-1024.4277	1.0702059	-0.044405706	0.512
8500	-1860.3078	809.13555	-1051.1723	1.0556237	-0.018849627	0.512
8600	-1841.1531	776.85955	-1064.2935	1.0135154	-0.080192818	0.512
8700	-1860.6583	785.807	-1074.8513	1.0251885	-0.29734141	0.512
8800	-1841.0455	779.78036	-1061.2651	1.017326	-0.11420405	0.512
8900	-1887.3837	878.92659	-1008.4571	1.1466753	-0.34666733	0.512
9000	-1879.4834	767.25891	-1112.2245	1.0009901	-0.3331713	0.512
9100	-1900.1999	818.54475	-1081.6552	1.0678992	-0.19458572	0.512
9200	-1882.1203	794.90843	-1087.2118	1.0370625	-0.25879106	0.512
9300	-1893.5664	783.13068	-1110.4357	1.0216969	-0.25735285	0.512
9400	-1893.5147	756.00962	-1137.5051	0.98631392	-0.26461519	0.512
9500	-1908.8115	742.60538	-1166.2061	0.96882633	-0.4468834	0.512
9600	-1887.0565	762.24949	-1124.807	0.99445465	-0.36695082	0.512

(continues on next page)

(continued from previous page)

```

    9700   -1878.5858    771.53563   -1107.0502    1.0065696   -0.2300855    0.512
    9800   -1848.4047    752.27373   -1096.1309    0.98143997   -0.28729274   0.512
    9900   -1865.561    731.41466   -1134.1464    0.95422656   -0.3874617    0.512
   10000   -1887.2808    787.80237   -1099.4784    1.0277917   -0.26779032   0.512
Loop time of 1.63759 on 1 procs for 8000 steps with 512 atoms

Performance: 2110423.670 tau/day, 4885.240 timesteps/s
99.4% CPU use with 1 MPI tasks x no OpenMP threads

MPI task timing breakdown:
Section | min time | avg time | max time | %varavg | %total
-----|-----|-----|-----|-----|-----
Pair    | 1.0823   | 1.0823   | 1.0823   | 0.0     | 66.09
Bond    | 0.00054955 | 0.00054955 | 0.00054955 | 0.0     | 0.03
Neigh   | 0.39492   | 0.39492   | 0.39492   | 0.0     | 24.12
Comm    | 0.064503   | 0.064503   | 0.064503   | 0.0     | 3.94
Output  | 0.035598   | 0.035598   | 0.035598   | 0.0     | 2.17
Modify  | 0.049172   | 0.049172   | 0.049172   | 0.0     | 3.00
Other   |           | 0.01058   |           |         | 0.65

Nlocal:   512 ave 512 max 512 min
Histogram: 1 0 0 0 0 0 0 0 0
Nghost:   1398 ave 1398 max 1398 min
Histogram: 1 0 0 0 0 0 0 0 0
Neighs:   12036 ave 12036 max 12036 min
Histogram: 1 0 0 0 0 0 0 0 0

Total # of neighbors = 12036
Ave neighs/atom = 23.5078
Ave special neighs/atom = 0
Neighbor list builds = 800
Dangerous builds = 800
Total wall time: 0:00:02

```

```
[3]: %matplotlib inline
```

```

import freud
from matplotlib import pyplot as plt
import numpy as np
import warnings

```

```

[4]: with warnings.catch_warnings():
    warnings.simplefilter('ignore')
    # We read the number of particles, the system box, and the
    # particle positions into 3 separate arrays.
    N = int(np.genfromtxt(
        'output_custom.xyz', skip_header=3, max_rows=1))
    box_data = np.genfromtxt(
        'output_custom.xyz', skip_header=5, max_rows=3)
    data = np.genfromtxt(
        'output_custom.xyz', skip_header=9,
        invalid_raise=False)

    # Remove the unwanted text rows
    data = data[~np.isnan(data).all(axis=1)].reshape(-1, N, 6)

```

(continues on next page)

(continued from previous page)

```

box = freud.box.Box.from_box(
    box_data[:, 1] - box_data[:, 0])


# We shift the system by half the box lengths to match the
# freud coordinate system, which is centered at the origin.
# Since all methods support periodicity, this shift is simply
# for consistency but does not affect any analyses.
data[:, :3] -= box.L/2
rdf = freud.density.RDF(bins=100, r_max=4, r_min=1)
for frame in data:
    rdf.compute(system=(box, frame[:, :3]), reset=False)


msd = freud.msd.MSD(box)
msd.compute(positions=data[:, :, :3], images=data[:, :, 3:])

# Plot the RDF
plt.plot(rdf.bin_centers, rdf.rdf)
plt.title('Radial Distribution Function')
plt.xlabel('$r$')
plt.ylabel('$g(r)$')
plt.show()

# Plot the MSD
plt.plot(msd.msd)
plt.title('Mean Squared Displacement')
plt.xlabel('$t$')
plt.ylabel('MSD$(t)$')
plt.show()

```





Using Machine Learning for Structural Identification

This notebook provides a demonstration of how a simple set of descriptors computed by freud can be coupled with machine learning for structural identification. The set of descriptors used here are not enough to identify complex crystal structures, but this notebook provides an introduction. For a more powerful set of descriptors, see the paper [Machine learning for crystal identification and discovery \(Spellings 2018\)](#) and the library [pythia](#), both of which use freud for their computations.

```
[1]: import freud
import matplotlib.pyplot as plt
import matplotlib.cm
import numpy as np
import pandas as pd
import warnings
warnings.filterwarnings("ignore")
```

We generate sample body-centered cubic, face-centered cubic, and simple cubic structures. Each structure has at least 4000 particles.

```
[2]: N = 4000
noise = 0.04
structures = {}
n = round((N/2)**(1/3))
structures['bcc'] = freud.data.UnitCell.bcc().generate_system(n, sigma_noise=noise)
n = round((N/4)**(1/3))
structures['fcc'] = freud.data.UnitCell.fcc().generate_system(n, sigma_noise=noise)
n = round((N/1)**(1/3))
structures['sc'] = freud.data.UnitCell.sc().generate_system(n, sigma_noise=noise)
for name, (box, positions) in structures.items():
    print(name, 'has', len(positions), 'particles.')
```

```
bcc has 4394 particles.
fcc has 4000 particles.
sc has 4096 particles.
```

Next, we compute the Steinhardt order parameters q_l for $l \in \{4, 6, 8, 10, 12\}$.

We use the Voronoi neighbor list, removing neighbors whose Voronoi facets are small.


```
[3]: def get_features(box, positions, structure):
    voro = freud.locality.Voronoi()
    voro.compute(system=(box, positions))
    nlist = voro.nlist.copy()
    nlist.filter(nlist.weights > 0.1)
    features = {}
    for l in [4, 6, 8, 10, 12]:
        ql = freud.order.Steinhardt(l=l, weighted=True)
        ql.compute(system=(box, positions), neighbors=nlist)
        features['q{}'.format(l)] = ql.particle_order


    return features
```

```
[4]: structure_features = {}
    for name, (box, positions) in structures.items():
        structure_features[name] = get_features(box, positions, name)
```

Here, we plot a histogram of the q_4 and q_6 values for each structure.

```
[5]: for l in [4, 6]:
    plt.figure(figsize=(3, 2), dpi=300)
    for name in structures.keys():
        plt.hist(structure_features[name]['q{}'.format(l)], range=(0, 1), bins=100,
        ↪label=name, alpha=0.7)
    plt.title(r'$q_{\{\{l\}\}}$'.format(l=l))
    plt.legend()
    for lh in plt.legend().legendHandles:
        lh.set_alpha(1)
    plt.show()
```





Next, we will train a Support Vector Machine to predict particles' structures based on these Steinhardt Q_l descriptors. We build pandas data frames to hold the structure features, encoding the structure as an integer. We use `train_test_split` to train on part of the data and test the model on a separate part of the data.

```
[6]: structure_dfs = {}
     for i, structure in enumerate(structure_features):
         df = pd.DataFrame.from_dict(structure_features[structure])
         df['class'] = i
         structure_dfs[structure] = df
```

```
[7]: df = pd.concat(structure_dfs.values()).reset_index(drop=True)
```

```
[8]: from sklearn.preprocessing import normalize
     from sklearn.model_selection import train_test_split
     from sklearn.svm import SVC
```

```
[9]: X = df.drop('class', axis=1).values
     X = normalize(X)
     y = df['class'].values
     X_train, X_test, y_train, y_test = train_test_split(
         X, y, test_size=0.33, random_state=42)

     svm = SVC()
     svm.fit(X_train, y_train)
```

(continues on next page)

(continued from previous page)

```
print('Score:', svm.score(X_test, y_test))
```

Score: 0.9868995633187773


Finally, we use the Uniform Manifold Approximation and Projection method ([McInnes 2018](#), [GitHub repo](#)) to project the high-dimensional descriptors into a two-dimensional plot. Notice that some bcc particles overlap with fcc particles. This can be expected from the noise that was added to the structures. The particles that were incorrectly classified by the SVM above are probably located in this overlapping region.

```
[10]: from umap import UMAP
      umap = UMAP(random_state=42)

      X_reduced = umap.fit_transform(X)

[11]: plt.figure(figsize=(4, 3), dpi=300)
      for i in range(max(y) + 1):
          indices = np.where(y == i)[0]
          plt.scatter(X_reduced[indices, 0], X_reduced[indices, 1],
                      color=matplotlib.cm.tab10(i), s=8, alpha=0.2,
                      label=list(structure_features.keys())[i])

      plt.legend()
      for lh in plt.legend().legendHandles:
          lh.set_alpha(1)
      plt.show()
```



Calculating Strain via Voxelization

This notebook shows how to use `freud`'s neighbor finding to create a voxelized version of a system.

In brief, we are going to create a set of points that define the centers of our voxels, then assign all particles to one of these voxels. Then we sum up some property of the particles amongst all particles in a bin.

At the end we want to have a sampling of some particle property in our system on a regular grid (as a NumPy array).

```
[1]: %matplotlib inline
import freud
import numpy as np
import matplotlib.pyplot as plt
import re
from scipy.sparse import csr_matrix, csc_matrix
```

This uses data from some text files that were output from the visualization software OVITO (<https://ovito.org/>)

The files have a header with box information, and then a list of particle info. These files have 10 fields per particle:

```
(ID#, position(x,y,z), strains(xx,yy,zz,yz,xz,xy))
```

The goal is to turn this into an $(N_x, N_y, N_z, 3, 3)$ NumPy array, where N_x, N_y, N_z are the number of bins in each dimension, and each of those bins has an averaged 3x3 strain array.

First we read in the box info from our text files and construct an average box. We need this so we can make our bin centers

```
[2]: framefiles = ['data/strain_data/frame{f}'.format(f=f) for f in [100, 110, 120, 130]]

# read all the boxes, so we can make the grid points for voxelizing
boxes = []
for f in framefiles:
    ff = open(f, 'r')
    _ = ff.readline()
    header = ff.readline()

    match = re.match('^Lattice=".*"', header)
    boxstring = match.group(0)
    boxes.append(np.array(str.split(boxstring[9:-1]), dtype=np.float).reshape((3,3)).
→T)
    ff.close()

# find the average box
ave_box = np.array(boxes).mean(axis=0)
```

Now we make the bin centers using `np.meshgrid`, but append and combine the X, Y, and Z coordinates into an array of shape $(N_x N_y N_z, 3)$ to pass to `freud`.

```
[3]: res = (60, 10, 45) # The number of bins (in x,y,z)
xx = np.linspace(-ave_box[0,0]/2,ave_box[0,0]/2,num=res[0])
yy = np.linspace(-ave_box[1,1]/2,ave_box[1,1]/2,num=res[1])
zz = np.linspace(-ave_box[2,2]/2,ave_box[2,2]/2,num=res[2])
XX, YY, ZZ = np.meshgrid(xx,yy,zz)

XYZ = np.append(np.append(XX.flatten().reshape((-1,1)),
                          YY.flatten().reshape((-1,1)), axis=1),
                ZZ.flatten().reshape((-1,1)), axis=1).astype(np.float32)
```

Now we iterate over our files and compute the first nearest neighbor (among the bin centers) of the particles, so we know which bin to average them in.

It is important to use scipy's `csc_matrix` for this process when the number of particles is large. These files contain >80,000 particles, and without the sparse matrix, the dot product to determine grid totals would be extremely slow.

```
[4]: master_strains = np.zeros((XYZ.shape[0], 6)) # matrix to sum into

for i in range(len(framefiles)):
    data = np.loadtxt(framefiles[i], skiprows=2).astype(np.float32)

    box = freud.box.Box(Lx=boxes[i][0, 0],
                        Ly=boxes[i][1, 1],
                        Lz=boxes[i][2, 2],
                        yz=boxes[i][1, 2],
                        xz=boxes[i][0, 2],
                        xy=boxes[i][0, 1])
    nlist = freud.AABBQuery(box, XYZ).query(
        data[:,1:4], {'num_neighbors': 1}).toNeighborList()
    neighbors = nlist.point_indices

    sprse = csc_matrix((np.ones(len(neighbors)), (neighbors, np.
    ↪ arange(len(neighbors)))),
                        shape=(XYZ.shape[0], len(neighbors)))

    # strain data
    sdata = data[:, 4:]
    binned = np.zeros((XYZ.shape[0], 6))
    # number of particles in each bin
    grid_totals = sprse.dot(np.ones(len(neighbors)))
    grid_totals[grid_totals==0] = 1 # get rid of division errors

    for j in range(6):
        binned[:,j] = sprse.dot(sdata[:, j]) / grid_totals

    master_strains = master_strains + binned

master_strains = master_strains/len(framefiles) # divide by number of frames
```

Now we pack up the resulting array into the shape we want it to be: $(N_x, N_y, N_z, 3, 3)$


```
[5]: final_matrix = np.zeros((res[1],res[0],res[2],3,3))

# this mapping turns 6 strain values into a symmetric (3,3) matrix
voigt_map = {0:(0,0), 1:(1,1), 2:(2,2), 3:(1,2), 4:(0,2), 5:(0,1)}

for i in range(6):
    v = voigt_map[i]
    final_matrix[:, :, :, v[0], v[1]] = master_strains[:, i].reshape(res[1], res[0], res[2])
    if v[0] != v[1]:
        final_matrix[:, :, :, v[1], v[0]] = master_strains[:, i].reshape(res[1], res[0],
    ↪ res[2])
```

Since we are only using four frames, the distribution is not very well sampled. But we can get a clue that a distinct distribution of strain is emerging if we average along the first axis of the matrix (this particular system should not vary in that direction)

```
[6]: plt.figure(figsize=(10,10))
plt.imshow(final_matrix[:, :, :, 0, 0].mean(axis=0),
           origin='lower', cmap=plt.cm.bwr,
           vmin=-0.04, vmax=0.04, interpolation='none')
plt.colorbar()
plt.show()
```



Visualizing analyses with fresnel

In this notebook, we simulate a system of tetrahedra, color particles according to their local density, and path-trace the resulting image with `fresnel`.

The cell below runs a short `HOOMD-blue` simulation of tetrahedra using Hard Particle Monte Carlo (HPMC).

```
[1]: import hoomd
import hoomd.hpmc
hoomd.context.initialize('')

# Create an 8x8x8 simple cubic lattice
system = hoomd.init.create_lattice(
    unitcell=hoomd.lattice.sc(a=1.5), n=8)

# Create our tetrahedra and configure the HPMC integrator
mc = hoomd.hpmc.integrate.convex_polyhedron(seed=42)
mc.set_params(d=0.2, a=0.1)
vertices = [( 0.5, 0.5, 0.5),
            (-0.5,-0.5, 0.5),
            (-0.5, 0.5,-0.5),
            ( 0.5,-0.5,-0.5)]
mc.shape_param.set('A', vertices=vertices)

# Run for 5,000 steps
hoomd.run(5e3)
snap = system.take_snapshot()
```

HOOMD-blue v2.6.0-151-gea140cffb DOUBLE HPMC_MIXED MPI TBB SSE SSE2 SSE3 SSE4_1_
→SSE4_2 AVX AVX2
Compiled: 09/25/2019
Copyright (c) 2009-2019 The Regents of the University of Michigan.

You are using HOOMD-blue. Please cite the following:
* J A Anderson, C D Lorenz, and A Travesset. "General purpose molecular dynamics simulations fully implemented on graphics processing units", Journal of Computational Physics 227 (2008) 5342-5359
* J Glaser, T D Nguyen, J A Anderson, P Liu, F Spiga, J A Millan, D C Morse, and S C Glotzer. "Strong scaling of general-purpose molecular dynamics simulations on GPUs", Computer Physics Communications 192 (2015) 97-107

You are using HPMC. Please cite the following:
* J A Anderson, M E Irrgang, and S C Glotzer. "Scalable Metropolis Monte Carlo for simulation of hard shapes", Computer Physics Communications 204 (2016) 21-30

HOOMD-blue is running on the CPU
notice(2): Group "all" created containing 512 particles
** starting run **
Time 00:00:10 | Step 2094 / 5000 | TPS 209.394 | ETA 00:00:13
Time 00:00:20 | Step 4238 / 5000 | TPS 214.352 | ETA 00:00:03
Time 00:00:23 | Step 5000 / 5000 | TPS 213.528 | ETA 00:00:00
Average TPS: 212.118

notice(2): - HPMC stats:
notice(2): Average translate acceptance: 0.749166
notice(2): Average rotate acceptance: 0.867601
notice(2): Trial moves per second: 434403

(continues on next page)

(continued from previous page)

```
notice(2): Overlap checks per second:      3.12535e+07
notice(2): Overlap checks per trial move: 71.946
notice(2): Number of overlap errors:      0
** run complete **
```

Now we import the modules needed for analysis and visualization.

```
[2]: import fresnel
import freud
import matplotlib.cm
from matplotlib.colors import Normalize
import numpy as np
device = fresnel.Device()
```

Next, we'll set up the arrays needed for the scene and its geometry. This includes the analysis used for coloring particles.

```
[3]: poly_info = fresnel.util.convex_polyhedron_from_vertices(vertices)
positions = snap.particles.position
orientations = snap.particles.orientation
box = freud.Box.from_box(snap.box)
ld = freud.density.LocalDensity(3.0, 1.0)
ld.compute(system=snap)
colors = matplotlib.cm.viridis(Normalize()(ld.density))
box_points = np.asarray([
    box.make_absolute(
        [[0, 0, 0], [0, 0, 0], [0, 0, 0], [1, 1, 0],
         [1, 1, 0], [1, 1, 0], [0, 1, 1], [0, 1, 1],
         [0, 1, 1], [1, 0, 1], [1, 0, 1], [1, 0, 1]]),
    box.make_absolute(
        [[1, 0, 0], [0, 1, 0], [0, 0, 1], [1, 0, 0],
         [0, 1, 0], [1, 1, 1], [1, 1, 1], [0, 1, 0],
         [0, 0, 1], [0, 0, 1], [1, 1, 1], [1, 0, 0]]))])
```


This cell creates the scene and geometry objects to be rendered by fresnel.

```
[4]: scene = fresnel.Scene(device)
geometry = fresnel.geometry.ConvexPolyhedron(
    scene, poly_info,
    position=positions,
    orientation=orientations,
    color=fresnel.color.linear(colors))
geometry.material = fresnel.material.Material(
    color=fresnel.color.linear([0.25, 0.5, 0.9]),
    roughness=0.8, primitive_color_mix=1.0)
geometry.outline_width = 0.05
box_geometry = fresnel.geometry.Cylinder(
    scene, points=box_points.swapaxes(0, 1))
box_geometry.radius[:] = 0.1
box_geometry.color[:] = np.tile([0, 0, 0], (12, 2, 1))
box_geometry.material.primitive_color_mix = 1.0
scene.camera = fresnel.camera.fit(scene, view='isometric', margin=0.1)
```

First, we preview the scene. (This doesn't use path tracing, and is much faster.)

```
[5]: fresnel.preview(scene, aa_level=3, w=600, h=600)
```


[5]:



Finally, we use path tracing for a high quality image. The number of light samples can be increased to reduce path tracing noise.

```
[6]: fresnel.pathtrace(scene, light_samples=16, w=600, h=600)
```

[6]:



Visualization with plato

In this notebook, we run a Lennard-Jones simulation, color particles according to their local density computed with `freud`, and display the results with `plato`. Note that `plato` has multiple backends – see the [plato documentation](#) for information about each backend and the features it supports.

```
[1]: import hoomd
import hoomd.md
hoomd.context.initialize('')

# Silence the HOOMD output
hoomd.util.quiet_status()
hoomd.option.set_notice_level(0)
```

(continues on next page)

(continued from previous page)

```

# Create a 10x10x10 simple cubic lattice of particles with type name A
system = hoemd.init.create_lattice(unitcell=hoemd.lattice.sc(a=1.5, type_name='A'),
    ↪n=10)

# Specify Lennard-Jones interactions between particle pairs
nl = hoemd.md.nlist.cell()
lj = hoemd.md.pair.lj(r_cut=3.0, nlist=nl)
lj.pair_coeff.set('A', 'A', epsilon=1.0, sigma=1.0)

# Integrate at constant temperature
hoemd.md.integrate.mode_standard(dt=0.005)
integrator = hoemd.md.integrate.nvt(group=hoemd.group.all(), kT=0.01, tau=0.5)
integrator.randomize_velocities(seed=42)

# Run for 10,000 time steps
hoemd.run(10e3)
snap = system.take_snapshot()

HOOMD-blue v2.6.0-151-gea140cffb DOUBLE HPMC_MIXED MPI TBB SSE SSE2 SSE3 SSE4_1_
    ↪SSE4_2 AVX AVX2
Compiled: 09/25/2019
Copyright (c) 2009-2019 The Regents of the University of Michigan.
---
You are using HOOMD-blue. Please cite the following:
* J A Anderson, C D Lorenz, and A Travesset. "General purpose molecular dynamics
  simulations fully implemented on graphics processing units", Journal of
  Computational Physics 227 (2008) 5342-5359
* J Glaser, T D Nguyen, J A Anderson, P Liu, F Spiga, J A Millan, D C Morse, and
  S C Glotzer. "Strong scaling of general-purpose molecular dynamics simulations
  on GPUs", Computer Physics Communications 192 (2015) 97-107
---
HOOMD-blue is running on the CPU

```

Now we import the modules needed for visualization.

```

[2]: import freud
import matplotlib.cm
from matplotlib.colors import Normalize
import numpy as np
import plato
# For interactive scenes, use:
import plato.draw.pythreejs as draw
# For static scenes, use:
#import plato.draw.fresnel as draw

```

This code sets up the plato Scene object with the particles and colors computed above.

```

[3]: positions = snap.particles.position
box = freud.Box.from_box(snap.box)
ld = freud.density.LocalDensity(3.0, 1.0)
ld.compute(system=snap)
colors = matplotlib.cm.viridis(Normalize()(ld.density))
radii = np.ones(len(positions)) * 0.5
box_prim = draw.Box.from_box(box, width=0.2)
sphere_prim = draw.Spheres(
    positions=snap.particles.position,
    radii=radii,

```

(continues on next page)

(continued from previous page)

```

    colors=colors,
    vertex_count=32)
scene = draw.Scene((sphere_prim, box_prim), zoom=1.5)

```

Click and drag the 3D scene below - it's interactive!

```

[4]: scene.show()

Renderer(camera=OrthographicCamera(bottom=-15.0,
↳ children=(DirectionalLight(intensity=0.692820323027551, posit...

```

Visualizing 3D Voronoi and Voxelization

The `plato-draw` package allows for visualizing particle data in 2D and 3D using a variety of backend libraries. Here, we show a 3D Voronoi diagram drawn using `fresnel` and `pythreejs`. We use `rowan` to generate the view rotation.

To install dependencies:

- `conda install -c conda-forge fresnel`
- `pip install plato-draw rowan`

```

[1]: import freud
import matplotlib.cm
import numpy as np
import rowan
import plato.draw.fresnel
backend = plato.draw.fresnel
# For interactive scenes:
# import plato.draw.pythreejs
# backend = plato.draw.pythreejs

[2]: def plot_crystal(box, positions, colors=None, radii=None, backend=None,
    polytopes=[], polytope_colors=None):
    if backend is None:
        backend = plato.draw.fresnel
    if colors is None:
        colors = np.array([[0.5, 0.5, 0.5, 1]] * len(positions))
    if radii is None:
        radii = np.array([0.5] * len(positions))
    sphere_prim = backend.Spheres(positions=positions, colors=colors, radii=radii)
    box_prim = backend.Box.from_box(box, width=0.1)
    if polytope_colors is None:
        polytope_colors = colors * np.array([1, 1, 1, 0.4])
    polytope_prims = []
    for p, c in zip(polytopes, polytope_colors):
        p_prim = backend.ConvexPolyhedra(
            positions=[[0, 0, 0]], colors=c, vertices=p, outline=0)
        polytope_prims.append(p_prim)
    rotation = rowan.multiply(
        rowan.from_axis_angle([1, 0, 0], np.pi/10),
        rowan.from_axis_angle([0, 1, 0], -np.pi/10))
    scene = backend.Scene([sphere_prim, box_prim, *polytope_prims],
        zoom=3, rotation=rotation)
    if backend is not plato.draw.fresnel:
        scene.enable('directional_light')

```

(continues on next page)

(continued from previous page)

```

else:
    scene.enable('antialiasing')
scene.show()

```

We generate an fcc structure and add Gaussian noise to the positions. Colors are assigned randomly.

```


[3]: np.random.seed(12)
    box, positions = freud.data.UnitCell.fcc().generate_system(3, scale=2, sigma_noise=0.
    ↪05)
    cmap = matplotlib.cm.get_cmap('tab20')
    colors = cmap(np.random.rand(len(positions)))

```

```

[4]: plot_crystal(box, positions, colors, backend=backend)

```




We make a Voronoi tessellation of the system and plot it in 3D. The Voronoi cells are approximately [rhombic dodecahedra](#), which tessellate 3D space in a face-centered cubic lattice.

```

[5]: voro = freud.locality.Voronoi()
    voro.compute(system=(box, positions))
    plot_crystal(box, positions, colors=colors,
    backend=backend, polytopes=voro.polytopes)

```




We generate a voxelization of this space by creating a dense lattice of points on a simple cubic lattice.

```
[6]: def make_cubic_grid(box, voxels_per_side):
      v_space = np.linspace(0, 1, voxels_per_side+1)
      v_space = (v_space[:-1] + v_space[1:])/2 # gets centers of the voxels
      return np.array([box.make_absolute([x, y, z])
                       for x in v_space for y in v_space for z in v_space])
```

```
[7]: voxels_per_side = 30
      cubic_grid = make_cubic_grid(box, voxels_per_side)

      # Make the spheres overlap just a bit
      radii = np.ones(len(cubic_grid)) * 0.8 * np.max(box.L) / voxels_per_side

      plot_crystal(box, cubic_grid, radii=radii, backend=backend)
```




We color the voxels by their first nearest neighbor. This is mathematically equivalent to being inside the corresponding Voronoi cell. Here, we get the neighbor indices (this can be used to separate the Voronoi cells into voxels).

```
[8]: aq = freud.AABBQuery(box, positions)
voxel_neighbors = -np.ones(len(cubic_grid), dtype=np.int)
for i, j, distance in aq.query(cubic_grid, {'num_neighbors': 1}):
    voxel_neighbors[i] = j
```

Next, we use these indices to color and draw the voxelization.

```
[9]: voxel_colors = np.array([colors[i] for i in voxel_neighbors])
plot_crystal(box, cubic_grid, colors=voxel_colors,
             radii=radii, backend=backend)
```



7.5.4 Benchmarks

Performance is a central consideration for **freud**. Below are some benchmarks comparing **freud** to other tools offering similar analysis methods.

Benchmarking Neighbor Finding against scipy

The neighbor finding algorithms in **freud** are highly efficient and rely on parallelized C++ code. Below, we show a benchmark of **freud**'s AABQuery algorithm against the `scipy.spatial.cKDTree`. This benchmark was run on an Intel(R) Core(TM) i3-8100B CPU @ 3.60GHz.

```
[1]: import freud
import scipy.spatial
import numpy as np
import matplotlib.pyplot as plt
import timeit
from tqdm import tqdm

[2]: def make_scaled_system(N, Nneigh=12):
    L = (4 / 3 * np.pi * N / Nneigh)**(1/3)
    return freud.data.make_random_system(L, N)
```

(continues on next page)

(continued from previous page)

```
box, points = make_scaled_system(1000)
```

Timing Functions

```
[3]: def time_statement(stmt, repeat=5, number=100, **kwargs):
    timer = timeit.Timer(stmt=stmt, globals=kwargs)
    times = timer.repeat(repeat, number)
    return np.mean(times), np.std(times)

[4]: def time_scipy_cKDTree(box, points):
    shifted_points = points + np.asarray(box.L)/2
    # SciPy only supports cubic boxes
    assert box.Lx == box.Ly == box.Lz
    assert box.xy == box.xz == box.yz == 0
    return time_statement("kdtree = scipy.spatial.cKDTree(points, boxsize=L);"
                          "kdtree.query_ball_tree(kdtree, r=rcut)",
                          scipy=scipy, points=shifted_points, L=box.Lx, rcut=1.0)

[5]: def time_freud_AABBQuery(box, points):
    return time_statement("aq = freud.locality.AABBQuery(box, points);"
                          "aq.query(points, {'r_max': r_max, 'exclude_ii': False})."
                          "↪toNeighborList()",
                          freud=freud, box=box, points=points, r_max=1.0)

[6]: # Test timing functions
kd_t = time_scipy_cKDTree(box, points)
print(kd_t)
abq_t = time_freud_AABBQuery(box, points)
print(abq_t)

(0.4641454226, 0.003790939209936744)
(0.26300359499999998, 0.006359869892978881)
```

Perform Measurements

```
[7]: def measure_runtime_scaling(Ns, r_max=1.0):
    result_times = []
    for N in tqdm(Ns):
        box, points = make_scaled_system(N)
        result_times.append((
            time_scipy_cKDTree(box, points),
            time_freud_AABBQuery(box, points)))
    return np.asarray(result_times)

[8]: def plot_result_times(result_times, Ns):
    plt.figure(figsize=(6, 4), dpi=200)
    plt.errorbar(Ns, result_times[:, 0, 0], result_times[:, 0, 1], label="scipy v{ }_↪cKDTree".format(scipy.__version__))
    plt.errorbar(Ns, result_times[:, 1, 0], result_times[:, 1, 1], label="freud v{ }_↪AABBQuery".format(freud.__version__))
```

(continues on next page)


(continued from previous page)

```
plt.title(r'Neighbor finding for 12 average neighbors')
plt.xlabel(r'Number of points $N$')
plt.ylabel(r'Runtime for 100 iterations (s)')
plt.legend()
plt.show()
```

```
[9]: # Use geometrically-spaced values of N, rounded to one significant figure
Ns = list(sorted(set(map(
    lambda x: int(round(x, -int(np.floor(np.log10(np.abs(x))))),
    np.exp(np.linspace(np.log(50), np.log(5000), 10))))))
```

```
[10]: result_times = measure_runtime_scaling_N(Ns)
plot_result_times(result_times, Ns)
```

```
100%|| 10/10 [00:42<00:00, 4.21s/it]
```



Benchmarking RDF against MDAnalysis

The algorithms in freud are highly efficient and rely on parallelized C++ code. Below, we show a benchmark of `freud.density.RDF` against `MDAnalysis.analysis.rdf`. This benchmark was run on an Intel(R) Core(TM) i3-8100B CPU @ 3.60GHz.


```
[1]: import freud
import gsd
import MDAnalysis
import MDAnalysis.analysis.rdf
import multiprocessing as mp
import numpy as np
import matplotlib.pyplot as plt
import timeit
from tqdm import tqdm
```

```
[2]: trajectory_filename = 'data/rdf_benchmark.gsd'
r_max = 5
r_min = 0.1
nbins = 75
```

```
[3]: trajectory = MDAnalysis.coordinates.GSD.GSDReader(trajectory_filename)
topology = MDAnalysis.core.topology.Topology(n_atoms=trajectory[0].n_atoms)
u = MDAnalysis.as_Universe(topology, trajectory_filename)


rdf = MDAnalysis.analysis.rdf.InterRDF(g1=u.atoms, g2=u.atoms,
                                       nbins=nbins,
                                       range=(r_min, r_max)).run()
```

```
[4]: plt.plot(rdf.bins, rdf.rdf)
plt.show()
```



```
[5]: freud_rdf = freud.density.RDF(bins=nbins, r_max=r_max, r_min=r_min)
for frame in trajectory:
    freud_rdf.compute(system=frame, reset=False)
freud_rdf
```

[5]:



Timing Functions

```
[6]: def time_statement(stmt, repeat=3, number=1, **kwargs):
    timer = timeit.Timer(stmt=stmt, globals=kwargs)
    times = timer.repeat(repeat, number)
    return np.mean(times), np.std(times)

[7]: def time_mdanalysis_rdf(trajecory_filename, r_max, r_min, nbins):
    trajectory = MDAnalysis.coordinates.GSD.GSDReader(trajecory_filename)
    frame = trajectory[0]
    topology = MDAnalysis.core.topology.Topology(n_atoms=frame.n_atoms)
    u = MDAnalysis.as_Universe(topology, trajecory_filename)
    code = """rdf = MDAnalysis.analysis.rdf.InterRDF(g1=u.atoms, g2=u.atoms,
↳nbins=nbins, range=(r_min, r_max)).run()"""
    return time_statement(code, MDAnalysis=MDAnalysis, u=u, r_max=r_max, r_min=r_min,
↳nbins=nbins)

[8]: def time_freud_rdf(trajecory_filename, r_max, r_min, nbins):
    trajectory = MDAnalysis.coordinates.GSD.GSDReader(trajecory_filename)
    code = """
rdf = freud.density.RDF(bins=nbins, r_max=r_max, r_min=r_min)
for frame in trajectory:
    rdf.compute(system=frame, reset=False)"""
    return time_statement(code, freud=freud, trajectory=trajectory, r_max=r_max, r_
↳min=r_min, nbins=nbins)

[9]: # Test timing functions
params = dict(
    trajecory_filename=trajecory_filename,
    r_max=r_max,
    r_min=r_min,
    nbins=nbins)
```

(continues on next page)

(continued from previous page)

```
def system_size(trajectory_filename, **kwargs):
    with gsd.hoomd.open(params['trajectory_filename'], 'rb') as trajectory:
        return {'frames': len(trajectory),
                'particles': len(trajectory[0].particles.position)}

print(system_size(**params))
mdanalysis_rdf_runtime = time_mdanalysis_rdf(**params)
print('MDAnalysis:', mdanalysis_rdf_runtime)
freud_rdf_runtime = time_freud_rdf(**params)
print('freud:', freud_rdf_runtime)

{'frames': 5, 'particles': 15625}
MDAnalysis: (18.00504128, 0.054983033593944214)
freud: (2.8556541516666747, 0.05481114115556424)
```

Perform Measurements


```
[10]: def measure_runtime_scaling_r_max(r_maxes, **params):
    result_times = []
    for r_max in tqdm(r_maxes):
        params.update(dict(r_max=r_max))
        freud.parallel.set_num_threads(1)
        freud_single = time_freud_rdf(**params)
        freud.parallel.set_num_threads(0)
        result_times.append((time_mdanalysis_rdf(**params), freud_single, time_freud_
→rdf(**params)))
    return np.asarray(result_times)
```

```
[11]: def plot_result_times(result_times, r_maxes, frames, particles):
    plt.figure(figsize=(6, 4), dpi=200)
    plt.errorbar(r_maxes, result_times[:, 0, 0], result_times[:, 0, 1],
        label="MDAnalysis v{} analysis.rdf.InterRDF".format(MDAnalysis.__
→version__))
    plt.errorbar(r_maxes, result_times[:, 1, 0], result_times[:, 1, 1],
        label="freud v{} density.RDF, 1 thread".format(freud.__version__))
    plt.errorbar(r_maxes, result_times[:, 2, 0], result_times[:, 2, 1],
        label="freud v{} density.RDF, {} threads".format(freud.__version__,
→mp.cpu_count()))
    plt.title(r'RDF for {} frames, {} particles'.format(frames, particles))
    plt.xlabel(r'RDF $r_{{max}}$')
    plt.ylabel(r'Average Runtime (s)')
    plt.yscale('log')
    plt.legend()
    plt.show()
```

```
[12]: r_maxes = [0.2, 0.3, 0.5, 1, 2, 3]
```

```
[13]: result_times = measure_runtime_scaling_r_max(r_maxes, **params)
plot_result_times(result_times, r_maxes, **system_size(params['trajectory_filename']))

100%|| 6/6 [00:31<00:00, 5.28s/it]
```



```
[14]: print('Speedup, parallel freud / serial freud: {:.3f}x'.format(np.average(result_
      ↳ times[:, 1, 0] / result_times[:, 2, 0])))
      print('Speedup, parallel freud / MDAnalysis: {:.3f}x'.format(np.average(result_
      ↳ times[:, 0, 0] / result_times[:, 2, 0])))
      print('Speedup, serial freud / MDAnalysis: {:.3f}x'.format(np.average(result_times[:, 0,
      ↳ 0, 0] / result_times[:, 1, 0])))

Speedup, parallel freud / serial freud: 2.900x
Speedup, parallel freud / MDAnalysis: 7.182x
Speedup, serial freud / MDAnalysis: 2.619x
```

7.6 Query API

This page provides a thorough review of how neighbor finding is structured in **freud**. It assumes knowledge at the level of the [Finding Neighbors](#) level of the tutorial; if you're not familiar with using the `query` method with query arguments to find neighbors of points, please familiarize yourself with that section of the tutorial.

The central interface for neighbor finding is the `freud.locality.NeighborQuery` family of classes, which provide methods for dynamically finding neighbors given a `freud.box.Box`. The `freud.locality.NeighborQuery` class defines an abstract interface for neighbor finding that is implemented by its subclasses, namely the `freud.locality.LinkCell` and `freud.locality.AABBQuery` classes. These classes represent specific data structures used to accelerate neighbor finding. These two different methods have different performance characteristics, but in most cases `freud.locality.AABBQuery` performs at least as well as, if not

better than, `freud.locality.LinkCell` and is entirely parameter free, so it is the default method of choice used internally in **freud**'s `PairCompute` classes.

In general, these data structures operate by constructing them using one set of points, after which they can be queried to efficiently find the neighbors of arbitrary other points using `freud.locality.NeighborQuery.query()`.

7.6.1 Query Arguments

The table below describes the set of valid query arguments.

Query Argument	Definition	Data type	Legal Values	Valid for
mode	The type of query to perform (distance cutoff or number of neighbors)	str	'none', 'ball', 'nearest'	<code>freud.locality.AABBQuery</code> , <code>freud.locality.LinkCell</code>
r_max	Maximum distance to find neighbors	float	$r_{\text{max}} > 0$	<code>freud.locality.AABBQuery</code> , <code>freud.locality.LinkCell</code>
r_min	Minimum distance to find neighbors	float	$0 \leq r_{\text{min}} < r_{\text{max}}$	<code>freud.locality.AABBQuery</code> , <code>freud.locality.LinkCell</code>
num_neighbors	Number of neighbors	int	$\text{num_neighbors} > 0$	<code>freud.locality.AABBQuery</code> , <code>freud.locality.LinkCell</code>
exclude_ii	Whether or not to include neighbors with the same index in the array	bool	True/False	<code>freud.locality.AABBQuery</code> , <code>freud.locality.LinkCell</code>
r_guess	Initial search distance for sequence of ball queries	float	$r_{\text{guess}} > 0$	<code>freud.locality.AABBQuery</code>
scale	Scale factor for <code>r_guess</code> when not enough neighbors are found	float	$\text{scale} > 1$	<code>freud.locality.AABBQuery</code>

7.6.2 Query Modes

Ball Query (Distance Cutoff)

A ball query finds all particles within a specified radial distance of the provided query points. This query is executed when `mode='ball'`. As described in the table above, this mode can be coupled with filters for a minimum distance (`r_min`) and/or self-exclusion (`exclude_ii`).

Nearest Neighbors Query (Fixed Number of Neighbors)

A nearest neighbor query (sometimes called k -nearest neighbors) finds a desired number of neighbor points for each query point, ordered by distance to the query point. This query is executed when `mode='nearest'`. As described in the table above, this mode can be coupled with filters for a maximum distance (`r_max`), minimum distance (`r_min`), and/or self-exclusion (`exclude_ii`).

Mode Deduction

The `mode` query argument specifies the type of query that is being performed, and it therefore governs how other arguments are interpreted. In most cases, however, the query mode can be deduced from the set of query arguments. Specifically, any query with the `num_neighbors` key set is assumed to be a query with `mode='nearest'`. One of `num_neighbors` or `r_max` must always be specified to form a valid set of query arguments. Specifying the `mode` key explicitly will ensure that querying behavior is consistent if additional query modes are added to **freud**.

7.6.3 Query Results

Although they don't typically need to be operated on directly, it can be useful to know a little about the objects returned by queries. The `freud.locality.NeighborQueryResult` stores the `query_points` passed to a query and returns neighbors for them one at a time (like any Python iterator). The primary goal of the result class is to support easy iteration and conversion to more persistent formats. Since it is an iterator, you can use any typical Python approach to consuming it, including passing it to `list` to build a list of the neighbors. For a more **freud**-friendly approach, you can use the `toNeighborList` method to convert the object into a **freud** `freud.locality.NeighborList`. Under the hood, the underlying C++ classes loop through candidate points and identifying neighbors for each `query_point`; this is the same process that occurs when `Compute` classes employ `NeighborQuery` objects for finding neighbors on-the-fly, but in that case it all happens on the C++ side.

7.6.4 Custom NeighborLists

Thus far, we've mostly discussed `NeighborLists` `<freud.locality.NeighborList` as a way to persist neighbor information beyond a single query. In *Using freud Efficiently*, more guidance is provided on how you can use these objects to speed up certain uses of **freud**. However, these objects are also extremely useful because they provide a *completely customizable* way to specify neighbors to **freud**. Of particular note here is the `freud.locality.NeighborList.from_arrays()` factory function that allows you to make `freud.locality.NeighborList` objects by directly specifying the `(i, j)` pairs that should be in the list. This kind of explicit construction of the list enables custom analyses that would otherwise be impossible. For example, consider a molecular dynamics simulation in which particles only interact via extremely short-ranged patches on their surface, and that particles should only be considered bonded if their patches are actually interacting, irrespective of how close together the particles themselves are. This type of neighbor interaction cannot be captured by any normal querying mode, but could be constructed by the user and then fed to **freud** for downstream analysis.

7.6.5 Nearest Neighbor Asymmetry

There is one important but easily overlooked detail associated with using query arguments with `mode='nearest'`. Consider a simple example of three points on the x-axis located at -1, 0, and 2 (and assume the box is of dimensions (100, 100, 100), i.e. sufficiently large that periodicity plays no role):

```
box = [100, 100, 100]
points = [[-1, 0, 0], [0, 0, 0], [2, 0, 0]]
query_args = dict(mode='nearest', num_neighbors=1, exclude_ii=True)
list(freud.locality.AABBQuery(box, points).query(points, query_args))
# Output: [(0, 1, 1), (1, 0, 1), (2, 1, 2)]
```

Evidently, the calculation is not symmetric. This feature of nearest neighbor queries can have unexpected side effects if a `PairCompute` is performed using distinct `points` and `query_points` and the two are interchanged. In such cases, users should always keep in mind that **freud** promises that every `query_point` will end up with `num_neighbors` points (assuming no hard cutoff `r_max` is imposed and enough points are present in the system). However, it is possible (and indeed likely) that any given point will have more or fewer than that many neighbors.

This distinction can be particularly tricky for calculations that depend on vector directionality: **freud** imposes the convention that bond vectors always point from `query_point` to `point`, so users of calculations like PMFTs where directionality is important should keep this in mind.

7.7 Using freud Efficiently

The **freud** library is designed to be both fast and easy-to-use. In many cases, the library's performance is good enough that users don't need to worry about their usage patterns. However, in highly performance-critical applications (such as real-time visualization or on-the-fly calculations mid-simulation), users can benefit from knowing the best ways to make use of **freud**. This page provides some guidance on this topic.

7.7.1 Reusing Locality Information

Perhaps the most powerful method users have at their disposal for speeding up calculations is proper reuse of the data structures in `freud.locality`. As one example, consider using **freud** to calculate multiple neighbor-based quantities for the same set of data points. It is important to recognize that internally, each time such a calculation is performed using a `(box, points)` tuple, the compute class is internally rebuilding a neighbor-finding accelerator such a `freud.locality.AABBQuery` object and then using it to find neighbors:

```
# Behind the scenes, freud is essentially running
# freud.locality.AABBQuery(box, points).query(points, dict(r_max=5, exclude_ii=True))
# and feeding the result to the RDF calculation.
rdf = freud.density.RDF(bins=50, r_max=5)
rdf.compute(system=(box, points))
```

If users anticipate performing many such calculations on the same system of points, they can amortize the cost of rebuilding the `AABBQuery` object by constructing it once and then passing it into multiple computations:

```
# Now, let's instead reuse the object for a pair of calculations:
nq = freud.locality.AABBQuery(box=box, points=points)
rdf = freud.density.RDF(bins=50, r_max=5)
rdf.compute(system=nq)

r_max = 4
orientations = np.array([[1, 0, 0, 0]] * num_points)
pmft = freud.pmft.PMFTXYZ(r_max, r_max, r_max, bins=100)
pmft.compute(system=nq, orientations=orientations)
```

This reuse can significantly improve performance in e.g. visualization contexts where users may wish to calculate a *bond order diagram* and an *RDF* at each frame, perhaps for integration with a visualization toolkit like **OVITO**.

A slightly different use-case would be the calculation of multiple quantities based on *exactly the same set of neighbors*. If the user in fact expects to perform computations with the exact same pairs of neighbors (for example, to compute `freud.order.Steinhardt` for multiple l values), then the user can further speed up the calculation by precomputing the entire `freud.NeighborList` and storing it for future use.

```
r_max = 3
nq = freud.locality.AABBQuery(box=box, points=points)
nlist = nq.query(points, dict(r_max=r_max))
q6_arrays = []
for l in range(3, 6):
    ql = freud.order.Steinhardt(l=l)
    q6_arrays.append(ql.compute((box, points), neighbors=nlist).particle_order)
```

Notably, if the user calls a compute method with `compute(system=(box, points))`, unlike in the examples above **freud** will not construct a `freud.locality.NeighborQuery` internally because the full set of neighbors is completely specified by the `NeighborList`. In all these cases, **freud** does the minimal work possible to find neighbors, so judicious use of these data structures can substantially accelerate your code.

7.7.2 Proper Data Inputs

Minor speedups may also be gained from passing properly structured data to **freud**. The package was originally designed for analyzing particle simulation trajectories, which are typically stored in single-precision binary formats. As a result, the **freud** library also operates in single precision and therefore converts all inputs to single-precision. However, NumPy will typically work in double precision by default, so depending on how data is streamed to **freud**, the package may be performing numerous data copies in order to ensure that all its data is in single-precision. To avoid this problem, make sure to specify the appropriate data types (`numpy.float32`) when constructing your NumPy arrays.

7.8 Reading Simulation Data for freud

The **freud** package is designed for maximum flexibility by making minimal assumptions about its data. However, users accustomed to the more restrictive patterns of most other tools may find this flexibility confusing. In particular, knowing how to provide data from specific simulation sources can be a significant source of confusion. This page is intended to describe how various types of data may be converted into a form suitable for **freud**.

To simplify the examples below, we will assume in all cases that the user wishes to compute a *radial distribution function* over all frames in the trajectory and that the following code has already been run:

```
import freud
rdf = freud.density.RDF(bins=50, r_max=5)
```

7.8.1 Native Integrations

The **freud** library offers interoperability with several popular tools for particle simulations, analysis, and visualization. Below is a list of file formats and tools that are directly supported as “system-like” objects (see `freud.locality.NeighborQuery.from_system`). Such system-like objects are data containers that store information about a periodic box and particle positions. Other attributes, such as particle orientations, are not included automatically in the system representation and must be loaded as separate NumPy arrays.

GSD Trajectories

Using the GSD Python API, GSD files can be easily integrated with **freud** as shown in the *Quickstart Guide*. This format is natively supported by *HOOMD-blue*. Note: the GSD format can also be read by *MDAnalysis* and *garnett*. Here, we provide an example that reads data from a GSD file.

```
import gsd.hoomd
traj = gsd.hoomd.open('trajectory.gsd', 'rb')

for frame in traj:
    rdf.compute(system=frame, reset=False)
```

MDAnalysis Readers

The `MDAnalysis` package can read many popular trajectory formats, including common output formats from CHARMM, NAMD, LAMMPS, Gromacs, Tinker, AMBER, GAMESS, HOOMD-blue, and more.

DCD files are among the most familiar simulation outputs due to their longevity. Here, we provide an example that reads data from a DCD file.

```
import MDAnalysis
reader = MDAnalysis.coordinates.DCD.DCDReader('trajectory.dcd')

for frame in reader:
    rdf.compute(system=frame, reset=False)
```

garnett Trajectories

The `garnett` package can read several trajectory formats that have historically been supported by the HOOMD-blue simulation engine, as well as other common types such as DCD and CIF. The `garnett` package will auto-detect supported file formats by the file extension. Here, we provide an example that reads data from a POS file.

```
import garnett

with garnett.read('trajectory.pos') as traj:
    for frame in traj:
        rdf.compute(system=frame, reset=False)
```

OVITO Modifiers

The `OVITO Open Visualization Tool` supports user-written Python modifiers. The `freud` package can be installed alongside OVITO to enable user-written `Python script modifiers` that leverage analyses from `freud`. Below is an example modifier that creates a user particle property in the OVITO pipeline for Steinhardt bond order parameters.

```
import freud

def modify(frame, data):
    ql = freud.order.Steinhardt(l=6)
    ql.compute(system=data, neighbors={'num_neighbors': 6})
    data.create_user_particle_property(
        name='ql', data_type=float, data=ql.ql)
    print('Created ql property for {} particles.'.format(data.particles.count))
```

HOOMD-blue Snapshots

HOOMD-blue supports analyzers, callback functions that can perform analysis. Below is an example demonstrating how to use an analyzer to log the Steinhardt bond order parameter q_6 during the simulation run.

```
import hoomd
from hoomd import md
import freud

hoomd.context.initialize()

# Create a 10x10x10 simple cubic lattice of particles with type name A
```

(continues on next page)

(continued from previous page)

```

system = hoomd.init.create_lattice(
    unitcell=hoomd.lattice.sc(a=2.0, type_name='A'), n=10)

# Specify Lennard-Jones interactions between particle pairs
nl = md.nlist.cell()
lj = md.pair.lj(r_cut=3.0, nlist=nl)
lj.pair_coeff.set('A', 'A', epsilon=1.0, sigma=1.0)

# Integrate at constant temperature
md.integrate.mode_standard(dt=0.005)
hoomd.md.integrate.langevin(group=hoomd.group.all(), kT=1.2, seed=4)

# Create a Steinhardt object to analyze snapshots
ql = freud.order.Steinhardt(l=6)

def compute_q6(timestep):
    snap = system.take_snapshot()
    ql.compute(system=snap, neighbors={'num_neighbors': 6})
    return ql.order

# Register a logger that computes q6 and saves to a file
ql_logger = hoomd.analyze.log(filename='ql.dat', quantities=['q6'], period=100)
ql_logger.register_callback('q6', compute_q6)

# Run for 10,000 time steps
hoomd.run(10e3)

```

7.8.2 Reading Text Files

Typically, it is best to use one of the natively supported data readers described above; however it is sometimes necessary to parse trajectory information directly from a text file. One example of a plain text format is the XYZ file format, which can be generated and used by many tools for particle simulation and analysis, including LAMMPS and VMD. Note that various readers do exist for XYZ files, including MDAnalysis, but in this example we read the file manually to demonstrate how to read these inputs as plain text. Though they are easy to parse, XYZ files usually contain no information about the system box, so this must already be known by the user. Assuming knowledge of the box used in the simulation, a LAMMPS XYZ file could be used as follows:

```

N = int(np.genfromtxt('trajectory.xyz', max_rows=1))
traj = np.genfromtxt(
    'trajectory.xyz', skip_header=2,
    invalid_raise=False)[: , 1:4].reshape(-1, N, 3)
box = freud.box.Box.cube(L=20)

for frame_positions in traj:
    rdf.compute(system=(box, frame_positions), reset=False)

```

The first line is the number of particles, so we read this line and use it to determine how to reshape the contents of the rest of the file into a NumPy array.

7.8.3 Other External Readers

For many trajectory formats, high-quality readers already exist. However sometimes these readers' data structures must be converted into a format understood by **freud**. Below, we show an example that converts the MDAnalysis box dimensions from a matrix into a `freud.box.Box`. Note that *MDAnalysis inputs* are natively supported by **freud** without this extra step. For other formats not supported by a reader listed above, a similar process can be followed.

```
import MDAnalysis
reader = MDAnalysis.coordinates.DCD.DCDReader('trajectory.dcd')

for frame in reader:
    box = freud.box.Box.from_matrix(frame.triclinic_dimensions)
    rdf.compute(system=(box, frame.positions), reset=False)
```

7.9 Box Module

Overview

`freud.box.Box`The freud Box class for simulation boxes.

Details

The `Box` class defines the geometry of a simulation box. The class natively supports periodicity by providing the fundamental features for wrapping vectors outside the box back into it.

class `freud.box.Box`

Bases: `object`

The freud Box class for simulation boxes.

This class defines an arbitrary triclinic geometry within which all points are confined. For more information, see the [documentation](#) on boxes and periodic boundary conditions.

Also available as `freud.Box`.

Parameters

- **Lx** (*float, optional*) – The x-dimension length.
- **Ly** (*float, optional*) – The y-dimension length.
- **Lz** (*float, optional*) – The z-dimension length (Default value = 0).
- **xy** (*float, optional*) – The xy tilt factor (Default value = 0).
- **xz** (*float, optional*) – The xz tilt factor (Default value = 0).
- **yz** (*float, optional*) – The yz tilt factor (Default value = 0).
- **is2D** (*bool, optional*) – Whether the box is 2-dimensional. Uses `Lz == 0` if None. (Default value = None)

L

Get or set the box lengths along x, y, and z.

Type (3,) `numpy.ndarray`

L_inv

The inverse box lengths.

Type (3,) `numpy.ndarray`

Lx

Get or set the x-dimension length.

Type `float`

Ly

Get or set the y-dimension length.

Type `float`

Lz

Get or set the z-dimension length.

Type `float`

center

Subtract center of mass from an array of vectors, using periodic boundaries.

This calculation accounts for periodic images. [This Wikipedia page](#) describes the mathematics of this method.

Example:

```
>>> import freud
>>> box = freud.Box.cube(10)
>>> points = [[-1, -1, 0], [-1, 1, 0], [2, 0, 0]]
>>> box.center(points)
array([[ -0.8154063, -1.          ,  0.          ],
       [ -0.8154063,  1.          ,  0.          ],
       [  2.1845937,  0.          ,  0.          ]], dtype=float32)
```

Parameters

- **vecs** (($N, 3$) `numpy.ndarray`) – Vectors to center.
- **masses** (($N, 3$) `numpy.ndarray`) – Masses corresponding to each vector, defaulting to 1 if not provided or None (Default value = None).

Returns Vectors with center of mass subtracted.

Return type ($N, 3$) `numpy.ndarray`

center_of_mass

Compute center of mass of an array of vectors, using periodic boundaries.

This calculation accounts for periodic images. [This Wikipedia page](#) describes the mathematics of this method.

Example:

```
>>> import freud
>>> import numpy as np
>>> box = freud.Box.cube(10)
>>> points = [[-1, -1, 0], [-1, 1, 0], [2, 0, 0]]
>>> np.mean(points, axis=0) # Does not account for periodic images
array([0., 0., 0.])
>>> box.center_of_mass(points) # Accounts for periodic images
array([-0.18459368,  0.          ,  0.          ])
```

Parameters

- **vecs** (($N, 3$) `numpy.ndarray`) – Vectors used to find center of mass.
- **masses** (($N, 3$) `numpy.ndarray`) – Masses corresponding to each vector, defaulting to 1 if not provided or None (Default value = None).

Returns Center of mass.

Return type (3) `numpy.ndarray`

classmethod **cube** (*type cls, L=None*)

Construct a cubic box with equal lengths.

Parameters **L** (*float*) – The edge length

dimensions

Get or set the number of dimensions (2 or 3).

Type `int`

classmethod **from_box** (*type cls, box, dimensions=None*)

Initialize a Box instance from a box-like object.

Parameters

- **box** – A box-like object
- **dimensions** (*int*) – Dimensionality of the box (Default value = None)

Note: Objects that can be converted to freud boxes include lists like [`Lx`, `Ly`, `Lz`, `xy`, `xz`, `yz`], dictionaries with keys '`Lx`', '`Ly`', '`Lz`', '`xy`', '`xz`', '`yz`', '`dimensions`', objects with attributes `Lx`, `Ly`, `Lz`, `xy`, `xz`, `yz`, `dimensions`, 3x3 matrices (see `from_matrix()`), or existing `freud.box.Box` objects.

If any of `Lz`, `xy`, `xz`, `yz` are not provided, they will be set to 0.

If all values are provided, a triclinic box will be constructed. If only `Lx`, `Ly`, `Lz` are provided, an orthorhombic box will be constructed. If only `Lx`, `Ly` are provided, a rectangular (2D) box will be constructed.

If the optional `dimensions` argument is given, this will be used as the box dimensionality. Otherwise, the box dimensionality will be detected from the `dimensions` of the provided box. If no dimensions can be detected, the box will be 2D if `Lz == 0`, and 3D otherwise.

Returns The resulting box object.

Return type `freud.box.Box`

classmethod **from_matrix** (*type cls, box_matrix, dimensions=None*)

Initialize a Box instance from a box matrix.

For more information and the source for this code, see: <https://hoomd-blue.readthedocs.io/en/stable/box.html>

Parameters

- **box_matrix** (*array-like*) – A 3x3 matrix or list of lists
- **dimensions** (*int*) – Number of dimensions (Default value = None)

get_box_vector

Get the box vector with index i .

Parameters **i** (*unsigned int*) – Index ($0 \leq i < d$) of the box vector, where d is the box dimension (2 or 3).

Returns Box vector with index i .

Return type (3,) `numpy.ndarray`

get_images

Returns the images corresponding to unwrapped vectors.

Parameters **vecs** ((3,) or ($N, 3$) `numpy.ndarray`) – Coordinates of unwrapped vector(s).

Returns Image index vector(s).

Return type (3,) or ($N, 3$) `numpy.ndarray`

is2D

Whether the box is 2D.

Type `bool`

make_absolute

Convert fractional coordinates into absolute coordinates.

Parameters **fractional_coordinates** ((3,) or ($N, 3$) `numpy.ndarray`) – Fractional coordinate vector(s), between 0 and 1 within parallelepipedal box.

Returns Absolute coordinate vector(s).

Return type (3,) or ($N, 3$) `numpy.ndarray`

make_fractional

Convert absolute coordinates into fractional coordinates.

Parameters **absolute_coordinates** ((3,) or ($N, 3$) `numpy.ndarray`) – Absolute coordinate vector(s).

Returns Fractional coordinate vector(s).

Return type (3,) or ($N, 3$) `numpy.ndarray`

periodic

Get or set the periodicity of the box in each dimension.

Type (3,) `numpy.ndarray`

periodic_x

Get or set the periodicity of the box in x.

Type `bool`

periodic_y

Get or set the periodicity of the box in y.

Type `bool`

periodic_z

Get or set the periodicity of the box in z.

Type `bool`

plot

Plot a `Box` object.

Parameters

- **title** (*str*) – Title of the graph. (Default value = None).
- **ax** (`matplotlib.axes.Axes`) – Axes object to plot. If None, make a new axes and figure object. If plotting a 3D box, the axes must be 3D. (Default value = None).
- **image** (*list*) – The periodic image location at which to draw the box (Default value = [0, 0, 0]).
- ***args** – Passed on to `mpl_toolkits.mplot3d.Axes3D.plot()` or `matplotlib.axes.Axes.plot()`.
- ****kwargs** – Passed on to `mpl_toolkits.mplot3d.Axes3D.plot()` or `matplotlib.axes.Axes.plot()`.

classmethod square (*type cls, L=None*)

Construct a 2-dimensional (square) box with equal lengths.

Parameters **L** (*float*) – The edge length**to_dict**

Return box as dictionary.

Example::

```
>>> box = freud.box.Box.cube(L=10)
>>> box.to_dict()
{'Lx': 10.0, 'Ly': 10.0, 'Lz': 10.0,
 'xy': 0.0, 'xz': 0.0, 'yz': 0.0, 'dimensions': 3}
```

Returns Box parameters**Return type** `dict`**to_matrix**

Returns the box matrix (3x3).

Example::

```
>>> box = freud.box.Box.cube(L=10)
>>> box.to_matrix()
array([[10.,  0.,  0.],
       [ 0., 10.,  0.],
       [ 0.,  0., 10.]])
```

Returns Box matrix**Return type** (3,3) `numpy.ndarray`**unwrap**

Unwrap an array of vectors inside the box back into real space, using an array of image indices that determine how many times to unwrap in each dimension.

Parameters

- **vecs** ((3,) or (N,3) `numpy.ndarray`) – Vector(s) to be unwrapped.
- **imgs** ((3,) or (N,3) `numpy.ndarray`) – Image indices for vector(s).

Returns Unwrapped vector(s).**Return type** (3,) or (N,3) `numpy.ndarray`

v1

The first box vector $(L_x, 0, 0)$.

Type $(3,)$ `np.ndarray`

v2

The second box vector $(x_y * L_y, L_y, 0)$.

Type $(3,)$ `np.ndarray`

v3

The third box vector $(x_z * L_z, y_z * L_z, L_z)$.

Type $(3,)$ `np.ndarray`

volume

The box volume (area in 2D).

Type `float`

wrap

Wrap an array of vectors into the box, using periodic boundaries.

Note: Since the origin of the box is in the center, wrapping is equivalent to applying the minimum image convention to the input vectors.

Parameters **vecs** $((3,)$ or $(N, 3)$ `numpy.ndarray`) – Unwrapped vector(s).

Returns Vector(s) wrapped into the box.

Return type $(3,)$ or $(N, 3)$ `numpy.ndarray`

xy

Get or set the xy tilt factor.

Type `float`

xz

Get or set the xz tilt factor.

Type `float`

yz

Get or set the yz tilt factor.

Type `float`

7.10 Cluster Module

Overview

<code>freud.cluster.Cluster</code>	Finds clusters using a network of neighbors.
<code>freud.cluster.ClusterProperties</code>	Routines for computing properties of point clusters.

Details

The `freud.cluster` module aids in finding and computing the properties of clusters of points in a system.

class `freud.cluster.Cluster`

Bases: `freud.locality._PairCompute`

Finds clusters using a network of neighbors.

Given a set of points and their neighbors, `freud.cluster.Cluster` will determine all of the connected components of the network formed by those neighbor bonds. That is, two points are in the same cluster if and only if a path exists between them on the network of bonds. The class attribute `cluster_idx` holds an array of cluster indices for each point. By the definition of a cluster, points that are not bonded to any other point end up in their own 1-point cluster.

Identifying micelles is one use-case for finding clusters. This operation is somewhat different, though. In a cluster of points, each and every point belongs to one and only one cluster. However, because a string of points belongs to a polymer, that single polymer may be present in more than one cluster. To handle this situation, an optional layer is presented on top of the `cluster_idx` array. Given a key value per point (e.g. the polymer id), the compute function will process clusters with the key values in mind and provide a list of keys that are present in each cluster in the attribute `cluster_keys`, as a list of lists. If keys are not provided, every point is assigned a key corresponding to its index, and `cluster_keys` contains the point ids present in each cluster.

property `cluster_idx`

The cluster index for each point.

Type (N_{points}) `numpy.ndarray`

property `cluster_keys`

A list of lists of the keys contained in each cluster.

Type `list(list)`

compute

Compute the clusters for the given set of points.

Parameters

- **system** – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.
- **keys** ((N_{points}) `numpy.ndarray`) – Membership keys, one for each point.
- **neighbors** (`freud.locality.NeighborList` or dict, optional) – Either a `NeighborList` of neighbor pairs to use in the calculation, or a dictionary of `query arguments` (Default value: None).

default_query_args

No default query arguments.

property `num_clusters`

The number of clusters.

Type `int`

plot

Plot cluster distribution.

Parameters **ax** (`matplotlib.axes.Axes`, optional) – Axis to plot on. If None, make a new figure and axis. (Default value = None)

Returns Axis with the plot.

Return type (`matplotlib.axes.Axes`)

class `freud.cluster.ClusterProperties`Bases: `freud.util._Compute`

Routines for computing properties of point clusters.

Given a set of points and cluster ids (from `Cluster` or another source), this class determines the following properties for each cluster:

- Center of mass
- Gyration tensor
- Size (number of points)

The center of mass for each cluster (properly handling periodic boundary conditions) can be accessed with `centers` attribute. The 3×3 symmetric gyration tensors G can be accessed with `gyrations` attribute.

property `centers`

The centers of mass of the clusters.

Type ($N_{clusters}$, 3) `numpy.ndarray`**compute**

Compute properties of the point clusters. Loops over all points in the given array and determines the center of mass of the cluster as well as the gyration tensor. These can be accessed after the call to `compute()` with the `centers` and `gyrations` attributes.

Parameters

- **system** – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.
- **cluster_idx** ($(N_{points},)$ `np.ndarray`) – Cluster indexes for each point.

property `gyrations`

The gyration tensors of the clusters.

Type ($N_{clusters}$, 3, 3) `numpy.ndarray`**property** `radii_of_gyration`

The radius of gyration of each cluster.

Type ($N_{clusters},$) `numpy.ndarray`**property** `sizes`

The cluster sizes.

Type ($N_{clusters}$) `numpy.ndarray`

7.11 Data Module

Overview

<code>freud.data.UnitCell</code>	Class to represent the unit cell of a crystal structure.
<code>freud.data.make_random_system</code>	Helper function to make random points with a cubic or square box.

Details

The `freud.data` module provides certain sample data sets and utility functions that are useful for testing and examples.

Stability

`freud.data` is **unstable**. When upgrading from version 2.x to 2.y ($y > x$), existing freud scripts may need to be updated. The API will be finalized in a future release.

class `freud.data.UnitCell` (*box*, *basis_positions*=[[0, 0, 0]])

Bases: `object`

Class to represent the unit cell of a crystal structure.

This class represents the unit cell of a crystal structure, which is defined by a lattice and a basis. It provides the basic attributes of the unit cell as well as enabling the generation of systems of points (optionally with some noise) from the unit cell.

Parameters

- **box** – A box-like object (see `from_box()`) containing the lattice vectors of the unit cell.
- **basis_positions** ($(N_{points}, 3)$ `numpy.ndarray`) – The basis of the unit cell in fractional coordinates (Default value = `[[0, 0, 0]]`).

property `a1`

The first lattice vector.

Type `(3,) np.ndarray`

property `a2`

The second lattice vector.

Type `(3,) np.ndarray`

property `a3`

The third lattice vector.

Type `(3,) np.ndarray`

property `basis_positions`

The basis positions.

Type `(N_{points}, 3) np.ndarray`

classmethod `bcc()`

Create a body-centered cubic crystal.

Returns A bcc unit cell.

Return type `UnitCell`

property `box`

The box instance containing the lattice vectors.

Type `freud.box.Box`

property `dimensions`

The dimensionality of the unit cell.

Type `int`

classmethod `fcc()`

Create a face-centered cubic crystal.

Returns An fcc unit cell.

Return type `UnitCell`

generate_system(`num_replicas=1`, `scale=1`, `sigma_noise=0`, `seed=None`)

Generate a system from the unit cell.

The box and the positions are expanded by `scale`, and then Gaussian noise with standard deviation `sigma_noise` is added to the positions. All points are wrapped back into the box before being returned.

Parameters

- **num_replicas** (`tuple` or `int`) – If provided as a single number, the number of replicas in all dimensions. If a `tuple`, the number of times replicated in each dimension. Must be of the form `(nx, ny, 1)` for 2D boxes (Default value = 1).
- **scale** (`float`) – Factor by which to scale the unit cell (Default value = 1).
- **sigma_noise** (`float`) – The standard deviation of the normal distribution used to add noise to the positions in the system (Default value = 0).
- **seed** (`int`) – If provided, used to seed the random noise generation. Not used unless `sigma_noise > 0` (Default value = None).

Returns A system-like object (see `from_system`).

Return type `tuple (freud.box.Box, np.ndarray)`

property `lattice_vectors`

The matrix of lattice vectors.

Type `(3,3) np.ndarray`

classmethod `sc()`

Create a simple cubic crystal.

Returns An sc unit cell.

Return type `UnitCell`

classmethod `square()`

Create a square crystal.

Returns A square unit cell.

Return type `UnitCell`

`freud.data.make_random_system(box_size, num_points, is2D=False, seed=None)`

Helper function to make random points with a cubic or square box.

Parameters

- **box_size** (`float`) – Size of box.
- **num_points** (`int`) – Number of points.
- **is2D** (`bool`) – If true, creates a 2D system. (Default value = False).
- **seed** (`int`) – Random seed to use. (Default value = None).

Returns Generated box and points.

Return type `tuple (freud.box.Box, (num_points, 3) numpy.ndarray)`

7.12 Density Module

Overview

<code>freud.density.CorrelationFunction</code>	Computes the complex pairwise correlation function.
<code>freud.density.GaussianDensity</code>	Computes the density of a system on a grid.
<code>freud.density.LocalDensity</code>	Computes the local density around a particle.
<code>freud.density.RDF</code>	Computes the RDF $g(r)$ for supplied data.

Details

The `freud.density` module contains various classes relating to the density of the system. These functions allow evaluation of particle distributions with respect to other particles.

class `freud.density.CorrelationFunction`

Bases: `freud.locality._SpatialHistogram1D`

Computes the complex pairwise correlation function.

The correlation function is given by $C(r) = \langle s_1^*(0) \cdot s_2(r) \rangle$ between two sets of points p_1 (`points`) and p_2 (`query_points`) with associated values s_1 (`values`) and s_2 (`query_values`). Computing the correlation function results in an array of the expected (average) product of all values at a given radial distance r .

The values of r where the correlation function is computed are controlled by the `r_max` and `dr` parameters to the constructor. `r_max` determines the maximum distance at which to compute the correlation function and `dr` is the step size for each bin.

Note: Self-correlation: It is often the case that we wish to compute the correlation function of a set of points with itself. If `query_points` is the same as `points`, not provided, or `None`, we omit accumulating the self-correlation value in the first bin.

Parameters

- **bins** (*unsigned int*) – The number of bins in the RDF.
- **r_max** (*float*) – Maximum pointwise distance to include in the calculation.

bin_centers

The centers of each bin in the histogram.

Type ($N_{bins},$) `numpy.ndarray`

property bin_counts

The bin counts in the histogram.

Type `numpy.ndarray`

bin_edges

The edges of each bin in the histogram. Is one element larger because each bin has a lower and upper bound.

Type ($N_{bins} + 1,$) `numpy.ndarray`

bounds

A tuple indicating upper and lower bounds of the histogram.

Type `tuple`

property `box`

The box object used in the last computation.

Type `freud.box.Box`

compute

Calculates the correlation function and adds to the current histogram.

Parameters

- **system** – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.
- **values** ((N_{points}) `numpy.ndarray`) – Values associated with the system points used to calculate the correlation function.
- **query_points** ($(N_{query_points}, 3)$ `numpy.ndarray`, optional) – Query points used to calculate the correlation function. Uses the system's points if None (Default value = None).
- **query_values** ((N_{query_points}) `numpy.ndarray`, optional) – Query values used to calculate the correlation function. Uses values if None. (Default value = None).
- **neighbors** (`freud.locality.NeighborList` or dict, optional) – Either a `NeighborList` of neighbor pairs to use in the calculation, or a dictionary of `query arguments` (Default value: None).
- **reset** (`bool`) – Whether to erase the previously computed values before adding the new computation; if False, will accumulate data (Default value: True).

property `correlation`

Expected (average) product of all values at a given radial distance.

Type (N_{bins}) `numpy.ndarray`

default_query_args

The default query arguments are `{ 'mode': 'ball', 'r_max': self.r_max }`.

nbins

The number of bins in the histogram

Type `int`

plot

Plot complex correlation function.

Parameters **ax** (`matplotlib.axes.Axes`, optional) – Axis to plot on. If None, make a new figure and axis. (Default value = None)

Returns Axis with the plot.

Return type (`matplotlib.axes.Axes`)

class `freud.density.GaussianDensity`

Bases: `freud.util._Compute`

Computes the density of a system on a grid.

Replaces particle positions with a Gaussian blur and calculates the contribution from each to the proscribed grid based upon the distance of the grid cell from the center of the Gaussian. The resulting data is a regular grid of particle densities that can be used in standard algorithms requiring evenly spaced point, such as Fast Fourier Transforms. The dimensions of the image (grid) are set in the constructor, and can either be set equally for all dimensions or for each dimension independently.

Parameters

- **width** (*int or list or tuple*) – The number of bins to make the image in each direction (identical in all dimensions if a single integer value is provided).
- **r_max** (*float*) – Distance over which to blur.
- **sigma** (*float*) – Sigma parameter for Gaussian.

property box

Box used in the calculation.

Type *freud.box.Box*

compute

Calculates the Gaussian blur for the specified points.

Parameters **system** – Any object that is a valid argument to *freud.locality.NeighborQuery.from_system*.

property density

The image grid with the Gaussian density.

Type (*w_x, w_y, w_z*) *numpy.ndarray*

plot

Plot Gaussian Density.

Parameters **ax** (*matplotlib.axes.Axes*, optional) – Axis to plot on. If None, make a new figure and axis. (Default value = None)

Returns Axis with the plot.

Return type (*matplotlib.axes.Axes*)

r_max

Distance over which to blur.

Type *float*

sigma

Sigma parameter for Gaussian.

Type *float*

width

The number of bins to make the image in each direction (identical in all dimensions if a single integer value is provided).

Type *int or list or tuple*


class *freud.density.LocalDensity*

Bases: *freud.locality._PairCompute*

Computes the local density around a particle.

The density of the local environment is computed and averaged for a given set of query points in a sea of data points. Providing the same points calculates them against themselves. Computing the local density results in an array listing the value of the local density around each query point. Also available is the number of neighbors for each query point, giving the user the ability to count the number of particles in that region. Note that the computed density is essentially a number density (allowing for fractional values as described below). If particles have a specific volume, a volume density can be computed by simply multiplying the number density by the volume of the particles.

In order to provide sufficiently smooth data, data points can be fractionally counted towards the density. Rather than perform compute-intensive area (volume) overlap calculations to determine the exact amount of overlap area (volume), the LocalDensity class performs a simple linear interpolation relative to the centers of the data points. Specifically, a point is counted as one neighbor if it is entirely contained within the r_{max} , half of a neighbor if the distance to its center is exactly r_{max} , and zero if its center is a distance greater than or equal to $r_{\text{max}} + \text{diameter}$ from the query point's center. Graphically, this looks like:



Parameters

- **r_max** (*float*) – Maximum distance over which to calculate the density.
- **diameter** (*float*) – Diameter of particle circumsphere.

property box

Box used in the calculation.

Type *freud.box.Box*

compute

Calculates the local density for the specified points.

Parameters

- **system** – Any object that is a valid argument to *freud.locality.NeighborQuery.from_system*.
- **query_points** (($N_{\text{query_points}}$, 3) *numpy.ndarray*, optional) – Query points used to calculate the correlation function. Uses the system's points if None (Default value = None).
- **neighbors** (*freud.locality.NeighborList* or dict, optional) – Either a *NeighborList* of neighbor pairs to use in the calculation, or a dictionary of *query arguments* (Default value: None).

default_query_args

The default query arguments are `{'mode': 'ball', 'r_max': self.r_max + 0.5*self.diameter}`.

property density

Density of points per query point.

Type (N_{points}) `numpy.ndarray`

diameter

Diameter of particle circumsphere.

Type `float`

property num_neighbors

Number of neighbor points for each query point.

Type (N_{points}) `numpy.ndarray`

r_max

Maximum distance over which to calculate the density.

Type `float`

class freud.density.RDF

Bases: `freud.locality._SpatialHistogram1D`

Computes the RDF $g(r)$ for supplied data.

Note that the RDF is defined strictly according to the pair correlation function, i.e.

$$g(r) = V \frac{N-1}{N} \langle \delta(r) \rangle$$

In the thermodynamic limit, the fraction tends to unity and the limiting behavior of $\lim_{r \rightarrow \infty} g(r) = 1$ is recovered. However, for very small systems the long range behavior of the radial distribution will instead tend to $\frac{N-1}{N}$. In small systems, where this deviation is noticeable, the `normalize` flag may be used to rescale the results and force the long range behavior to 1. Note that this option will have little to no effect on larger systems (for example, for systems of 100 particles the RDF will differ by 1%).

Note: **2D:** `freud.density.RDF` properly handles 2D boxes. The points must be passed in as `[x, y, 0]`.

Parameters

- **bins** (*unsigned int*) – The number of bins in the RDF.
- **r_max** (*float*) – Maximum interparticle distance to include in the calculation.
- **r_min** (*float, optional*) – Minimum interparticle distance to include in the calculation (Default value = 0).
- **normalize** (*bool, optional*) – Scale the RDF values by $\frac{N_{query_points}}{N_{query_points}-1}$. This argument primarily exists to deal with standard RDF calculations where no special `query_points` or `neighbors` are provided, but where the number of `query_points` is small enough that the long-ranged limit of $g(r)$ deviates significantly from 1. It should not be used if `query_points` is provided as a different set of points, or if unusual query arguments are provided to `compute()`, specifically if `exclude_ii` is set to `False`. This normalization is not meaningful in such cases and will simply convolute the data.

bin_centers

The centers of each bin in the histogram.

Type (N_{bins} ,) `numpy.ndarray`

property bin_counts

The bin counts in the histogram.

Type `numpy.ndarray`

bin_edges

The edges of each bin in the histogram. Is one element larger because each bin has a lower and upper bound.

Type ($N_{bins} + 1$,) `numpy.ndarray`

bounds

A tuple indicating upper and lower bounds of the histogram.

Type `tuple`

property box

The box object used in the last computation.

Type `freud.box.Box`

compute

Calculates the RDF and adds to the current RDF histogram.

Parameters

- **system** – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.
- **query_points** ((N_{query_points} , 3) `numpy.ndarray`, optional) – Query points used to calculate the RDF. Uses the system's points if None (Default value = None).
- **neighbors** (`freud.locality.NeighborList` or dict, optional) – Either a `NeighborList` of neighbor pairs to use in the calculation, or a dictionary of `query arguments` (Default value: None).
- **reset** (`bool`) – Whether to erase the previously computed values before adding the new computation; if False, will accumulate data (Default value: True).

default_query_args

The default query arguments are {'mode': 'ball', 'r_max': self.r_max}.

property n_r

Histogram of cumulative bin_counts values. More precisely, `n_r[i]` is the average number of points contained within a ball of radius `R[i]+dr/2` centered at a given `query_point` averaged over all `query_points` in the last call to `compute()`.

Type (N_{bins} ,) `numpy.ndarray`

nbins

The number of bins in the histogram

Type `int`

plot

Plot radial distribution function.

Parameters **ax** (`matplotlib.axes.Axes`, optional) – Axis to plot on. If None, make a new figure and axis. (Default value = None)

Returns Axis with the plot.

Return type (`matplotlib.axes.Axes`)

property `rdf`

Histogram of RDF values.

Type (N_{bins}) `numpy.ndarray`

7.13 Environment Module

Overview

<code>freud.environment.BondOrder</code>	Compute the bond orientational order diagram for the system of particles.
<code>freud.environment.LocalDescriptors</code>	Compute a set of descriptors (a numerical “fingerprint”) of a particle’s local environment.
<code>freud.environment.EnvironmentCluster</code>	Clusters particles according to whether their local environments match or not, according to various shape matching metrics.
<code>freud.environment.EnvironmentMotifMatch</code>	Find matches between local arrangements of a set of points and a provided motif.
<code>freud.environment.AngularSeparationGlobal</code>	Calculates the minimum angles of separation between orientations and global orientations.
<code>freud.environment.AngularSeparationNeighbor</code>	Calculates the minimum angles of separation between orientations and query orientations.
<code>freud.environment.LocalBondProjection</code>	Calculates the maximal projection of nearest neighbor bonds for each particle onto some set of reference vectors, defined in the particles’ local reference frame.

Details

The `freud.environment` module contains functions which characterize the local environments of particles in the system. These methods use the positions and orientations of particles in the local neighborhood of a given particle to characterize the particle environment.

class `freud.environment.AngularSeparationGlobal`

Bases: `freud.util._Compute`

Calculates the minimum angles of separation between orientations and global orientations.

property `angles`

($N_{orientations}$, $N_{global_orientations}$) `numpy.ndarray`: The global angles in radians.

compute

Calculates the minimum angles of separation between `global_orientations` and `orientations`, checking for underlying symmetry as encoded in `equiv_orientations`. The result is stored in the `global_angles` class attribute.

Parameters

- **`global_orientations`** ($(N_{global}, 4)$ `numpy.ndarray`) – Set of global orientations to calculate the order parameter.

- **orientations** ($(N_{particles}, 4)$ `numpy.ndarray`) – Orientations to calculate the order parameter.
- **equiv_orientations** ($(N_{equiv}, 4)$ `numpy.ndarray`, optional) – The set of all equivalent quaternions that map the particle to itself (the elements of its rotational symmetry group). Important: `equiv_orientations` must include both q and $-q$, for all included quaternions. Note that this calculation assumes that all points in the system share the same set of equivalent orientations. (Default value = `[[1, 0, 0, 0]]`)

class `freud.environment.AngularSeparationNeighbor`

Bases: `freud.locality._PairCompute`

Calculates the minimum angles of separation between orientations and query orientations.

property angles

The neighbor angles in radians. The angles are stored in the order of the neighborlist object.

Type (N_{bonds}) `numpy.ndarray`

compute

Calculates the minimum angles of separation between `orientations` and `query_orientations`, checking for underlying symmetry as encoded in `equiv_orientations`. The result is stored in the `neighbor_angles` class attribute.

Parameters

- **system** – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.
- **orientations** ($(N_{points}, 4)$ `numpy.ndarray`) – Orientations associated with system points that are used to calculate bonds.
- **query_points** ($(N_{query_points}, 3)$ `numpy.ndarray`, optional) – Query points used to calculate the correlation function. Uses the system's points if None (Default value = None).
- **query_orientations** ($(N_{query_points}, 4)$ `numpy.ndarray`, optional) – Query orientations used to calculate bonds. Uses `orientations` if None. (Default value = None).
- **equiv_orientations** ($(N_{equiv}, 4)$ `numpy.ndarray`, optional) – The set of all equivalent quaternions that map the particle to itself (the elements of its rotational symmetry group). Important: `equiv_orientations` must include both q and $-q$, for all included quaternions. Note that this calculation assumes that all points in the system share the same set of equivalent orientations. (Default value = `[[1, 0, 0, 0]]`)
- **neighbors** (`freud.locality.NeighborList` or dict, optional) – Either a `NeighborList` of neighbor pairs to use in the calculation, or a dictionary of `query arguments` (Default value: None).

default_query_args

No default query arguments.

property nlist

The neighbor list from the last compute.

Type `freud.locality.NeighborList`

class `freud.environment.BondOrder`

Bases: `freud.locality._SpatialHistogram`

Compute the bond orientational order diagram for the system of particles.

The bond orientational order diagram (BOOD) is a way of studying the average local environments experienced by particles. In a BOOD, a particle and its nearest neighbors (determined by either a prespecified number of neighbors or simply a cutoff distance) are treated as connected by a bond joining their centers. All of the bonds in the system are then binned by their azimuthal (θ) and polar (ϕ) angles to indicate the location of a particle's neighbors relative to itself. The distance between the particle and its neighbor is only important when determining whether it is counted as a neighbor, but is not part of the BOOD; as such, the BOOD can be viewed as a projection of all bonds onto the unit sphere. The resulting 2D histogram provides insight into how particles are situated relative to one-another in a system.

This class provides access to the classical BOOD as well as a few useful variants. These variants can be accessed via the `mode` arguments to the `compute()` method. Available modes of calculation are:

- `'bod'` (Bond Order Diagram, *default*): This mode constructs the default BOOD, which is the 2D histogram containing the number of bonds formed through each azimuthal (θ) and polar (ϕ) angle.
- `'lbod'` (Local Bond Order Diagram): In this mode, a particle's neighbors are rotated into the local frame of the particle before the BOOD is calculated, *i.e.* the directions of bonds are determined relative to the orientation of the particle rather than relative to the global reference frame. An example of when this mode would be useful is when a system is composed of multiple grains of the same crystal; the normal BOOD would show twice as many peaks as expected, but using this mode, the bonds would be superimposed.
- `'obcd'` (Orientation Bond Correlation Diagram): This mode aims to quantify the degree of orientational as well as translational ordering. As a first step, the rotation that would align a particle's neighbor with the particle is calculated. Then, the neighbor is rotated **around the central particle** by that amount, which actually changes the direction of the bond. One example of how this mode could be useful is in identifying plastic crystals, which exhibit translational but not orientational ordering. Normally, the BOOD for a plastic crystal would exhibit clear structure since there is translational order, but with this mode, the neighbor positions would actually be modified, resulting in an isotropic (disordered) BOOD.
- `'oodc'` (Orientation Orientation Correlation Diagram): This mode is substantially different from the other modes. Rather than compute the histogram of neighbor bonds, this mode instead computes a histogram of the directors of neighboring particles, where the director is defined as the basis vector \hat{z} rotated by the neighbor's quaternion. The directors are then rotated into the central particle's reference frame. This mode provides insight into the local orientational environment of particles, indicating, on average, how a particle's neighbors are oriented.

Parameters

- **bins** (*unsigned int or sequence of length 2*) – If an unsigned int, the number of bins in θ and ϕ . If a sequence of two integers, interpreted as (`num_bins_theta`, `num_bins_phi`).
- **mode** (*str, optional*) – Mode to calculate bond order. Options are `'bod'`, `'lbod'`, `'obcd'`, or `'oodc'` (Default value = `'bod'`).

`bin_centers`

The centers of each bin in the histogram (has the same shape as the histogram itself).

Type `numpy.ndarray`

property `bin_counts`

The bin counts in the histogram.

Type `numpy.ndarray`

`bin_edges`

The edges of each bin in the histogram (is one element larger in each dimension than the histogram because each bin has a lower and upper bound).

Type `numpy.ndarray`

property bond_order

Bond order.

Type (N_ϕ, N_θ) `numpy.ndarray`**bounds**

A list of tuples indicating upper and lower bounds of each axis of the histogram.

Type `list (tuple)`**property box**

Box used in the calculation.

Type `freud.box.Box`**compute**

Calculates the correlation function and adds to the current histogram.

Parameters

- **system** – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.
- **orientations** $((N_{points}, 4) \text{ numpy.ndarray})$ – Orientations associated with system points that are used to calculate bonds. Uses identity quaternions if None (Default value = None).
- **query_points** $((N_{query_points}, 3) \text{ numpy.ndarray}, \text{optional})$ – Query points used to calculate the correlation function. Uses the system's points if None (Default value = None).
- **query_orientations** $((N_{query_points}, 4) \text{ numpy.ndarray}, \text{optional})$ – Query orientations used to calculate bonds. Uses orientations if None. (Default value = None).
- **neighbors** (`freud.locality.NeighborList` or dict, optional) – Either a `NeighborList` of neighbor pairs to use in the calculation, or a dictionary of `query arguments` (Default value: None).
- **reset** (`bool`) – Whether to erase the previously computed values before adding the new computation; if False, will accumulate data (Default value: True).

default_query_args

No default query arguments.

mode

Bond order mode.

Type `str`**nbins**

The number of bins in each dimension of the histogram

Type `list`**class freud.environment.EnvironmentCluster**Bases: `freud.environment._MatchEnv`

Clusters particles according to whether their local environments match or not, according to various shape matching metrics.

property cluster_environments $(N_{clusters}, N_{neighbors}, 3) \text{ numpy.ndarray}$: The environments for all clusters.

property cluster_idx

The per-particle index indicating cluster membership.

Type ($N_{particles}$) `numpy.ndarray`

compute

Determine clusters of particles with matching environments.

In general, it is recommended to specify a number of neighbors rather than just a distance cutoff as part of your neighbor querying when performing this computation. Using a distance cutoff alone could easily lead to situations where a point doesn't match a cluster because a required neighbor is just outside the cutoff.

Parameters

- **system** – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.
- **threshold** (`float`) – Maximum magnitude of the vector difference between two vectors, below which they are “matching”. Typically, a good choice is between 10% and 30% of the first well in the radial distribution function (this has distance units).
- **neighbors** (`freud.locality.NeighborList` or dict, optional) – Either a `NeighborList` of neighbor pairs to use in the calculation, or a dictionary of **query arguments** (Default value: None).
- **env_neighbors** (`freud.locality.NeighborList` or dict, optional) – Either a `NeighborList` of neighbor pairs to use in the calculation, or a dictionary of **query arguments** (Default value: None). This argument is used to define the neighbors of the environment that motifs are registered against.
- **registration** (`bool`, optional) – If True, first use brute force registration to orient one set of environment vectors with respect to the other set such that it minimizes the RMSD between the two sets. (Default value = False)
- **global_search** (`bool`, optional) – If True, do an exhaustive search wherein the environments of every single pair of particles in the simulation are compared. If False, only compare the environments of neighboring particles. (Default value = False)

default_query_args

No default query arguments.

property num_clusters

The number of clusters.

Type unsigned int

plot

Plot cluster distribution.

Parameters **ax** (`matplotlib.axes.Axes`, optional) – Axis to plot on. If None, make a new figure and axis. (Default value = None)

Returns Axis with the plot.

Return type (`matplotlib.axes.Axes`)

property point_environments

($N_{points}, N_{neighbors}, 3$) `numpy.ndarray`: All environments for all points.

class freud.environment.EnvironmentMotifMatch

Bases: `freud.environment._MatchEnv`

Find matches between local arrangements of a set of points and a provided motif.

In general, it is recommended to specify a number of neighbors rather than just a distance cutoff as part of your neighbor querying when performing this computation since it can otherwise be very sensitive. Specifically, it is highly recommended that you choose a number of neighbors query that requests at least as many neighbors as the size of the motif you intend to test against. Otherwise, you will struggle to match the motif. However, this is not currently enforced.

compute

Determine clusters of particles that match the motif provided by motif.

Parameters

- **system** – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.
- **motif** ($(N_{points}, 3)$ `numpy.ndarray`) – Vectors that make up the motif against which we are matching.
- **threshold** (`float`) – Maximum magnitude of the vector difference between two vectors, below which they are “matching”. Typically, a good choice is between 10% and 30% of the first well in the radial distribution function (this has distance units).
- **neighbors** (`freud.locality.NeighborList` or dict, optional) – Either a `NeighborList` of neighbor pairs to use in the calculation, or a dictionary of `query arguments` (Default value: None).
- **registration** (`bool`, optional) – If True, first use brute force registration to orient one set of environment vectors with respect to the other set such that it minimizes the RMSD between the two sets (Default value = False).

default_query_args

No default query arguments.

property matches

A boolean array indicating whether each point matches the motif.

Type ($(N_{points},)$ `numpy.ndarray`)

property point_environments

$(N_{points}, N_{neighbors}, 3)$ `numpy.ndarray`: All environments for all points.

class freud.environment.LocalBondProjection

Bases: `freud.locality._PairCompute`

Calculates the maximal projection of nearest neighbor bonds for each particle onto some set of reference vectors, defined in the particles’ local reference frame.

compute

Calculates the maximal projections of nearest neighbor bonds (between `points` and `query_points`) onto the set of reference vectors `proj_vecs`, defined in the local reference frames of the `points` as defined by the orientations `orientations`. This computation accounts for the underlying symmetries of the reference frame as encoded in `equiv_orientations`.

Parameters

- **system** – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.
- **orientations** ($(N_{points}, 4)$ `numpy.ndarray`) – Orientations associated with system points that are used to calculate bonds.
- **proj_vecs** ($(N_{vectors}, 3)$ `numpy.ndarray`) – The set of projection vectors, defined in the query particles’ reference frame, to calculate maximal local bond projections onto.

- **query_points** ($(N_{\text{query_points}}, 3)$ `numpy.ndarray`, optional) – Query points used to calculate the correlation function. Uses the system’s points if `None` (Default value = `None`). (Default value = `None`).
- **equiv_orientations** ($(N_{\text{equiv}}, 4)$ `numpy.ndarray`, optional) – The set of all equivalent quaternions that map the particle to itself (the elements of its rotational symmetry group). Important: `equiv_orientations` must include both q and $-q$, for all included quaternions. Note that this calculation assumes that all points in the system share the same set of equivalent orientations. (Default value = `[[1, 0, 0, 0]]`)
- **neighbors** (`freud.locality.NeighborList` or dict, optional) – Either a `NeighborList` of neighbor pairs to use in the calculation, or a dictionary of `query arguments` (Default value: `None`).

default_query_args

No default query arguments.

property nlist

The neighbor list from the last compute.

Type `freud.locality.NeighborList`

property normed_projections

$(N_{\text{bonds}}, N_{\text{projection_vecs}})$ `numpy.ndarray`: The projection of each bond between query particles and their neighbors onto each of the projection vectors, normalized by the length of the bond.

property projections

$(N_{\text{bonds}}, N_{\text{projection_vecs}})$ `numpy.ndarray`: The projection of each bond between query particles and their neighbors onto each of the projection vectors.

class freud.environment.LocalDescriptors

Bases: `freud.locality._PairCompute`

Compute a set of descriptors (a numerical “fingerprint”) of a particle’s local environment.

The resulting spherical harmonic array will be a complex-valued array of shape $(\text{num_bonds}, \text{num_sphs})$. Spherical harmonic calculation can be restricted to some number of nearest neighbors through the `max_num_neighbors` argument; if a particle has more bonds than this number, the last one or more rows of bond spherical harmonics for each particle will not be set. This feature is useful for computing descriptors on the same system but with different subsets of neighbors; a `freud.locality.NeighborList` with the correct ordering can then be reused in multiple calls to `compute()` with different values of `max_num_neighbors` to compute descriptors for different local neighborhoods with maximum efficiency.

Parameters

- **l_max** (`unsigned int`) – Maximum spherical harmonic l to consider.
- **negative_m** (`bool`, optional) – True if we should also calculate Y_{lm} for negative m . (Default value = `True`)
- **mode** (`str`, optional) – Orientation mode to use for environments, either `'neighborhood'` to use the orientation of the local neighborhood, `'particle_local'` to use the given particle orientations, or `'global'` to not rotate environments (Default value = `'neighborhood'`).

compute

Calculates the local descriptors of bonds from a set of source points to a set of destination points.

Parameters

- **system** – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.

- **query_points** ($(N_{\text{query_points}}, 3)$ `numpy.ndarray`, optional) – Query points used to calculate the correlation function. Uses the system’s points if `None` (Default value = `None`).
- **orientations** ($(N_{\text{points}}, 4)$ `numpy.ndarray`) – Orientations associated with system points that are used to calculate bonds.
- **neighbors** (`freud.locality.NeighborList` or dict, optional) – Either a `NeighborList` of neighbor pairs to use in the calculation, or a dictionary of `query arguments` (Default value: `None`).
- **max_num_neighbors** (`unsigned int`, optional) – Hard limit on the maximum number of neighbors to use for each particle for the given neighbor-finding algorithm. Uses all neighbors if set to 0 (Default value = 0).

default_query_args

No default query arguments.

l_max

The maximum spherical harmonic l calculated for.

Type `unsigned int`

mode

Orientation mode to use for environments, either 'neighborhood' to use the orientation of the local neighborhood, 'particle_local' to use the given particle orientations, or 'global' to not rotate environments.

Type `str`

negative_m

True if we also calculated Y_{lm} for negative m .

Type `bool`

property nlist

The neighbor list from the last compute.

Type `freud.locality.NeighborList`

property num_sphs

The last number of spherical harmonics computed. This is equal to the number of bonds in the last computation, which is at most the number of `points` multiplied by the lower of the `num_neighbors` arguments passed to the last compute call or the constructor (it may be less if there are not enough neighbors for every particle).

Type `unsigned int`

property sph

$(N_{\text{bonds}}, \text{SphWidth})$ `numpy.ndarray`: The last computed spherical harmonic array.

7.14 Interface Module

Overview

*freud.interface.Interface*Measures the interface between two sets of points.

Details

The *freud.interface* module contains functions to measure the interface between sets of points.

class *freud.interface.Interface*

Bases: *freud.locality._PairCompute*

Measures the interface between two sets of points.

compute

Compute the particles at the interface between two sets of points.

Parameters

- **system** – Any object that is a valid argument to *freud.locality.NeighborQuery.from_system*.
- **query_points** (*(N_{query_points}, 3) numpy.ndarray*, optional) – Second set of points (in addition to the system points) to calculate the interface.
- **neighbors** (*freud.locality.NeighborList* or dict, optional) – Either a *NeighborList* of neighbor pairs to use in the calculation, or a dictionary of *query arguments* (Default value: None).

default_query_args

No default query arguments.

property point_count

Number of particles from *points* on the interface.

Type *int*

property point_ids

The particle IDs from *points*.

Type *np.ndarray*

property query_point_count

Number of particles from *query_points* on the interface.

Type *int*

property query_point_ids

The particle IDs from *query_points*.

Type *np.ndarray*

7.15 Locality Module

Overview

<code>freud.locality.AABBQuery</code>	Use an Axis-Aligned Bounding Box (AABB) tree [HAN+16] to find neighbors.
<code>freud.locality.LinkCell</code>	Supports efficiently finding all points in a set within a certain distance from a given point.
<code>freud.locality.NeighborList</code>	Class representing bonds between two sets of points.
<code>freud.locality.NeighborQuery</code>	Class representing a set of points along with the ability to query for neighbors of these points.
<code>freud.locality.NeighborQueryResult</code>	Class encapsulating the output of queries of NeighborQuery objects.
<code>freud.locality.PeriodicBuffer</code>	Replicate periodic images of points inside a box.
<code>freud.locality.Voronoi</code>	Computes Voronoi diagrams using voro++.

Details

The `freud.locality` module contains data structures to efficiently locate points based on their proximity to other points.

class `freud.locality.AABBQuery`

Bases: `freud.locality.NeighborQuery`

Use an Axis-Aligned Bounding Box (AABB) tree [HAN+16] to find neighbors.

Also available as `freud.AABBQuery`.

Parameters

- **box** (`freud.box.Box`) – Simulation box.
- **points** (`((N, 3) numpy.ndarray)`) – The points to use to build the tree.

box

The box object used by this data structure.

Type `freud.box.Box`

classmethod `from_system` (`type cls, system, dimensions=None`)

Create a `NeighborQuery` from any system-like object.

The standard concept of a system in **freud** is any object that provides a way to access a box-like object (anything that can be coerced to a box by `freud.box.Box.from_box()`) and an array-like object (according to NumPy’s definition) of particle positions that turns into a $N \times 3$ array.

Supported types for `system` include:

- `AABBQuery`
- `LinkCell`
- A sequence of (`box`, `points`) where `box` is a `Box` and `points` is a `numpy.ndarray`.
- Objects with attributes `box` and `points`.
- `MDAnalysis.coordinates.base.Timestep`
- `gsd.hoomd.Snapshot`

- `garnett.trajectory.Frame`
- `ovito.data.DataCollection`
- `hoomd.data` snapshot

Parameters

- **system** (*system-like object*) – Any object that can be converted to a [`NeighborQuery`](#).
- **dimensions** (*int*) – Whether the object is 2 or 3 dimensional. It may be inferred if not provided, but in some cases inference is not possible, in which case it will default to 3 (Default value = None).

Returns The same [`NeighborQuery`](#) object if one is given, or an instance of [`NeighborQuery`](#) built from an inferred box and points.

Return type [`freud.locality.NeighborQuery`](#)

plot

Plot system box and points.

Parameters

- **ax** ([`matplotlib.axes.Axes`](#)) – Axis to plot on. If None, make a new figure and axis. The axis projection (2D or 3D) must match the dimensionality of the system (Default value = None).
- **title** (*str*) – Title of the plot (Default value = None).
- ***args** – Passed on to [`mpl_toolkits.mplot3d.Axes3D.plot\(\)`](#) or [`matplotlib.axes.Axes.plot\(\)`](#).
- ****kwargs** – Passed on to [`mpl_toolkits.mplot3d.Axes3D.plot\(\)`](#) or [`matplotlib.axes.Axes.plot\(\)`](#).

Returns Axis with the plot.

Return type [`matplotlib.axes.Axes`](#)

points

The array of points in this data structure.

Type [`np.ndarray`](#)

query

Query for nearest neighbors of the provided point.

Parameters

- **query_points** (*(N, 3) numpy.ndarray*) – Points to query for.
- **query_args** (*dict*) – Query arguments determining how to find neighbors. For information on valid query argument, see the [Query API](#).

Returns Results object containing the output of this query.

Return type [`NeighborQueryResult`](#)

class [`freud.locality.LinkCell`](#)

Bases: [`freud.locality.NeighborQuery`](#)

Supports efficiently finding all points in a set within a certain distance from a given point.

Also available as [`freud.LinkCell`](#).

Parameters

- **box** (*freud.box.Box*) – Simulation box.
- **points** ($((N, 3)$ *numpy.ndarray*) – The points to bin into the cell list.
- **cell_width** (*float, optional*) – Width of cells. If not provided, *~LinkCell* will estimate a cell width based on the number of points and the box size assuming constant density of points throughout the box.

box

The box object used by this data structure.

Type *freud.box.Box*

cell_width

Cell width.

Type *float*

classmethod from_system (*type cls, system, dimensions=None*)

Create a *NeighborQuery* from any system-like object.

The standard concept of a system in **freud** is any object that provides a way to access a box-like object (anything that can be coerced to a box by *freud.box.Box.from_box()*) and an array-like object (according to [NumPy's definition](#)) of particle positions that turns into a $N \times 3$ array.

Supported types for system include:

- *AABBQuery*
- *LinkCell*
- A sequence of (box, points) where box is a *Box* and points is a *numpy.ndarray*.
- Objects with attributes box and points.
- *MDAnalysis.coordinates.base.Timestep*
- *gsd.hoomd.Snapshot*
- *garnett.trajectory.Frame*
- *ovito.data.DataCollection*
- *hoomd.data* snapshot

Parameters

- **system** (*system-like object*) – Any object that can be converted to a *NeighborQuery*.
- **dimensions** (*int*) – Whether the object is 2 or 3 dimensional. It may be inferred if not provided, but in some cases inference is not possible, in which case it will default to 3 (Default value = None).

Returns The same *NeighborQuery* object if one is given, or an instance of *NeighborQuery* built from an inferred box and points.

Return type *freud.locality.NeighborQuery*

plot

Plot system box and points.

Parameters

- **ax** (`matplotlib.axes.Axes`) – Axis to plot on. If `None`, make a new figure and axis. The axis projection (2D or 3D) must match the dimensionality of the system (Default value = `None`).
- **title** (`str`) – Title of the plot (Default value = `None`).
- ***args** – Passed on to `mpl_toolkits.mplot3d.Axes3D.plot()` or `matplotlib.axes.Axes.plot()`.
- ****kwargs** – Passed on to `mpl_toolkits.mplot3d.Axes3D.plot()` or `matplotlib.axes.Axes.plot()`.

Returns Axis with the plot.

Return type `matplotlib.axes.Axes`

points

The array of points in this data structure.

Type `np.ndarray`

query

Query for nearest neighbors of the provided point.

Parameters

- **query_points** (`((N, 3) numpy.ndarray)`) – Points to query for.
- **query_args** (`dict`) – Query arguments determining how to find neighbors. For information on valid query argument, see the [Query API](#).

Returns Results object containing the output of this query.

Return type `NeighborQueryResult`

class `freud.locality.NeighborList`

Bases: `object`

Class representing bonds between two sets of points.

Compute classes contain a set of bonds between two sets of position arrays (“query points” and “points”) and hold a list of index pairs (i, j) where $i < N_{\text{query_points}}$, $j < N_{\text{points}}$ corresponding to neighbor pairs between the two sets.

For efficiency, all bonds must be sorted by the query point index, from least to greatest. Bonds have an query point index i and a point index j . The first bond index corresponding to a given query point can be found in $\log(N_{\text{bonds}})$ time using `find_first_index()`, because bonds are ordered by the query point index.

Note: Typically, there is no need to instantiate this class directly. In most cases, users should manipulate `freud.locality.NeighborList` objects received from a neighbor search algorithm, such as `freud.locality.LinkCell`, `freud.locality.AABBQuery`, or `freud.locality.Voronoi`.

Also available as `freud.NeighborList`.

Example:

```
# Assume we have position as Nx3 array
aq = freud.locality.AABBQuery(box, positions)
nlist = aq.query(positions, {'r_max': 3}).toNeighborList()

# Get all vectors from central particles to their neighbors
rijs = (positions[nlist.point_indices] -
```

(continues on next page)

(continued from previous page)

```
positions[nlist.query_point_indices])
rijs = box.wrap(rijs)
```

The NeighborList can be indexed to access bond particle indices. Example:

```
for i, j in nlist[:]:
    print(i, j)
```

copy

Create a copy. If other is given, copy its contents into this object. Otherwise, return a copy of this object.

Parameters **other** (*freud.locality.NeighborList*, optional) – A NeighborList to copy into this object (Default value = None).

distances

The distances for each bond.

Type (N_{bonds}) np.ndarray

filter

Removes bonds that satisfy a boolean criterion.

Parameters **filt** (np.ndarray) – Boolean-like array of bonds to keep (True means the bond will not be removed).

Note: This method modifies this object in-place.

Example:

```
# Keep only the bonds between particles of type A and type B
nlist.filter(types[nlist.query_point_indices] != types[nlist.point_indices])
```

filter_r

Removes bonds that are outside of a given radius range.

Parameters

- **r_max** (*float*) – Maximum bond distance in the resulting neighbor list.
- **r_min** (*float*, optional) – Minimum bond distance in the resulting neighbor list (Default value = 0).

find_first_index

Returns the lowest bond index corresponding to a query particle with an index $\geq i$.

Parameters **i** (*unsigned int*) – The particle index.

classmethod from_arrays (*type cls, num_query_points, num_points, query_point_indices, point_indices, distances, weights=None*)

Create a NeighborList from a set of bond information arrays.

Parameters

- **num_query_points** (*int*) – Number of query points (corresponding to query_point_indices).
- **num_points** (*int*) – Number of points (corresponding to point_indices).
- **query_point_indices** (np.ndarray) – Array of integers corresponding to indices in the set of query points.

- **point_indices** (`np.ndarray`) – Array of integers corresponding to indices in the set of points.
- **distances** (`np.ndarray`) – Array of distances between corresponding query points and points.
- **weights** (`np.ndarray`, optional) – Array of per-bond weights (if `None` is given, use a value of 1 for each weight) (Default value = `None`).

neighbor_counts

A neighbor count array indicating the number of neighbors for each query point.

Type ($N_{\text{query_points}}$) `np.ndarray`

point_indices

The point indices for each bond. This array is read-only to prevent breakage of `find_first_index()`. Equivalent to indexing with `[:, 1]`.

Type (N_{bonds}) `np.ndarray`

query_point_indices

The query point indices for each bond. This array is read-only to prevent breakage of `find_first_index()`. Equivalent to indexing with `[:, 0]`.

Type (N_{bonds}) `np.ndarray`

segments

A segment array indicating the first bond index for each query point.

Type ($N_{\text{query_points}}$) `np.ndarray`

weights

The weights for each bond. By default, bonds have a weight of 1.

Type (N_{bonds}) `np.ndarray`

class `freud.locality.NeighborQuery`

Bases: `object`

Class representing a set of points along with the ability to query for neighbors of these points.

Warning: This class should not be instantiated directly. The subclasses `AABBQuery` and `LinkCell` provide the intended interfaces.

The `NeighborQuery` class represents the abstract interface for neighbor finding. The class contains a set of points and a simulation box, the latter of which is used to define the system and the periodic boundary conditions required for finding neighbors of these points. The primary mode of interacting with the `NeighborQuery` is through the `query()` and `queryBall()` functions, which enable finding either the nearest neighbors of a point or all points within a distance cutoff, respectively. Subclasses of `NeighborQuery` implement these methods based on the nature of the underlying data structure.

Parameters

- **box** (`freud.box.Box`) – Simulation box.
- **points** ($(N, 3)$ `numpy.ndarray`) – Point coordinates to build the structure.

box

The box object used by this data structure.

Type `freud.box.Box`

classmethod `from_system` (*type cls, system, dimensions=None*)

Create a `NeighborQuery` from any system-like object.

The standard concept of a system in **freud** is any object that provides a way to access a box-like object (anything that can be coerced to a box by `freud.box.Box.from_box()`) and an array-like object (according to NumPy's definition) of particle positions that turns into a $N \times 3$ array.

Supported types for `system` include:

- `AABBQuery`
- `LinkCell`
- A sequence of (`box`, `points`) where `box` is a `Box` and `points` is a `numpy.ndarray`.
- Objects with attributes `box` and `points`.
- `MDAnalysis.coordinates.base.Timestep`
- `gsd.hoomd.Snapshot`
- `garnett.trajectory.Frame`
- `ovito.data.DataCollection`
- `hoomd.data` snapshot

Parameters

- **system** (*system-like object*) – Any object that can be converted to a `NeighborQuery`.
- **dimensions** (*int*) – Whether the object is 2 or 3 dimensional. It may be inferred if not provided, but in some cases inference is not possible, in which case it will default to 3 (Default value = None).

Returns The same `NeighborQuery` object if one is given, or an instance of `NeighborQuery` built from an inferred box and points.

Return type `freud.locality.NeighborQuery`

plot

Plot system box and points.

Parameters

- **ax** (`matplotlib.axes.Axes`) – Axis to plot on. If None, make a new figure and axis. The axis projection (2D or 3D) must match the dimensionality of the system (Default value = None).
- **title** (*str*) – Title of the plot (Default value = None).
- ***args** – Passed on to `mpl_toolkits.mplot3d.Axes3D.plot()` or `matplotlib.axes.Axes.plot()`.
- ****kwargs** – Passed on to `mpl_toolkits.mplot3d.Axes3D.plot()` or `matplotlib.axes.Axes.plot()`.

Returns Axis with the plot.

Return type `matplotlib.axes.Axes`

points

The array of points in this data structure.

Type `np.ndarray`

query

Query for nearest neighbors of the provided point.

Parameters

- **query_points** ((N , 3) `numpy.ndarray`) – Points to query for.
- **query_args** (`dict`) – Query arguments determining how to find neighbors. For information on valid query argument, see the [Query API](#).

Returns Results object containing the output of this query.

Return type `NeighborQueryResult`

class `freud.locality.NeighborQueryResult`

Bases: `object`

Class encapsulating the output of queries of `NeighborQuery` objects.

Warning: This class should not be instantiated directly, it is the return value of all *query** functions of `NeighborQuery`. The class provides a convenient interface for iterating over query results, and can be transparently converted into a list or a `NeighborList` object.

The `NeighborQueryResult` makes it easy to work with the results of queries and convert them to various natural objects. Additionally, the result is a generator, making it easy for users to lazily iterate over the object.

toNeighborList

Convert query result to a `freud NeighborList`.

Parameters **sort_by_distance** (`bool`) – If `True`, sort neighboring bonds by distance. If `False`, sort neighboring bonds by point index (Default value = `False`).

Returns A `freud NeighborList` containing all neighbor pairs found by the query generating this result object.

Return type `NeighborList`

class `freud.locality.PeriodicBuffer`

Bases: `freud.util._Compute`

Replicate periodic images of points inside a box.

property buffer_box

The buffer box, expanded to hold the replicated points.

Type `freud.box.Box`

property buffer_ids

The buffer point ids.

Type (N_{buffer}) `numpy.ndarray`

property buffer_points

The buffer point positions.

Type (N_{buffer} , 3) `numpy.ndarray`

compute

Compute the periodic buffer.

Parameters

- **system** – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.

- **buffer** (*float or list of 3 floats*) – Buffer distance for replication outside the box.
- **images** (*bool, optional*) – If `False`, `buffer` is a distance. If `True`, `buffer` is a number of images to replicate in each dimension. Note that one image adds half of a box length to each side, meaning that one image doubles the box side lengths, two images triples the box side lengths, and so on. (Default value = `False`).

class `freud.locality.Voronoi`

Bases: `freud.util._Compute`

Computes Voronoi diagrams using voro++.

Voronoi diagrams ([Wikipedia](#)) are composed of convex polytopes (polyhedra in 3D, polygons in 2D) called cells, corresponding to each input point. The cells bound a region of Euclidean space for which all contained points are closer to a corresponding input point than any other input point. A ridge is defined as a boundary between cells, which contains points equally close to two or more input points.

The voro++ library [[Ryc09](#)] is used for fast computations of the Voronoi diagram.

compute

Compute Voronoi diagram.

Parameters `system` – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.

property `nlist`

Returns the computed `NeighborList`.

The `NeighborList` computed by this class is weighted. In 2D systems, the bond weight is the length of the ridge (boundary line) between the neighboring points' Voronoi cells. In 3D systems, the bond weight is the area of the ridge (boundary polygon) between the neighboring points' Voronoi cells. The weights are not normalized, and the weights for each query point sum to the surface area (perimeter in 2D) of the polytope.

It is possible for pairs of points to appear multiple times in the neighbor list. For example, in a small unit cell, points may neighbor one another on multiple sides because of periodic boundary conditions.

Returns Neighbor list.

Return type `NeighborList`

plot

Plot Voronoi diagram.

Parameters `ax` (`matplotlib.axes.Axes`) – Axis to plot on. If `None`, make a new figure and axis. (Default value = `None`)

color_by_sides (`bool`): If `True`, color cells by the number of sides. If `False`, random colors are used for each cell. (Default value = `True`)

cmap (`str`): Colormap name to use (Default value = `None`).

Returns Axis with the plot.

Return type `matplotlib.axes.Axes`

property `polytopes`

A list of `numpy.ndarray` defining Voronoi polytope vertices for each cell.

Type `list[numpy.ndarray]`

property volumes

Returns an array of Voronoi cell volumes (areas in 2D).

Type (N_{points}) `numpy.ndarray`

7.16 MSD Module

Overview

*freud.msd.MSD*Compute the mean squared displacement.

Details

The *freud.msd* module provides functions for computing the mean-squared-displacement (MSD) of particles in periodic systems.

class `freud.msd.MSD`

Bases: `freud.util._Compute`

Compute the mean squared displacement.

The mean squared displacement (MSD) measures how much particles move over time. The MSD plays an important role in characterizing Brownian motion, since it provides a measure of whether particles are moving according to diffusion alone or if there are other forces contributing. There are a number of definitions for the mean squared displacement. This function provides access to the two most common definitions through the mode argument.

- 'window' (*default*): This mode calculates the most common form of the MSD, which is defined as

$$MSD(m) = \frac{1}{N_{particles}} \sum_{i=1}^{N_{particles}} \frac{1}{N-m} \sum_{k=0}^{N-m-1} (\vec{r}_i(k+m) - \vec{r}_i(k))^2$$

where $r_i(t)$ is the position of particle i in frame t . According to this definition, the mean squared displacement is the average displacement over all windows of length m over the course of the simulation. Therefore, for any m , $MSD(m)$ is averaged over all windows of length m and over all particles. This calculation can be accessed using the 'window' mode of this function.

The windowed calculation can be quite computationally intensive. To perform this calculation efficiently, we use the algorithm described in [CPC+11] as described in [this StackOverflow thread](#).

Note: The most intensive part of this calculation is computing an FFT. To maximize performance, *freud* attempts to use the fastest FFT library available. By default, the order of preference is `pyFFTW`, `SciPy`, and then `NumPy`. If you are experiencing significant slowdowns in calculating the MSD, you may benefit from installing a faster FFT library, which *freud* will automatically detect. The performance change will be especially noticeable if the length of your trajectory is a number whose prime factorization consists of extremely large prime factors. The standard Cooley-Tukey FFT algorithm performs very poorly in this case, so installing `pyFFTW` will significantly improve performance.

Note that while `pyFFTW` is released under the BSD 3-Clause license, the `FFTW` library is available under either GPL or a commercial license.

- `'direct'`: Under some circumstances, however, we may be more interested in calculating a different quantity described by

$$MSD(t) = \frac{1}{N_{particles}} \sum_{i=1}^{N_{particles}} (r_i(t) - r_i(0))^2$$

In this case, at each time point (i.e. simulation frame) we simply compute how much particles have moved from their initial position, averaged over all particles. For more information on this calculation, see [the Wikipedia page](#).

Note: The MSD is only well-defined when the box is constant over the course of the simulation. Additionally, the number of particles must be constant over the course of the simulation.

Parameters

- **box** (*freud.box.Box*, optional) – If not provided, the class will assume that all positions provided in calls to `compute()` are already unwrapped. (Default value = None).
- **mode** (*str*, optional) – Mode of calculation. Options are `'window'` and `'direct'`. (Default value = `'window'`).

box

Box used in the calculation.

Type *freud.box.Box*

compute

Calculate the MSD for the positions provided.

Note: Unlike most methods in `freud`, accumulation for the MSD is split over points rather than frames of a simulation. The reason for this choice is that efficient computation of the MSD requires using the entire trajectory for a given particle. As a result, when setting `reset=False`, you must provide the positions of each point over the full length of the trajectory, but you may call `compute` multiple times with different subsets the points to calculate the MSD over the full set of positions. The primary use-case is when the trajectory is so large that computing an MSD on all particles at once is prohibitively expensive.

Parameters

- **positions** (*(N_{frames}, N_{particles}, 3) numpy.ndarray*) – The particle positions over a trajectory. If neither box nor images are provided, the positions are assumed to be unwrapped already.
- **images** (*(N_{frames}, N_{particles}, 3) numpy.ndarray*, optional) – The particle images to unwrap with if provided. Must be provided along with a simulation box (in the constructor) if particle positions need to be unwrapped. If neither are provided, positions are assumed to be unwrapped already. (Default value = None).
- **reset** (*bool*) – Whether to erase the previously computed values before adding the new computation; if False, will accumulate data (Default value: True).

property msd

The mean squared displacement.

Type (*N_{frames},*) *numpy.ndarray*

plot

Plot MSD.

Parameters **ax** (`matplotlib.axes.Axes`, optional) – Axis to plot on. If `None`, make a new figure and axis. (Default value = `None`)

Returns Axis with the plot.

Return type (`matplotlib.axes.Axes`)

7.17 Order Module

Overview

<code>freud.order.Cubatic</code>	Compute the cubatic order parameter [HAG15] for a system of particles using simulated annealing instead of Newton-Raphson root finding.
<code>freud.order.Nematic</code>	Compute the nematic order parameter for a system of particles.
<code>freud.order.Hexatic</code>	Calculates the k -atic order parameter for 2D systems.
<code>freud.order.Translational</code>	Compute the translational order parameter for each particle.
<code>freud.order.Steinhardt</code>	Compute the local Steinhardt [Ste83] rotationally invariant Q_l W_l order parameter for a set of points.
<code>freud.order.SolidLiquid</code>	Identifies solid-like clusters using dot products of q_{lm} .
<code>freud.order.RotationalAutocorrelation</code>	Calculates a measure of total rotational autocorrelation.

Details

The `freud.order` module contains functions which compute order parameters for the whole system or individual particles. Order parameters take bond order data and interpret it in some way to quantify the degree of order in a system using a scalar value. This is often done through computing spherical harmonics of the bond order diagram, which are the spherical analogue of Fourier Transforms.

class `freud.order.Cubatic`Bases: `freud.util._Compute`

Compute the cubatic order parameter [HAG15] for a system of particles using simulated annealing instead of Newton-Raphson root finding.

Parameters

- **t_initial** (`float`) – Starting temperature.
- **t_final** (`float`) – Final temperature.
- **scale** (`float`) – Scaling factor to reduce temperature.
- **n_replicates** (`unsigned int`, *optional*) – Number of replicate simulated annealing runs. (Default value = 1).
- **seed** (`unsigned int`, *optional*) – Random seed to use in calculations. If `None`, system time is used. (Default value = `None`).

compute

Calculates the per-particle and global order parameter.

Parameters orientations ($(N_{particles}, 4)$ `numpy.ndarray`) – Orientations as angles to use in computation.

property cubatic_tensor

Rank 4 homogeneous tensor representing the optimal system-wide coordinates.

Type (3, 3, 3, 3) `numpy.ndarray`

property global_tensor

Rank 4 tensor corresponding to the global orientation. Computed from all orientations.

Type (3, 3, 3, 3) `numpy.ndarray`

property order

Cubatic order parameter of the system.

Type `float`

property orientation

The quaternion of global orientation.

Type (4) `numpy.ndarray`

property particle_order

Order parameter.

Type ($N_{particles}$) `numpy.ndarray`

scale

The scale.

Type `float`

seed

Random seed to use in calculations.

Type unsigned int

t_final

The value of the final temperature.

Type `float`

t_initial

The value of the initial temperature.

Type `float`

class `freud.order.Hexatic`

Bases: `freud.locality._PairCompute`

Calculates the k -atic order parameter for 2D systems.

The k -atic order parameter (called the hexatic order parameter for $k = 6$) is analogous to Steinhardt order parameters, and is used to measure order in the bonds of 2D systems.

The k -atic order parameter for a particle i and its n neighbors j is given by:

$$\psi_k(i) = \frac{1}{n} \sum_j^n e^{ki\phi_{ij}}$$

The parameter k governs the symmetry of the order parameter and typically matches the number of neighbors to be found for each particle. The quantity ϕ_{ij} is the angle between the vector r_{ij} and $(1, 0)$.

Note: 2D: `freud.order.Hexatic` is only defined for 2D systems. The points must be passed in as `[x, y, 0]`.

Parameters `k` (*unsigned int, optional*) – Symmetry of order parameter. (Default value = 6).

compute

Calculates the hexatic order parameter.

Parameters

- **system** – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.
- **neighbors** (`freud.locality.NeighborList` or dict, optional) – Either a `NeighborList` of neighbor pairs to use in the calculation, or a dictionary of `query arguments` (Default value: None).

default_query_args

The default query arguments are `{ 'mode': 'nearest', 'num_neighbors': self.k }`.

k

Symmetry of the order parameter.

Type unsigned int

property particle_order

Order parameter.

Type ($N_{particles}$) `numpy.ndarray`

class `freud.order.Nematic`

Bases: `freud.util._Compute`

Compute the nematic order parameter for a system of particles.

Parameters `u` ((3) `numpy.ndarray`) – The nematic director of a single particle in the reference state (without any rotation applied).

compute

Calculates the per-particle and global order parameter.

Parameters `orientations` (($N_{particles}, 4$) `numpy.ndarray`) – Orientations to calculate the order parameter.

property director

The average nematic director.

Type (3) `numpy.ndarray`

property nematic_tensor

3x3 matrix corresponding to the average particle orientation.

Type (3,3) `numpy.ndarray`

property order

Nematic order parameter of the system.

Type float

property particle_tensor

$(N_{\text{particles}}, 3, 3)$ `numpy.ndarray`: One 3x3 matrix per-particle corresponding to each individual particle orientation.

u

The normalized reference director (the normalized vector provided on construction).

Type (3) `numpy.ndarray`

class freud.order.RotationalAutocorrelation

Bases: `freud.util._Compute`

Calculates a measure of total rotational autocorrelation.

For any calculation of rotational correlations of extended (i.e. non-point) particles, encoding the symmetries of these particles is crucial to appropriately determining correlations. For systems of anisotropic particles in three dimensions, representing such equivalence can be quite mathematically challenging. This calculation is based on the hyperspherical harmonics as laid out in [KDvAG19]. Generalizations of spherical harmonics to four dimensions, hyperspherical harmonics provide a natural basis for periodic functions in 4 dimensions just as harmonic functions (sines and cosines) or spherical harmonics do in lower dimensions. The idea behind this calculation is to embed orientation quaternions into a 4-dimensional space and then use hyperspherical harmonics to find correlations in a symmetry-aware fashion.

The choice of the hyperspherical harmonic parameter l determines the symmetry of the functions. The output is not a correlation function, but rather a scalar value that measures total system orientational correlation with an initial state. As such, the output can be treated as an order parameter measuring degrees of rotational (de)correlation. For analysis of a trajectory, the compute call needs to be done at each trajectory frame.

Parameters **1** (`int`) – Order of the hyperspherical harmonic. Must be a positive, even integer.

compute

Calculates the rotational autocorrelation function for a single frame.

Parameters

- **ref_orientations** $((N_{\text{orientations}}, 4)$ `numpy.ndarray`) – Orientations for the initial frame.
- **orientations** $((N_{\text{orientations}}, 4)$ `numpy.ndarray`) – Orientations for the frame of interest.

l

The azimuthal quantum number, which defines the order of the hyperspherical harmonic.

Type `int`

property order

Autocorrelation of the system.

Type `float`

property particle_order

Rotational autocorrelation values calculated for each orientation.

Type $(N_{\text{orientations}})$ `numpy.ndarray`

class freud.order.SolidLiquid

Bases: `freud.locality._PairCompute`

Identifies solid-like clusters using dot products of q_{lm} .

The solid-liquid order parameter [tW95][FHND10] uses a Steinhardt-like approach to identify solid-like particles. First, a bond parameter $q_l(i, j)$ is computed for each neighbor bond.

If `normalize_q` is true (default), the bond parameter is given by $q_l(i, j) = \frac{\sum_{m=-l}^l \text{Re } q_{lm}(i) q_{lm}^*(j)}{\sqrt{\sum_{m=-l}^l |q_{lm}(i)|^2} \sqrt{\sum_{m=-l}^l |q_{lm}(j)|^2}}$

If `normalize_q` is false, then the denominator of the above expression is left out.

Next, the bonds are filtered to keep only “solid-like” bonds with $q_l(i, j)$ above a cutoff value $q_{threshold}$.

If a particle has more than $S_{threshold}$ solid-like bonds, then the particle is considered solid-like. Finally, solid-like particles are clustered.

Parameters

- **l** (*unsigned int*) – Spherical harmonic quantum number l .
- **q_threshold** (*float*) – Value of dot product threshold when evaluating $q_l(i, j)$ to determine if a bond is solid-like. For $l = 6$, 0.7 is generally good for FCC or BCC structures [FHND10].
- **solid_threshold** (*unsigned int*) – Minimum required number of adjacent solid-like bonds for a particle to be considered solid-like for clustering. For $l = 6$, 6-8 is generally good for FCC or BCC structures.
- **normalize_q** (*bool*) – Whether to normalize the dot product (Default value = True).

property cluster_idx

($N_{particles}$) `numpy.ndarray`: Solid-like cluster indices for each particle.

property cluster_sizes

The sizes of all clusters.

Type ($N_{clusters}$,) `np.ndarray`

compute

Compute the order parameter.

Parameters

- **system** – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.
- **neighbors** (`freud.locality.NeighborList` or dict, optional) – Either a `NeighborList` of neighbor pairs to use in the calculation, or a dictionary of `query arguments` (Default value: None).

default_query_args

No default query arguments.

l

Spherical harmonic quantum number l .

Type unsigned int

property largest_cluster_size

The largest cluster size.

Type unsigned int

property nlist

Neighbor list of solid-like bonds.

Type `freud.locality.NeighborList`

normalize_q

Whether the dot product is normalized.

Type `bool`

property num_connections

The number of solid-like bonds for each particle.

Type ($N_{particles}$) `numpy.ndarray`

plot

Plot solid-like cluster distribution.

Parameters **ax** (`matplotlib.axes.Axes`, optional) – Axis to plot on. If `None`, make a new figure and axis. (Default value = `None`)

Returns Axis with the plot.

Return type (`matplotlib.axes.Axes`)

q_threshold

Value of dot product threshold.

Type `float`

property ql_ij

Bond dot products $q_l(i, j)$. Indexed by the elements of `self.nlist`.

Type (N_{bonds}) `numpy.ndarray`

solid_threshold

Value of number-of-bonds threshold.

Type `float`

class freud.order.Steinhardt

Bases: `freud.locality._PairCompute`

Compute the local Steinhardt [Ste83] rotationally invariant Q_l W_l order parameter for a set of points.

Implements the local rotationally invariant q_l or w_l order parameter described by Steinhardt. For a particle i , we calculate the average order parameter by summing the spherical harmonics between particle i and its neighbors

j in a local region: $\bar{q}_{lm}(i) = \frac{1}{N_b} \sum_{j=1}^{N_b} Y_{lm}(\theta(\vec{r}_{ij}), \phi(\vec{r}_{ij}))$. The particles included in the sum are determined by the `r_max` argument to the constructor.

For q_l , this is then combined in a rotationally invariant fashion to remove local orientational order as follows:

$$q_l(i) = \sqrt{\frac{4\pi}{2l+1} \sum_{m=-l}^l |\bar{q}_{lm}|^2}.$$

For w_l , it is then defined as a weighted average over the $\bar{q}_{lm}(i)$ values using Wigner 3j symbols (Clebsch-Gordan coefficients). The resulting combination is rotationally (i.e. frame) invariant.

The `average` argument in the constructor provides access to a variant of this parameter that performs a average over the first and second shell combined [LD08]. To compute this parameter, we perform a second averaging over the first neighbor shell of the particle to implicitly include information about the second neighbor shell. This averaging is performed by replacing the value $\bar{q}_{lm}(i)$ in the original definition by the average value of $\bar{q}_{lm}(k)$ over all the k neighbors of particle i as well as itself.

The `norm` attribute argument provides normalized versions of the order parameter, where the normalization is performed by averaging the q_{lm} values over all particles before computing the order parameter of choice.

Parameters

- **l** (*unsigned int*) – Spherical harmonic quantum number l .
- **average** (*bool, optional*) – Determines whether to calculate the averaged Steinhardt order parameter. (Default value = `False`)

- **wl** (*bool*, *optional*) – Determines whether to use the w_l version of the Steinhardt order parameter. (Default value = `False`)
- **weighted** (*bool*, *optional*) – Determines whether to use neighbor weights in the computation of spherical harmonics over neighbors. If enabled and used with a Voronoi neighbor list, this results in the Minkowski Structure Metrics q'_l . (Default value = `False`)
- **wl_normalize** (*bool*, *optional*) – Determines whether to normalize the w_l version of the Steinhardt order parameter. (Default value = `False`)

average

Whether the the averaged Steinhardt order parameter was calculated.

Type `bool`

compute

Compute the order parameter.

Parameters

- **system** – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.
- **neighbors** (`freud.locality.NeighborList` or dict, optional) – Either a `NeighborList` of neighbor pairs to use in the calculation, or a dictionary of `query arguments` (Default value: `None`).

default_query_args

No default query arguments.

l

Spherical harmonic quantum number l .

Type `unsigned int`

property order

The system wide normalization of the q_l or w_l order parameter.

Type `float`

property particle_order

Variant of the Steinhardt order parameter for each particle (filled with `nan` for particles with no neighbors).

Type ($N_{particles}$) `numpy.ndarray`

plot

Plot order parameter distribution.

Parameters **ax** (`matplotlib.axes.Axes`, optional) – Axis to plot on. If `None`, make a new figure and axis. (Default value = `None`)

Returns Axis with the plot.

Return type (`matplotlib.axes.Axes`)

property ql

($N_{particles}$) `numpy.ndarray`: q_l Steinhardt order parameter for each particle (filled with `nan` for particles with no neighbors). This is always available, no matter which options are selected.

weighted

Whether neighbor weights were used in the computation of spherical harmonics over neighbors.

Type `bool`

wlWhether the W_l version of the Steinhardt order parameter was used.**Type** `bool`**class** `freud.order.Translational`Bases: `freud.locality._PairCompute`

Compute the translational order parameter for each particle.

Note: 2D: `freud.order.Translational` is only defined for 2D systems. The points must be passed in as `[x, y, 0]`.

Parameters `k` (`float`, *optional*) – Symmetry of order parameter. (Default value = 6.0).**compute**

Calculates the local descriptors.

Parameters

- **system** – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.
- **neighbors** (`freud.locality.NeighborList` or dict, *optional*) – Either a `NeighborList` of neighbor pairs to use in the calculation, or a dictionary of `query arguments` (Default value: None).

default_query_args`{'mode': 'nearest', 'num_neighbors': int(self.k)}.`**Type** The default query arguments are**Type** `code`**k**

Normalization of the order parameter.

Type `unsigned int`**property** `particle_order`

Order parameter.

Type ($N_{particles}$) `numpy.ndarray`

7.18 Parallel Module

Overview

<code>freud.parallel.NumThreads</code>	Context manager for managing the number of threads to use.
<code>freud.parallel.get_num_threads</code>	Get the number of threads for parallel computation.
<code>freud.parallel.set_num_threads</code>	Set the number of threads for parallel computation.

Details

The `freud.parallel` module controls the parallelization behavior of freud, determining how many threads the TBB-enabled parts of freud will use. freud uses all available threads for parallelization unless directed otherwise.

class `freud.parallel.NumThreads`

Bases: `object`

Context manager for managing the number of threads to use.

Parameters `N` (*int*, *optional*) – Number of threads to use in this context. If `None`, which will use all available threads. (Default value = `None`).

`freud.parallel.get_num_threads`

Get the number of threads for parallel computation.

Returns Number of threads.

Return type (*int*)

`freud.parallel.set_num_threads`

Set the number of threads for parallel computation.

Parameters `nthreads` (*int*, *optional*) – Number of threads to use. If `None`, use all threads available. (Default value = `None`).

7.19 PMFT Module

Overview

<code>freud.pmft.PMFTR12</code>	Computes the PMFT [vAKA+14][vAAS+13] in a 2D system described by r , θ_1 , θ_2 .
<code>freud.pmft.PMFTXYT</code>	Computes the PMFT [vAKA+14][vAAS+13] for systems described by coordinates x , y , θ .
<code>freud.pmft.PMFTXY</code>	Computes the PMFT [vAKA+14][vAAS+13] in coordinates x , y .
<code>freud.pmft.PMFTXYZ</code>	Computes the PMFT [vAKA+14][vAAS+13] in coordinates x , y , z .

Details

The `freud.pmft` module allows for the calculation of the Potential of Mean Force and Torque (PMFT) [vAKA+14][vAAS+13] in a number of different coordinate systems. The shape of the arrays computed by this module depend on the coordinate system used, with space discretized into a set of bins created by the PMFT object's constructor. Each query point's neighboring points are assigned to bins, determined by the relative positions and/or orientations of the particles. Next, the pair correlation function (PCF) is computed by normalizing the binned histogram, by dividing out the number of accumulated frames, bin sizes (the Jacobian), and query point number density. The PMFT is then defined as the negative logarithm of the PCF. For further descriptions of the numerical methods used to compute the PMFT, refer to the supplementary information of [vAKA+14].

Note: The coordinate system in which the calculation is performed is not the same as the coordinate system in which particle positions and orientations should be supplied. Only certain coordinate systems are available for certain particle positions and orientations:

- 2D particle coordinates (position: $[x, y, 0]$, orientation: θ):
 - r, θ_1, θ_2 .
 - x, y .
 - x, y, θ .
- 3D particle coordinates:
 - x, y, z .

Note: For any bins where the histogram is zero (i.e. no observations were made with that relative position/orientation of particles), the PMFT will return nan.

class `freud.pmft.PMFT12`

Bases: `freud.pmft._PMFT`

Computes the PMFT [vAKA+14][vAAS+13] in a 2D system described by r, θ_1, θ_2 .

Note: **2D:** `freud.pmft.PMFT12` is only defined for 2D systems. The points must be passed in as $[x, y, 0]$.

Parameters

- **r_max** (*float*) – Maximum distance at which to compute the PMFT.
- **bins** (*unsigned int or sequence of length 3*) – If an unsigned int, the number of bins in r, θ_1 , and θ_2 . If a sequence of three integers, interpreted as (num_bins_r, num_bins_t1, num_bins_t2).

bin_centers

The centers of each bin in the histogram (has the same shape as the histogram itself).

Type `numpy.ndarray`

property bin_counts

The bin counts in the histogram.

Type `numpy.ndarray`

bin_edges

The edges of each bin in the histogram (is one element larger in each dimension than the histogram because each bin has a lower and upper bound).

Type `numpy.ndarray`

bounds

A list of tuples indicating upper and lower bounds of each axis of the histogram.

Type `list (tuple)`

property box

The box object used in the last computation.

Type `freud.box.Box`

compute

Calculates the PMFT.

Parameters

- **system** – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.
- **orientations** ($(N_{\text{points}}, 4)$ or $(N_{\text{points}},)$ `numpy.ndarray`) – Orientations associated with system points that are used to calculate bonds. If the array is one-dimensional, the values are treated as angles in radians corresponding to **counterclockwise** rotations about the z axis.
- **query_points** ($(N_{\text{query_points}}, 3)$ `numpy.ndarray`, optional) – Query points used to calculate the PMFT. Uses the system's points if None (Default value = None).
- **query_orientations** ($(N_{\text{query_points}}, 4)$ `numpy.ndarray`, optional) – Query orientations associated with query points that are used to calculate bonds. If the array is one-dimensional, the values are treated as angles in radians corresponding to **counterclockwise** rotations about the z axis. Uses `orientations` if None. (Default value = None).
- **neighbors** (`freud.locality.NeighborList` or dict, optional) – Either a `NeighborList` of neighbor pairs to use in the calculation, or a dictionary of `query arguments` (Default value: None).
- **reset** (`bool`) – Whether to erase the previously computed values before adding the new computation; if False, will accumulate data (Default value: True).

default_query_args

The default query arguments are `{'mode': 'ball', 'r_max': self.r_max}`.

nbins

The number of bins in each dimension of the histogram

Type `list`

property pmft

The discrete potential of mean force and torque.

Type `np.ndarray`

class freud.pmft.PMFTXY

Bases: `freud.pmft._PMFT`

Computes the PMFT [vAKA+14][vAAS+13] in coordinates x, y .

Since there are 3 degrees of translational and rotational freedom in 2 dimensions, this class is implicitly integrating out one of them. Specifically, by comparison to `PMFTXYT` we see that the missing dimension is the relative orientation of the second particle. Note that this degree of freedom is still accounted for in the Jacobian of this calculation.

Note: 2D: `freud.pmft.PMFTXY` is only defined for 2D systems. The points must be passed in as `[x, y, 0]`.

Parameters

- **x_max** (`float`) – Maximum x distance at which to compute the PMFT.
- **y_max** (`float`) – Maximum y distance at which to compute the PMFT.
- **bins** (`unsigned int` or `sequence of length 2`) – If an unsigned int, the number of bins in x and y . If a sequence of two integers, interpreted as `(num_bins_x, num_bins_y)`.

bin_centers

The centers of each bin in the histogram (has the same shape as the histogram itself).

Type `numpy.ndarray`

property bin_counts

The bin counts in the histogram.

Type `numpy.ndarray`

bin_edges

The edges of each bin in the histogram (is one element larger in each dimension than the histogram because each bin has a lower and upper bound).

Type `numpy.ndarray`

bounds

A list of tuples indicating upper and lower bounds of each axis of the histogram.

Type `list (tuple)`

property box

The box object used in the last computation.

Type `freud.box.Box`

compute

Calculates the PMFT.

Note: The orientations of the system points are irrelevant for this calculation because that dimension is integrated out. The provided `query_orientations` are therefore always associated with `query_points` (which are equal to the system points if no `query_points` are explicitly provided).

Parameters

- **system** – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.
- **query_orientations** ($(N_{\text{query_points}}, 4)$ or $(N_{\text{query_points}}, \text{numpy.ndarray})$) – Query orientations associated with query points that are used to calculate bonds. If the array is one-dimensional, the values are treated as angles in radians corresponding to **counterclockwise** rotations about the z axis.
- **query_points** ($(N_{\text{query_points}}, 3)$ `numpy.ndarray`, optional) – Query points used to calculate the PMFT. Uses the system's points if None (Default value = None).
- **neighbors** (`freud.locality.NeighborList` or dict, optional) – Either a `NeighborList` of neighbor pairs to use in the calculation, or a dictionary of `query_arguments` (Default value: None).
- **reset** (`bool`) – Whether to erase the previously computed values before adding the new computation; if False, will accumulate data (Default value: True).

default_query_args

The default query arguments are `{ 'mode': 'ball', 'r_max': self.r_max }`.

nbins

The number of bins in each dimension of the histogram

Type `list`

plot

Plot PMFTXY.

Parameters **ax** (`matplotlib.axes.Axes`, optional) – Axis to plot on. If `None`, make a new figure and axis. (Default value = `None`)

Returns Axis with the plot.

Return type (`matplotlib.axes.Axes`)

property pmft

The discrete potential of mean force and torque.

Type `np.ndarray`

class `freud.pmft.PMFTXYT`

Bases: `freud.pmft._PMFT`

Computes the PMFT [vAKA+14][vAAS+13] for systems described by coordinates x, y, θ .

Note: **2D:** `freud.pmft.PMFTXYT` is only defined for 2D systems. The points must be passed in as `[x, y, 0]`.

Parameters

- **x_max** (*float*) – Maximum x distance at which to compute the PMFT.
- **y_max** (*float*) – Maximum y distance at which to compute the PMFT.
- **bins** (*unsigned int or sequence of length 3*) – If an unsigned int, the number of bins in x , y , and t . If a sequence of three integers, interpreted as (`num_bins_x`, `num_bins_y`, `num_bins_t`).

bin_centers

The centers of each bin in the histogram (has the same shape as the histogram itself).

Type `numpy.ndarray`

property bin_counts

The bin counts in the histogram.

Type `numpy.ndarray`

bin_edges

The edges of each bin in the histogram (is one element larger in each dimension than the histogram because each bin has a lower and upper bound).

Type `numpy.ndarray`

bounds

A list of tuples indicating upper and lower bounds of each axis of the histogram.

Type `list (tuple)`

property box

The box object used in the last computation.

Type `freud.box.Box`

compute

Calculates the PMFT.

Parameters

- **system** – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.
- **orientations** ($(N_{\text{points}}, 4)$ or $(N_{\text{points}},)$ `numpy.ndarray`) – Orientations associated with system points that are used to calculate bonds. If the array is one-dimensional, the values are treated as angles in radians corresponding to **counterclockwise** rotations about the z axis.
- **query_points** ($(N_{\text{query_points}}, 3)$ `numpy.ndarray`, optional) – Query points used to calculate the PMFT. Uses the system's points if None (Default value = None).
- **query_orientations** ($(N_{\text{query_points}}, 4)$ `numpy.ndarray`, optional) – Query orientations associated with query points that are used to calculate bonds. If the array is one-dimensional, the values are treated as angles in radians corresponding to **counterclockwise** rotations about the z axis. Uses **orientations** if None. (Default value = None).
- **neighbors** (`freud.locality.NeighborList` or dict, optional) – Either a `NeighborList` of neighbor pairs to use in the calculation, or a dictionary of **query arguments** (Default value: None).
- **reset** (`bool`) – Whether to erase the previously computed values before adding the new computation; if False, will accumulate data (Default value: True).

default_query_args

The default query arguments are `{ 'mode': 'ball', 'r_max': self.r_max }`.

nbins

The number of bins in each dimension of the histogram

Type `list`

property pmft

The discrete potential of mean force and torque.

Type `np.ndarray`

class freud.pmft.PMFTXYZ

Bases: `freud.pmft._PMFT`

Computes the PMFT [vAKA+14][vAAS+13] in coordinates x, y, z .

Since there are 6 degrees of translational and rotational freedom in 3 dimensions, this class is implicitly integrating out three of them. In particular, we are disregarding the orientational degrees of freedom in the system. The simplest parameterization of these degrees is using Euler angles. The total volume of orientations that are implicitly integrated out by this calculation can be computed by an explicit integral over the Euler angles:

$$\int_0^{2\pi} \int_0^\pi \int_0^{2\pi} \sin \theta d\phi d\theta d\psi = 8\pi^2$$

For more information on this calculation, see [GMS63] (the equation is also reproduced without proof at https://en.wikipedia.org/wiki/3D_rotation_group#Spherical_harmonics). This prefactor of $8\pi^2$ is accounted for in the Jacobian used to compute the `PMFTXYZ`.

Parameters

- **x_max** (`float`) – Maximum x distance at which to compute the PMFT.
- **y_max** (`float`) – Maximum y distance at which to compute the PMFT.
- **z_max** (`float`) – Maximum z distance at which to compute the PMFT.

- **bins** (*unsigned int or sequence of length 3*) – If an unsigned int, the number of bins in *x*, *y*, and *z*. If a sequence of three integers, interpreted as (*num_bins_x*, *num_bins_y*, *num_bins_z*).
- **shiftvec** (*list*) – Vector pointing from [0, 0, 0] to the center of the PMFT.

bin_centers

The centers of each bin in the histogram (has the same shape as the histogram itself).

Type `numpy.ndarray`

property bin_counts

The bin counts in the histogram.

Type `numpy.ndarray`

bin_edges

The edges of each bin in the histogram (is one element larger in each dimension than the histogram because each bin has a lower and upper bound).

Type `numpy.ndarray`

bounds

A list of tuples indicating upper and lower bounds of each axis of the histogram.

Type `list (tuple)`

property box

The box object used in the last computation.

Type `freud.box.Box`

compute

Calculates the PMFT.

Note: The orientations of the system points are irrelevant for this calculation because that dimension is integrated out. The provided `query_orientations` are therefore always associated with `query_points` (which are equal to the system points if no `query_points` are explicitly provided).

Parameters

- **system** – Any object that is a valid argument to `freud.locality.NeighborQuery.from_system`.
- **query_orientations** ($(N_{\text{points}}, 4)$ `numpy.ndarray`) – Query orientations associated with query points that are used to calculate bonds.
- **query_points** ($(N_{\text{query_points}}, 3)$ `numpy.ndarray`, optional) – Query points used to calculate the PMFT. Uses the system's points if None (Default value = None).
- **equiv_orientations** ($(N_{\text{faces}}, 4)$ `numpy.ndarray`, optional) – Orientations to be treated as equivalent to account for symmetry of the points. For instance, if the `query_points` are rectangular prisms with the long axis corresponding to the x-axis, then a point at (1, 0, 0) and a point at (-1, 0, 0) are symmetrically equivalent and can be counted towards both the positive and negative bins. If not supplied by user or None, a unit quaternion will be used (Default value = None).
- **neighbors** (`freud.locality.NeighborList` or dict, optional) – Either a `NeighborList` of neighbor pairs to use in the calculation, or a dictionary of `query arguments` (Default value: None).

- **reset** (*bool*) – Whether to erase the previously computed values before adding the new computation; if False, will accumulate data (Default value: True).

default_query_args

The default query arguments are {'mode': 'ball', 'r_max': self.r_max}.

nbins

The number of bins in each dimension of the histogram

Type `list`

property pmft

The discrete potential of mean force and torque.

Type `np.ndarray`

7.20 Development Guide

Contributions to **freud** are highly encouraged. The pages below offer information about how the project is structured, the goals of the **freud** library, and how to contribute new modules.

7.20.1 Design Principles

Vision

The **freud** library is designed to be a powerful and flexible library for the analysis of simulation output. To support a variety of analysis routines, **freud** places few restrictions on its components. The primary requirement for an analysis routine in **freud** is that it should be substantially computationally intensive so as to require coding up in C++: **all freud code should be composed of fast C++ routines operating on systems of particles in periodic boxes.** To remain easy-to-use, all C++ modules should be wrapped in Python code so they can be easily accessed from Python scripts or through a Python interpreter.

In order to achieve this goal, **freud** takes the following viewpoints:

- **freud** works directly with *NumPy* <<http://www.numpy.org/>> arrays to retain maximum flexibility. Integrations with other tools should be performed via the common data representations of NumPy arrays.
- For ease of maintenance, **freud** uses Git for version control; GitHub for code hosting and issue tracking; and the PEP 8 standard for code, stressing explicitly written code which is easy to read.
- To ensure correctness, **freud** employs unit testing using the Python unittest framework. In addition, **freud** utilizes [CircleCI](#) for continuous integration to ensure that all of its code works correctly and that any changes or new features do not break existing functionality.

Language choices

The **freud** library is written in two languages: Python and C++. C++ allows for powerful, fast code execution while Python allows for easy, flexible use. Intel Threading Building Blocks parallelism provides further power to C++ code. The C++ code is wrapped with Cython, allowing for user interaction in Python. NumPy provides the basic data structures in **freud**, which are commonly used in other Python plotting libraries and packages.

Unit Tests

All modules should include a set of unit tests which test the correct behavior of the module. These tests should be simple and short, testing a single function each, and completing as quickly as possible (ideally < 10 sec, but times up to a minute are acceptable if justified).

Benchmarks

Modules can be benchmarked in the following way. The following code is an example benchmark for the `freud.density.RDF` module.

```
1 import numpy as np
2 import freud
3 from benchmark import Benchmark
4 from benchmarker import run_benchmarks
5
6
7 class BenchmarkDensityRDF(Benchmark):
8     def __init__(self, r_max, bins, r_min):
9         self.r_max = r_max
10        self.bins = bins
11        self.r_min = r_min
12
13    def bench_setup(self, N):
14        self.box_size = self.r_max*3.1
15        np.random.seed(0)
16        self.points = np.random.random_sample((N, 3)).astype(np.float32) \
17            * self.box_size - self.box_size/2
18        self.rdf = freud.density.RDF(self.bins, self.r_max, r_min=self.r_min)
19        self.box = freud.box.Box.cube(self.box_size)
20
21    def bench_run(self, N):
22        self.rdf.compute((self.box, self.points), reset=False)
23        self.rdf.compute((self.box, self.points))
24
25
26 def run():
27     Ns = [1000, 10000]
28     r_max = 10.0
29     bins = 10
30     r_min = 0
31     number = 100
32     name = 'freud.density.RDF'
33     classobj = BenchmarkDensityRDF
34
35     return run_benchmarks(name, Ns, number, classobj,
36                           r_max=r_max, bins=bins, r_min=r_min)
37
38
39 if __name__ == '__main__':
40     run()
```

in a file `benchmark_density_RDF.py` in the `benchmarks` directory. More examples can be found in the `benchmarks` directory. The runtime of `BenchmarkDensityRDF.bench_run` will be timed for `number` of times on the input sizes of `Ns`. Its runtime with respect to the number of threads will also be measured. Benchmarks are run as a part of continuous integration, with performance comparisons between the current commit and the master branch.

Make Execution Explicit

While it is tempting to make your code do things “automatically”, such as have a calculate method find all `_calc` methods in a class, call them, and add their returns to a dictionary to return to the user, it is preferred in **freud** to execute code explicitly. This helps avoid issues with debugging and undocumented behavior:

```
# this is bad
class SomeFreudClass(object):
    def __init__(self, **kwargs):
        for key in kwargs.keys():
            setattr(self, key, kwargs[key])

# this is good
class SomeOtherFreudClass(object):
    def __init__(self, x=None, y=None):
        self.x = x
        self.y = y
```

Code Duplication

When possible, code should not be duplicated. However, being explicit is more important. In **freud** this translates to many of the inner loops of functions being very similar:

```
// somewhere deep in function_a
for (int i = 0; i < n; i++)
{
    vec3[float] pos_i = position[i];
    for (int j = 0; j < n; j++)
    {
        pos_j = position[j];
        // more calls here
    }
}

// somewhere deep in function_b
for (int i = 0; i < n; i++)
{
    vec3[float] pos_i = position[i];
    for (int j = 0; j < n; j++)
    {
        pos_j = position[j];
        // more calls here
    }
}
```

While it *might* be possible to figure out a way to create a base C++ class all such classes inherit from, run through positions, call a calculation, and return, this would be rather complicated. Additionally, any changes to the internals of the code, and may result in performance penalties, difficulty in debugging, etc. As before, being explicit is better.

However, if you have a class which has a number of methods, each of which requires the calling of a function, this function should be written as its own method (instead of being copy-pasted into each method) as is typical in object-oriented programming.

Python vs. Cython vs. C++

The **freud** library is meant to leverage the power of C++ code imbued with parallel processing power from TBB with the ease of writing Python code. The bulk of your calculations should take place in C++, as shown in the snippet below:

```
# this is bad
def badHeavyLiftingInPython(positions):
    # check that positions are fine
    for i, pos_i in enumerate(positions):
        for j, pos_j in enumerate(positions):
            if i != j:
                r_ij = pos_j - pos_i
                # ...
                computed_array[i] += some_val
    return computed_array

# this is good
def goodHeavyLiftingInCplusplus(positions):
    # check that positions are fine
    cplusplus_heavy_function(computed_array, positions, len(pos))
    return computed_array
```

In the C++ code, implement the heavy lifting function called above from Python:

```
void cplusplus_heavy_function(float* computed_array,
                             float* positions,
                             int n)
{
    for (int i = 0; i < n; i++)
    {
        for (int j = 0; j < n; j++)
        {
            if (i != j)
            {
                r_ij = pos_j - pos_i;
                // ...
                computed_array[i] += some_val;
            }
        }
    }
}
```

Some functions may be necessary to write at the Python level due to a Python library not having an equivalent C++ library, complexity of coding, etc. In this case, the code should be written in Cython and a *reasonable* attempt to optimize the code should be made.

7.20.2 Contributing to freud

Code Conventions

Python

Python (and Cython) code in **freud** should follow [PEP 8](#).

During continuous integration (CI), all Python and Cython code in **freud** is tested with [flake8](#) to ensure PEP 8 compliance. It is strongly recommended to [set up a pre-commit hook](#) to ensure code is compliant before pushing to the repository:

```
flake8 --install-hook git
git config --bool flake8.strict true
```

Documentation is written in reStructuredText and generated using [Sphinx](#). It should be written according to the [Google Python Style Guide](#). A few specific notes:

- The shapes of NumPy arrays should be documented as part of the type in the following manner:

```
points ((:math:`N_{\text{points}}`, 3) :class:`numpy.ndarray`):
```

- Optional arguments should be documented as such within the type after the actual type, and the default value should be included within the description:

```
box (:class:`freud.box.Box`, optional): Simulation box (Default value = None).
```

C++

C++ code should follow the result of running `clang-format-6.0` with the style specified in the file `.clang-format`. Please refer to [Clang Format 6](#) for details.

When in doubt, run `clang-format -style=file FILE_WITH_YOUR_CODE` in the top directory of the **freud** repository. If installing `clang-format` is not a viable option, the `check-style` step of continuous integration (CI) contains the information on the correctness of the style.

Code Organization

The code in **freud** is a mix of Python, Cython, and C++. From a user's perspective, methods in **freud** correspond to Compute classes, which are contained in Python modules that group methods by topic. To keep modules well-organized, **freud** implements the following structure:

- All C++ code is stored in the `cpp` folder at the root of the repository, with subdirectories corresponding to each module (e.g. `cpp/locality`).
- Python code is stored in the `freud` folder at the root of the repository.
- C++ code is exposed to Python using Cython code contained in `pxd` files with the following convention: `freud/_MODULENAME.pxd` (note the preceding underscore).
- The core Cython code for modules is contained in `freud/MODULENAME.pyx` (no underscore).
- Generated Cython C++ code (e.g. `freud/MODULENAME.cpp`) should not be committed during development. These files are updated only at release time.

- If a Cython module contains code that must be imported into other Cython modules (such as the `freud.box.Box` class), the `pyx` file must be accompanied by a `pxd` file with the same name: `freud/MODULENAME.pxd` (distinguished from `pxd` files used to expose C++ code by the lack of a preceding underscore). For more information on how `pxd` files work, see the [Cython documentation](#).
- All tests in **freud** are based on the Python standard `unittest` library and are contained in the `tests` folder. Test files are named by the convention `tests/test_MODULENAME_CLASSNAME.py`.
- Benchmarks for **freud** are contained in the `benchmarks` directory and are named analogously to tests: `benchmarks/benchmark_MODULENAME_CLASSNAME.py`.

Benchmarks

Benchmarking in **freud** is performed by running the `benchmarks/benchmark.py` script. This script finds all benchmarks (using the above naming convention) and attempts to run them. Each benchmark is defined by extending the `Benchmark` class defined in `benchmarks/benchmark.py`, which provides the standard benchmarking utilities used in **freud**. Subclasses just need to define a few methods to parameterize the benchmark, construct the **freud** object being benchmarked, and then call the relevant compute method. Rather than describing this process in detail, we consider the benchmark for the `freud.density.RDF` module as an example.

```

1 import numpy as np
2 import freud
3 from benchmark import Benchmark
4 from benchmarker import run_benchmarks
5
6
7 class BenchmarkDensityRDF(Benchmark):
8     def __init__(self, r_max, bins, r_min):
9         self.r_max = r_max
10        self.bins = bins
11        self.r_min = r_min
12
13    def bench_setup(self, N):
14        self.box_size = self.r_max*3.1
15        np.random.seed(0)
16        self.points = np.random.random_sample((N, 3)).astype(np.float32) \
17            * self.box_size - self.box_size/2
18        self.rdf = freud.density.RDF(self.bins, self.r_max, r_min=self.r_min)
19        self.box = freud.box.Box.cube(self.box_size)
20
21    def bench_run(self, N):
22        self.rdf.compute((self.box, self.points), reset=False)
23        self.rdf.compute((self.box, self.points))
24
25
26 def run():
27     Ns = [1000, 10000]
28     r_max = 10.0
29     bins = 10
30     r_min = 0
31     number = 100
32     name = 'freud.density.RDF'
33     classobj = BenchmarkDensityRDF
34
35     return run_benchmarks(name, Ns, number, classobj,
36                           r_max=r_max, bins=bins, r_min=r_min)

```

(continues on next page)

(continued from previous page)

```

37
38
39 if __name__ == '__main__':
40     run()

```

The `__init__` method defines basic parameters of the run, the `bench_setup` method is called to build up the *RDF* object, and the `bench_run` is used to time and call `compute`. More examples can be found in the `benchmarks` directory. The runtime of `BenchmarkDensityRDF.bench_run` will be timed for number of times on the input sizes of `Ns`. Its runtime with respect to the number of threads will also be measured. Benchmarks are run as a part of continuous integration, with performance comparisons between the current commit and the master branch.

Steps for Adding New Code

Once you've determined to add new code to **freud**, the first step is to create a new branch off of `master`. The process of adding code differs based on whether or not you are editing an existing module in **freud**. Adding new methods to an existing module in **freud** requires creating the new C++ files in the `cpp` directory, modifying the corresponding `MODULENAME.pxd` file in the `freud` directory, and creating a wrapper class in `freud/MODULENAME.pyx`. If the new methods belong in a new module, you must create the corresponding `pxd` and `pyx` files accordingly. In addition, you will need to import the new module in `freud/__init__.py` by adding `from . import MODULENAME` so that your module is imported by default.

Once the code is added, appropriate tests should be added to the `tests` folder. Test files are named by the convention `tests/test_MODULENAME_CLASSNAME.py`. The final step is updating documentation, which is contained in `rst` files named with the convention `doc/source/modules/MODULENAME.rst`. If you have added a class to an existing module, all you have to do is add that same class to the `autosummary` section of the corresponding `rst` file. If you have created a new module, you will have to create the corresponding `rst` file with the summary section listing classes and functions in the module followed by a more detailed description of all classes. All classes and functions should be documented inline in the code, which allows automatic generation of the detailed section using the `automodule` directive (see any of the module `rst` files for an example). Finally, the new file needs to be added to `doc/source/index.rst` in the API section.

7.20.3 Special Topics

Some of the most central components have a high level of abstraction. This abstraction has multiple advantages: it dramatically simplifies the process of implementing new code, it reduces duplication throughout the code base, and ensures that bug fixes and optimization can occur along a single path for the entire module. However, this abstraction comes at the cost of significant complexity. This documentation should help orient developers familiarizing themselves with these topics by providing high-level overviews of how these parts of the code are structured and how the pieces fit together.

Memory Management

Memory handling in **freud** is a somewhat intricate topic. Most **freud** developers do not need to be aware of such details; however, certain practices must be followed to ensure that the expected behavior is achieved. This page provides an overview of how data should be handled in **freud** and how module developers should use **freud**'s core classes to ensure proper memory management. A thorough description of the process is also provided for developers who need to understand the internal logic for further development.

Note: This page specifically deals with modules primarily written in C++. These concepts do not apply to pure Python/Cython modules.

Problem Statement

The standard structure for **freud** modules involves a core implementation in a C++ class wrapped in a Cython class that owns a pointer to the C++ object. Python `compute` methods call through to C++ `compute` methods, which perform the calculation and populate class member arrays that are then accessed via properties of the owning Cython class. These classes are designed to be reusable, i.e. `compute` may be called many times on the same object with different data, and the accessed properties will return the most current data. Users have a reasonable expectation that if the accessed property is saved to another variable it will remain unchanged by future calls to `compute` or if the originating C++ object is destructed, but a naive implementation that ensures this invariant would involve reallocating memory on every call to `compute`, an unnecessarily expensive operation. Ultimately, what we want is a method that performs the minimal number of memory allocations while allowing users to operate transparently on outputs without worrying about whether the data will be invalidated by future operations.

ManagedArray

The **freud** `ManagedArray` template class provides a solution to this problem for arbitrary types of numerical data. Proper usage of the class can be summarized by the following steps:

1. Declaring `ManagedArray` class members in C++.
2. Calling the `prepare` method in every `compute`.
3. Making the array accessible via a getter method that **returns a const reference**.
4. Calling `make_managed_numpy_array` in Cython and returning the output as a property.

Plenty of examples of following this pattern can be found throughout the codebase, but for clarity we provide a complete description with examples below. If you are interested in more details on the internals of `ManagedArray` and how it actually works, you can skip to [Explaining ManagedArrays](#).

Using ManagedArrays

We'll use `freud.cluster.Cluster` to illustrate how the four steps above may be implemented. This class takes in a set of points and assigns each of them to clusters, which are store in the C++ array `m_cluster_idx`.

Step 1 is simple: we note that `m_cluster_idx` is a member variable of type `ManagedArray<unsigned int>`. For step 2, we look at the first few lines of `Cluster::compute`, where we see a call to `m_cluster_idx.prepare`. This method encapsulates the core logic of `ManagedArray`, namely the intelligent reallocation of memory whenever other code is still accessing it. This means that, if a user saves the corresponding Python property `freud.cluster.Cluster.cluster_idx` to a local variable in a script and then calls `freud.cluster.Cluster.compute`, the saved variable will still reference the original data, and the new data may be accessed again using `freud.cluster.Cluster.cluster_idx`.

Step 3 for the cluster indices is accomplished in the following code block:

```
#!/ Get a reference to the cluster ids.
const util::ManagedArray<unsigned int> &getClusterIdx() const
{
    return m_cluster_idx;
}
```

The return type of this method is crucial: all such methods must return const references to the members.

The final step is accomplished on the Cython side. Here is how the cluster indices are exposed in `freud.cluster.Cluster`:

```
@_Compute._computed_property
def cluster_idx(self):
    """math: `N_{points}` :class: `numpy.ndarray`: The cluster index for
    each point."""
    return freud.util.make_managed_numpy_array(
        &self.thisptr.getClusterIdx(),
        freud.util.arr_type_t.UNSIGNED_INT)
```

Essentially all the core logic is abstracted away from the user through the `freud.data.make_managed_numpy_array()`, which creates a NumPy array that is a view on an existing `ManagedArray`. This NumPy array will, in effect, take ownership of the data in the event that the user keeps a reference to it and requests a recomputation. Note the signature of this function: the first argument must be a **pointer to the `ManagedArray`** (which is why we had to return it by reference), and the second argument indicates the type of the data (the possible types can be found in `freud/util.pxd`). There is one other point to note that is not covered by the above example; if the template type of the `ManagedArray` is not a scalar, you also need to provide a third argument indicating the size of this vector. The most common use-case is for methods that return an object of type `ManagedArray<vec3<float>>`: in this case, we would call `make_managed_numpy_array(&GETTER_FUNC, freud.util.arr_type_t.FLOAT, 3)`.

Indexing ManagedArrays

With respect to indexing, the `ManagedArray` class behaves like any standard array-like container and can be accessed using e.g. `m_cluster_idx[index]`. In addition, because many calculations in **freud** output multidimensional information, `ManagedArray` also supports multidimensional indexing using `operator()`. For example, setting the element at second row and third column of a 2D `ManagedArray` `array` to one can be done using `array(1, 2) = 1` (indices beginning from 0). Therefore, `ManagedArray` objects can be used easily inside the core C++ calculations in **freud**.

Explaining ManagedArrays

We now provide a more detailed accounting of how the `ManagedArray` class actually works. Consider the following block of code:

```
rdf = freud.density.RDF(bins=100, r_max=3)

rdf.compute(system=(box1, points1))
rdf1 = rdf.rdf

rdf2.compute(system=(box2, points2))
rdf2 = rdf.rdf
```

We require that `rdf1` and `rdf2` be distinct arrays that are only equal if the results of computing the RDF are actually equivalent for the two systems, and we want to achieve this with the minimal number of memory allocations. In this case, that means there are two required allocations; returning copies would double that.

To achieve this goal, `ManagedArray` objects store a pointer to a pointer. Multiple `ManagedArray` objects can point to the same data array, and the pointers are all shared pointers to automate deletion of arrays when no references remain. The key using the class properly is the `prepare` method, which checks the reference count to determine whether it's safe to simply zero out the existing memory or if it needs to allocate a new array. In the above example, when `compute` is called a second time the `rdf1` object in Python still refers to the computed data, so `prepare` will detect that there are multiple (two) shared pointers pointing to the data and choose to reallocate the class's `ManagedArray` storing the RDF. By calling `prepare` at the top of every `compute` method, developers

ensure that the array used for the rest of the method has been properly zeroed out, and they do not need to worry about whether reallocation is needed (including cases where array sizes change).

To ensure that all references to data are properly handled, some additional logic is required on the Python side as well. The Cython `make_managed_numpy_array` instantiates a `_ManagedArrayContainer` class, which is essentially just a container for a `ManagedArray` that points to the same data as the `ManagedArray` provided as an argument to the function. This link is what increments the underlying shared pointer reference counter. The `make_managed_numpy_array` uses the fact that a `_ManagedArrayContainer` can be transparently converted to a NumPy array that points to the container; as a result, no data copies are made, but all NumPy arrays effectively share ownership of the data along with the originating C++ class. If any such arrays remain in scope for future calls to `compute`, `prepare` will recognize this and reallocate memory as needed.

Neighbor Finding

Neighbor finding is central to many methods in **freud**. The purpose of this page is to introduce the various C++ classes and functions involved in the neighbor finding process. This page focuses on aspects of the neighbor finding utilities in **freud** that are important for developers. As such, it assumes knowledge on the level of *Finding Neighbors* and *Pair Computations*, so please familiarize yourself with the contents of those pages before proceeding.

There are two primary use-cases for the neighbor finding code in **freud**. One is to directly expose this functionality to the user, via the *NeighborQuery* abstract class and its subclasses. The second is to enable looping over nearest neighbors (as defined by arbitrary query arguments or a precomputed *NeighborList*) inside of compute methods defined in C++. To support both of these use-cases, **freud** defines how to find neighbors inside iterator classes, which can be naturally looped over in either case. In this page, we first discuss these iterators and how they are structured with respect to the `locality::NeighborQuery` C++ class. We then discuss the utility functions built around this class to enable easier C++ computations, at which point we also discuss how *NeighborList* objects fit into this framework.

Per-Point Iterators and the NeighborQuery class

The lowest-level unit of the neighbor finding infrastructure in **freud** is the `locality::NeighborPerPointIterator`. This class defines an abstract interface for all neighbor iteration in **freud**, an interface essentially composed of the `next` and `end` methods. Given an instance of this class, these two methods provide the means for client code to get the next neighbor in the iteration until there are no further neighbors. Calls to `next` produces instances of `locality::NeighborBond`, a simple data class that contains the core information defining a bond (a pair of points, a distance, and any useful ancillary information).

The rationale for making per-point iteration the central element is twofold. The first is conceptual: all logic for finding neighbors is naturally reducible to a set of conditions on the neighbors of each query point. The second is more practical: since finding neighbors for each point must be sequential in many cases (such as nearest neighbor queries), per-point iteration is the smallest logical unit that can be parallelized.

Instances of `locality::NeighborPerPointIterator` should not be constructed directly; instead, they should be constructed via the `locality::NeighborQuery::querySingle` method. The `locality::NeighborQuery` class is an abstract data type that defines an interface for any method implemented for finding neighbors. All subclasses must implement the `querySingle` method, which should return a subclass of `locality::NeighborPerPointIterator`. For instance, the `locality::AABBQuery` class implements `querySingle`, which returns an instance of the `locality::AABBIterator` subclass. In general, different `NeighborQuery` subclasses will need to implement separate per-point iterators for each query mode; for `locality::AABBQuery`, these are the `locality::AABBQueryIterator` and the `locality::AABBQueryBallIterator`, which encode the logic for nearest neighbor and ball queries, respectively.

Although the `querySingle` method is what subclasses should implement, the primary interface to `NeighborQuery` subclasses is the `query` method, which accepts an arbitrary set of query points

and query arguments and simply generates a `locality::NeighborQueryIterator` object. The `locality::NeighborQueryIterator` class is an intermediary that allows lazy generation of neighbors. It essentially functions as the container for a set of points, query points, and query arguments; once iteration of this object begins, it produces `NeighborPerPointIterator` objects on demand. This mode of operation also enables the generator approach to looping over neighbors in Python, since iterating in Python corresponds directly to calling `next` on the underlying `NeighborQueryIterator`.

There is one conceptual complexity associated with this class that is important to understand. Since all of the logic for finding neighbors is contained in the per-point iterator classes, the `NeighborQueryIterator` actually retains a reference to the constructing `NeighborQuery` object so that it can call `querySingle` for each point. This bidirectionally linked structure enables encapsulation of the neighbor finding logic while also supporting easily parallelization (via parallel calls to `querySingle`). Additionally, this structure makes it natural to generate `NeighborList` objects.

NeighborLists

The `NeighborList` class represents a static list of neighbor pairs. The results of any query can be converted to a `NeighborList` by calling the `toNeighborList` method of the `NeighborQueryIterator`, another reason why the iterator class logic is separated from the `NeighborQuery` object: it allows generation of a `NeighborList` from – and more generally, independent operation on – the result of a query. The `NeighborList` is simply implemented as a collection of raw arrays, one of which holds pairs of neighbors. The others hold any additional information associated with each bond, such as distances or weights.

By definition, the bonds in a `NeighborList` are stored in the form `(query_point, point)` (i.e. this is how the underlying array is indexed) and ordered by `query_point`. This ordering makes the structure amenable to a fast binary search algorithm. Looping over neighbors of a given `query_point` is then simply a matter of finding the first index in the list where that `query_point` appears and then iterating until the `query_point` index in the list no longer matches the one under consideration.

Computing With Neighbors

One of the most common operations in **freud** is performing some computation over all neighbor-bonds in the system. Users have multiple ways of specifying neighbors (using query arguments or by a `NeighborList`), so **freud** provides some utility functions to abstract the process of looping over neighbors. These functions are defined in `locality/NeighborComputeFunctional.h`; the two most important ones are `loopOverNeighbors` and `loopOverNeighborsIterator`. Compute functions that perform neighbor computations typically accept a `NeighborQuery`, a `QueryArgs`, and a `NeighborList` object. These objects can then be passed to either of the utility functions, which loop over the `NeighborList` if it was provided (if no `NeighborList` is provided by the Python user, a `NULL` pointer is passed through), and if not, perform a query on the `NeighborQuery` object using the provided `QueryArgs` to generate the required neighbors. The actual computation should be encapsulated as a lambda function that is passed as an argument to these utilities.

The distinction between the two utility functions lies in the signature of the accepted lambda functions, which enables a slightly different form of computation. The default `loopOverNeighbors` function does exactly what is described above, namely it calls the provided compute function for every single bond. However, some computations require some additional code to be executed for each `query_point`, such as some sort of normalization. To enable this mode of operation, the `loopOverNeighborsIterator` method instead requires a lambda function that accepts two arguments, the `query_point` index and a `NeighborPerPointIterator`. This way, the client code can loop over the neighbors of a given `query_point` and perform the needed computation, then execute additional code (which may optionally depend on the index of the `query_point`, e.g. to update a specific array index).

Default Systems

There is one important implementation detail to note. The user is permitted to simply provide a set of points rather than a `NeighborQuery` object on the Python side (i.e. any valid argument to `from_system()`), but we need a natural way to mirror this in C++, ideally without too many method overloads. To implement this, we provide the `RawPoints` C++ class and its Python `_RawPoints` mirror, which is essentially a plain container for a box and a set of query points. This object inherits from `NeighborQuery`, allowing it to be passed directly into the C++ compute methods.

However, neighbor computations still need to know how to find neighbors. In this case, they must construct a `NeighborQuery` object capable of neighbor finding and then use the provided query arguments to find neighbors. To enable this calculation, the `RawPoints` class implements a query method that simply constructs an `AABBQuery` internally and queries it for neighbors.

Default NeighborLists

Some compute methods are actually computations that produce quantities per bond. One example is the `SolidLiquid` order parameter, which computes an order parameter value for each bond. The `NeighborComputeFunctional.h` file implements a `makeDefaultNList` function that supports this calculation by creating a `NeighborList` object from whatever inputs are provided on demand.

Histograms

Histograms are a common type of calculation implemented in **freud** because custom histograms are hard to compute efficiently in pure Python. The C++ `Histogram` class support weighted N-dimensional histograms with different spacings in each dimension. The key to this flexibility is the `Axis` class, which defines the range spacing along a single axis; an N-dimensional `Histogram` is composed of a sequence of N `Axis` objects. Binning values into the histogram is performed by binning along each axis. The standard `RegularAxis` subclass of `Axis` defines an evenly spaced axis with bin centers defined as the center of each bin; additional subclasses may be defined to add different spacing if desired.

Multithreading is achieved through the `ThreadLocalHistogram` class, which is a simple wrapper around the `Histogram` that creates an equivalent histogram on each thread. The standard pattern for parallel histogramming is to generate a `ThreadLocalHistogram` and add data into it, then call the `Histogram::reduceOverThreads` method to accumulate these data into a single histogram. In case any additional post-processing is required per bin, it can also be executed in parallel by providing it as a lambda function to `Histogram::reduceOverThreadsPerBin`.

Computing with Histograms

The `Histogram` class is designed as a data structure for the histogram. Most histogram computations in **freud** involve standard neighbor finding to get bonds, followed by binning some function of these bonds into a histogram. Examples include RDFs (binning bond distances), PMFTs (binning bonds by the different vector components of the bond), and bond order diagrams (binning bond angles). An important distinction between histogram computations and most others is that histograms naturally support an accumulation of information over multiple frames of data, an operation that is ill-defined for many other computations. As a result, histogram computations also need to implement some boilerplate for handling accumulating and averaging data over multiple frames.

The details of these computations are encapsulated by the `BondComputeHistogram` class, which contains a histogram, provides accessors to standard histogram properties like bin counts and axis sizes, and has a generic accumulation method that accepts a lambda compute function. This signature is very similar to the utility functions for looping over neighbors, and in fact the function is transparently forwarded to `locality::loopOverNeighbors`. Any

compute that matches this pattern should inherit from the `BondComputeHistogram` class and must implement an `accumulate` method to perform the computation and a `reduce` to reduce thread local histograms into a single histogram..

7.20.4 Making freud Releases

Release Process

Documented below are the steps needed to make a new release of **freud**.

1. Create a release branch, numbered according to [Semantic Versioning](#):

```
git checkout -b release/vX.Y.Z
```

Changelog

2. Review headings (Added, Changed, Fixed, Deprecated, Removed) and ensure consistent formatting.
3. Update the release version and release date from `next` to `vX.Y.Z - YYYY-MM-DD`.

Submodules

4. Update git submodules (optional, but should be done regularly).

Code Formatting

5. Reformat C++ code with `clang-format 6.0`:

```
clang-format -style=file cpp/**/*.cpp
```

Generate Cythonized C++

6. Rebuild the project with `--ENABLE-CYTHON` so that the files in `freud/*.cpp` are updated. Ideally, do this on a system with a relatively clean `PATH` and a system-provided Python, or else some user paths (including usernames) may be included in the result.

Contributors

7. Update the contributor list:

```
git shortlog -sne > contributors.txt
```

Bump version

8. Commit previous changes before running `bumpversion`.
9. Use the `bumpversion` package to increase the version number and automatically generate a git tag:

```
bumpversion patch # for X.Y.Z
bumpversion minor # for X.Y
bumpversion major # for X
```

10. Push the release branch to the remote:

```
git push -u origin release/vX.Y.Z
```

11. Ensure that ReadTheDocs and continuous integration pass (you will need to manually enable the branch on ReadTheDocs' web interface to test it). Then push the tag:

```
git push --tags
```

Automatic Builds

12. Pushing the tag will cause CircleCI to create a release for PyPI automatically (see automation in `.circleci/config.yml`). Make sure this succeeds – it takes a while to run.
13. Create a pull request and merge the release branch into the `master` branch. Delete the release branch on ReadTheDocs' web interface, since there is now a tagged version.
14. The conda-forge autotick bot should discover that the PyPI source distribution has changed, and will create a pull request to the `conda-forge feedstock`. This pull request may take a few hours to appear. If other changes are needed in the conda-forge recipe (e.g. new dependencies), follow the conda-forge documentation to create a pull request from *your own fork* of the feedstock. Merge the pull request after all continuous integration passes to trigger release builds for conda-forge.

Release Announcement

15. Verify that ReadTheDocs, PyPI, and conda-forge have been updated to the newest version.
16. Send a release notification via the `freud-users` group. Follow the template of previous release notifications.

7.21 How to cite freud

Please acknowledge the use of this software within the body of your publication for example by copying or adapting the following formulation:

Data analysis for this publication utilized the freud library[1].

[1] V. Ramasubramani, B. D. Dice, E. S. Harper, M. P. Spellings, J. A. Anderson, and S. C. Glotzer. `freud`: A Software Suite for High Throughput Analysis of Particle Simulation Data. 2019. arXiv:1906.06317.

To cite this reference, you can use the following BibTeX entry:

```
@misc{freud,
  author = {Vyas Ramasubramani and
            Bradley D. Dice and
            Eric S. Harper and
            Matthew P. Spellings and
            Joshua A. Anderson and
            Sharon C. Glotzer},
  title = {freud: A Software Suite for High Throughput
            Analysis of Particle Simulation Data},
  year = {2019},
  eprint = {arXiv:1906.06317},
}
```

7.22 References

7.23 License

BSD 3-Clause License for freud

Copyright (c) 2010–2019 The Regents of the University of Michigan
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.
3. Neither the name of the copyright holder nor the names of its contributors
may be used to endorse or promote products derived from this software without
specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

7.24 Credits

7.24.1 freud Developers

The following people contributed to the development of freud.

Vyas Ramasubramani - **Lead developer**

- Ensured PEP8 compliance.
- Added CircleCI continuous integration support.
- Create environment module and refactored order module.
- Rewrote most of freud docs, including order, density, and environment modules.
- Fixed nematic order parameter.
- Add properties for accessing class members.
- Various minor bug fixes.
- Refactored PMFT code.
- Refactored Steinhardt order parameter code.
- Wrote numerous examples of freud usage.
- Rewrote most of freud tests.
- Replaced CMake-based installation with setup.py using Cython.
- Add code coverage metrics.
- Added support for installing from PyPI, including ensuring that NumPy is installed.
- Converted all docstrings to Google format, fixed various incorrect docs.
- Debugged and added rotational autocorrelation code.
- Added MSD module.
- Wrote NeighborQuery, _QueryArgs, NeighborQueryResult classes.
- Wrote neighbor iterator infrastructure.
- Wrote PairCompute and SpatialHistogram parent classes.
- Wrote ManagedArray class.
- Wrote C++ histogram-related classes.
- Initial design of freud 2.0 API (NeighborQuery objects, neighbor computations, histograms).
- Standardized neighbor API in Python to use dictionaries of arguments or NeighborList objects for all pair computations.
- Standardized all attribute access into C++ with Python properties.
- Standardized variable naming of points/query_points across all of freud.
- Standardized vector directionality in computes.
- Enabled usage of quaternions in place of angles for orientations in 2D PMFT calculations.
- Wrote new freud 2.0 compute APIs based on neighbor_query objects and neighbors as either dictionaries or NeighborLists.

- Rewrote MatchEnv code to fit freud 2.0 API, splitting it into 3 separate calculations and rewriting internals using NeighborQuery objects.
- Wrote tutorial and reference sections of documentation.
- Unified util and common packages.
- Rewrote all docstrings in the package for freud 2.0.
- Changed Cubatic to use Mersenne Twisters for rng.
- Moved all citations into Bibtex format.
- Created data module.
- Standardized PMFT normalization.
- Enabled optional normalization of RDF.
- Changed correlation function to properly take the complex conjugate of inputs.
- Wrote developer documentation for version 2.0.
- Fixed handling of 2D systems from various data sources.
- Fixed usage of query orientations in PMFTXY and PMFTXYZ when points and query points are not identical.

Bradley Dice - **Lead developer**

- Cleaned up various docstrings.
- Fixed bugs in HexOrderParameter.
- Cleaned up testing code.
- Added bumpversion support.
- Reduced all compile warnings.
- Added Python interface for box periodicity.
- Added Voronoi support for neighbor lists across periodic boundaries.
- Added Voronoi weights for 3D.
- Added Voronoi cell volume computation.
- Incorporated internal BiMap class for Boost removal.
- Wrote numerous examples of freud usage.
- Added some freud tests.
- Added ReadTheDocs support.
- Rewrote interface module into pure Cython.
- Added box duck-typing.
- Removed nose from unit testing.
- Use lambda function for parallelizing CorrelationFunction with TBB.
- Finalized boost removal.
- Wrote AABQuery class.
- Consolidated cluster module functionality.
- Rewrote SolidLiquid order parameter class.

- Updated AngularSeparation class.
- Rewrote Voronoi implementation to leverage voro++.
- Implemented Voronoi bond weighting to enable Minkowski structure metrics.
- Refactored methods in Box and PeriodicBuffer for v2.0.
- Added checks to C++ for 2D boxes where required.
- Refactored cluster module.
- Standardized vector directionality in computes.
- NeighborQuery support to ClusterProperties, GaussianDensity, Voronoi, PeriodicBuffer, Interface.
- Standardized APIs for order parameters.
- Added radius of gyration to ClusterProperties.
- Improved Voronoi plotting code.
- Corrected number of points/query points in LocalDensity.
- Made PeriodicBuffer inherit from _Compute.
- Removed cudacpu and HOOMDMath includes.
- Added plotting functionality for Box and NeighborQuery objects.
- Added support for reading system data directly from MDAnalysis, garnett, gsd, HOOMD-blue, and OVITO.
- Revised tutorials and documentation on data inputs.
- Updated MSD to perform accumulation with `compute(..., reset=False)`.
- Added test PyPI support to continuous integration.
- Added continuous integration to freud-examples.
- Implemented periodic center of mass computations in C++.
- Revised docs about query modes.
- Implemented smarter heuristics in Voronoi for voro++ block sizes, resulting in significant performance gains for large systems.
- Corrected calculation of neighbor distances in the Voronoi NeighborList.
- Added finite tolerance to ensure stability of 2D Voronoi NeighborList computations.

Eric Harper, University of Michigan - **Former lead developer**

- Added TBB parallelism.
- Wrote PMFT module.
- Added NearestNeighbors (since removed).
- Wrote RDF.
- Added bonding module (since removed).
- Added cubatic order parameter.
- Added hexatic order parameter.
- Added Pairing2D (since removed).
- Created common array conversion logic.

Joshua A. Anderson, University of Michigan - **Creator and former lead developer**

- Initial design and implementation.
- Wrote LinkCell and IteratorLinkCell.
- Wrote GaussianDensity, LocalDensity.
- Added parallel module.
- Added indexing modules (since removed).
- Wrote Cluster and ClusterProperties modules.

Matthew Spellings - **Former lead developer**

- Added generic neighbor list.
- Enabled neighbor list usage across freud modules.
- Added correlation functions.
- Added LocalDescriptors class.
- Added interface module.

Erin Teich

- Wrote environment matching (MatchEnv) class.
- Wrote BondOrder class (with Julia Dshemuchadse).
- Wrote AngularSeparation class (with Andrew Karas).
- Contributed to LocalQI development.
- Wrote LocalBondProjection class.

M. Eric Irrgang

- Authored kspace module (since removed).
- Fixed numerous bugs.
- Contributed to freud.shape (since removed).

Chrisy Du

- Authored Steinhardt order parameter classes.
- Fixed support for triclinic boxes.

Antonio Osorio

- Developed TrajectoryXML class.
- Various bug fixes.
- OpenMP support.

Richmond Newman

- Developed the freud box.
- Solid liquid order parameter.

Carl Simon Adorf

- Developed the Python box module.

Jens Glaser

- Wrote kspace front-end (since removed).
- Modified kspace module (since removed).
- Wrote Nematic order parameter class.

Benjamin Schultz

- Wrote Voronoi class.
- Fix normalization in GaussianDensity.
- Bug fixes in shape module (since removed).

Bryan VanSaders

- Make Cython catch C++ exceptions.
- Add shiftvec option to PMFT.

Ryan Marson

- Various GaussianDensity bugfixes.

Yina Geng

- Co-wrote Voronoi neighbor list module.
- Add properties for accessing class members.

Carolyn Phillips

- Initial design and implementation.
- Package name.

Ben Swerdlow

- Documentation and installation improvements.

James Antonaglia

- Added number of neighbors as an argument to HexOrderParameter.
- Bugfixes.
- Analysis of deprecated kspace module.

Mayank Agrawal

- Co-wrote Voronoi neighbor list module.

William Zygmunt

- Helped with Boost removal.

Greg van Anders

- Bugfixes for CMake and SSE2 installation instructions.

James Proctor

- Cythonization of the cluster module.

Rose Cersonsky

- Enabled TBB-parallelism in density module.
- Fixed how C++ arrays were pulled into Cython.

Wenbo Shen

- Translational order parameter.

Andrew Karas

- Angular separation.
- Wrote reference implementation for rotational autocorrelation.

Paul Dodd

- Fixed CorrelationFunction namespace, added ComputeOCF class for TBB parallelization.

Tim Moore

- Added optional rmin argument to density.RDF.
- Enabled NeighborList indexing.

Alex Dutton

- BiMap class for MatchEnv.

Matthew Palathingal

- Replaced use of boost shared arrays with shared ptr in Cython.
- Helped incorporate BiMap class into MatchEnv.

Kelly Wang

- Enabled NeighborList indexing.

Yezhi Jin

- Added support for 2D arrays in the Python interface to Box functions.
- Rewrote Voronoi implementation to leverage voro++.
- Implemented Voronoi bond weighting to enable Minkowski structure metrics.

Brandon Butler

- Rewrote Steinhardt order parameter.

Jin Soo Ihm

- Added benchmarks.
- Contributed to NeighborQuery classes.
- Refactored C++ to perform neighbor queries on-the-fly.
- Added plotting functions to analysis classes.
- Wrote RawPoints class.
- Created Compute parent class with decorators to ensure properties have been computed.
- Updated common array conversion logic.
- Added many validation tests.

Mike Henry

- Fixed syntax in freud-examples notebooks for v2.0.
- Updated documentation links

7.24.2 Source code

Eigen (<http://eigen.tuxfamily.org>) is included as a git submodule in freud. Eigen is made available under the Mozilla Public License v2.0 (<http://mozilla.org/MPL/2.0/>). Its linear algebra routines are used for various tasks including the computation of eigenvalues and eigenvectors.

fsph (<https://github.com/glotzerlab/fsph>) is included as a git submodule in freud. It is used for the calculation of spherical harmonics. fsph is made available under the MIT license:

```
Copyright (c) 2016 The Regents of the University of Michigan

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
```

HOOMD-blue (<https://github.com/glotzerlab/hoomd-blue>) is the original source of some algorithms and tools for vector math implemented in freud. HOOMD-blue is made available under the BSD 3-Clause license:

```
BSD 3-Clause License for HOOMD-blue

Copyright (c) 2009-2019 The Regents of the University of Michigan All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice,
   this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice,
   this list of conditions and the following disclaimer in the documentation
   and/or other materials provided with the distribution.

3. Neither the name of the copyright holder nor the names of its contributors
   may be used to endorse or promote products derived from this software without
   specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
```

(continues on next page)

(continued from previous page)

(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

voro++ (<https://github.com/chr1shr/voro>) is included as a git submodule in freud. It is used for computing Voronoi diagrams. voro++ is made available under the following license:

Voro++ Copyright (c) 2008, The Regents of the University of California, through Lawrence Berkeley National Laboratory (subject to receipt of any required approvals from the U.S. Dept. of Energy). All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

(1) Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

(2) Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

(3) Neither the name of the University of California, Lawrence Berkeley National Laboratory, U.S. Dept. of Energy nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

You are under no obligation whatsoever to provide any bug fixes, patches, or upgrades to the features, functionality or performance of the source code ("Enhancements") to anyone; however, if you choose to make your Enhancements available either publicly, or directly to Lawrence Berkeley National Laboratory, without imposing a separate written license agreement for such Enhancements, then you hereby grant the following license: a non-exclusive, royalty-free perpetual license to install, use, modify, prepare derivative works, incorporate into other computer software, distribute, and sublicense such enhancements or derivative works thereof, in binary and source code form.

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

BIBLIOGRAPHY

- [CPC+11] Vania Calandrini, Eric Pellegrini, Paolo Calligari, Konrad Hinsén, and Gerald R Kneller. Nmoldyn-interfacing spectroscopic experiments, molecular dynamics simulations and models for time correlation functions. *École thématique de la Société Française de la Neutronique*, 12:201–232, 2011.
- [FHND10] L. Filion, M. Hermes, R. Ni, and M. Dijkstra. Crystal nucleation of hard spheres using molecular dynamics, umbrella sampling, and forward flux sampling: a comparison of simulation techniques. *The Journal of Chemical Physics*, 133(24):244115, Dec 2010. URL: <http://dx.doi.org/10.1063/1.3506838>, doi:10.1063/1.3506838.
- [GMS63] Izrail Moiseevich Gelfand, Robert Adolfovich Minlos, and Z. Ya Shapiro. *Representations of the Rotation and Lorentz Groups and their Applications*. Macmillan Publishers, 1963.
- [HAG15] Amir Haji-Akbari and Sharon C Glotzer. Strong orientational coordinates and orientational order parameters for symmetric objects. *Journal of Physics A: Mathematical and Theoretical*, 48(48):485201, Oct 2015. URL: <http://dx.doi.org/10.1088/1751-8113/48/48/485201>, doi:10.1088/1751-8113/48/48/485201.
- [HAN+16] Michael P. Howard, Joshua A. Anderson, Arash Nikoubashman, Sharon C. Glotzer, and Athanasios Z. Panagiotopoulos. Efficient neighbor list calculation for molecular simulation of colloidal systems using graphics processing units. *Computer Physics Communications*, 203:45–52, June 2016. doi:10.1016/j.cpc.2016.02.003.
- [KDvAG19] Andrew S. Karas, Julia Dshemuchadse, Greg van Anders, and Sharon C. Glotzer. Phase behavior and design rules for plastic colloidal crystals of hard polyhedra via consideration of directional entropic forces. *Soft Matter*, 15:5380–5389, 2019. doi:10.1039/C8SM02643B.
- [LD08] Wolfgang Lechner and Christoph Dellago. Accurate determination of crystal structures based on averaged local bond order parameters. *The Journal of Chemical Physics*, 129(11):114707, Sep 2008. URL: <http://dx.doi.org/10.1063/1.2977970>, doi:10.1063/1.2977970.
- [Ryc09] Chris Rycroft. Voro++: a three-dimensional voronoi cell library in c++. Technical Report, Lawrence Berkeley National Lab, 1 2009. doi:10.2172/946741.
- [Ste83] Paul J. Steinhardt. Bond-orientational order in liquids and glasses. *Physical Review B*, 28(2):784–805, 1983. doi:10.1103/PhysRevB.28.784.
- [tW95] Pieter Rein ten Wolde. Numerical evidence for bcc ordering at the surface of a critical fcc nucleus. *Physical Review Letters*, 75(14):2714–2717, 1995. doi:10.1103/PhysRevLett.75.2714.
- [vAAS+13] Greg van Anders, N. Khalid Ahmed, Ross Smith, Michael Engel, and Sharon C. Glotzer. Entropically patchy particles: engineering valence through shape entropy. *ACS Nano*, 8(1):931–940, Dec 2013. URL: <http://dx.doi.org/10.1021/nn4057353>, doi:10.1021/nn4057353.
- [vAKA+14] Greg van Anders, Daphne Klotsa, N. Khalid Ahmed, Michael Engel, and Sharon C. Glotzer. Understanding shape entropy through local dense packing. *PNAS; Proceedings of the National Academy of Sciences*, 111(45):E4812–E4821, 2014.

PYTHON MODULE INDEX

f

- `freud.box`, [138](#)
- `freud.cluster`, [144](#)
- `freud.data`, [146](#)
- `freud.density`, [148](#)
- `freud.environment`, [154](#)
- `freud.interface`, [162](#)
- `freud.locality`, [163](#)
- `freud.msd`, [172](#)
- `freud.order`, [174](#)
- `freud.parallel`, [182](#)
- `freud.pmft`, [182](#)

Symbols

-\\-COVERAGE, [17](#)
 -\\-ENABLE-CYTHON, [16](#)
 -\\-NTHREAD, [17](#)
 -\\-PRINT-WARNINGS, [16](#)
 -\\-TBB-INCLUDE, [17](#)
 -\\-TBB-LINK, [17](#)
 -\\-TBB-ROOT, [16](#)
 -j, [16](#)

A

a1() (*freud.data.UnitCell* property), [146](#)
 a2() (*freud.data.UnitCell* property), [146](#)
 a3() (*freud.data.UnitCell* property), [146](#)
 AABQuery (class in *freud.locality*), [163](#)
 angles() (*freud.environment.AngularSeparationGlobal* property), [154](#)
 angles() (*freud.environment.AngularSeparationNeighbor* property), [155](#)
 AngularSeparationGlobal (class in *freud.environment*), [154](#)
 AngularSeparationNeighbor (class in *freud.environment*), [155](#)
 average (*freud.order.Steinhardt* attribute), [180](#)

B

basis_positions() (*freud.data.UnitCell* property), [146](#)
 bcc() (*freud.data.UnitCell* class method), [146](#)
 bin_centers (*freud.density.CorrelationFunction* attribute), [148](#)
 bin_centers (*freud.density.RDF* attribute), [153](#)
 bin_centers (*freud.environment.BondOrder* attribute), [156](#)
 bin_centers (*freud.pmft.PMFTR12* attribute), [183](#)
 bin_centers (*freud.pmft.PMFTXY* attribute), [185](#)
 bin_centers (*freud.pmft.PMFTXYT* attribute), [186](#)
 bin_centers (*freud.pmft.PMFTXYZ* attribute), [188](#)
 bin_counts() (*freud.density.CorrelationFunction* property), [148](#)
 bin_counts() (*freud.density.RDF* property), [153](#)

bin_counts() (*freud.environment.BondOrder* property), [156](#)
 bin_counts() (*freud.pmft.PMFTR12* property), [183](#)
 bin_counts() (*freud.pmft.PMFTXY* property), [185](#)
 bin_counts() (*freud.pmft.PMFTXYT* property), [186](#)
 bin_counts() (*freud.pmft.PMFTXYZ* property), [188](#)
 bin_edges (*freud.density.CorrelationFunction* attribute), [148](#)
 bin_edges (*freud.density.RDF* attribute), [153](#)
 bin_edges (*freud.environment.BondOrder* attribute), [156](#)
 bin_edges (*freud.pmft.PMFTR12* attribute), [183](#)
 bin_edges (*freud.pmft.PMFTXY* attribute), [185](#)
 bin_edges (*freud.pmft.PMFTXYT* attribute), [186](#)
 bin_edges (*freud.pmft.PMFTXYZ* attribute), [188](#)
 bond_order() (*freud.environment.BondOrder* property), [156](#)
 BondOrder (class in *freud.environment*), [155](#)
 bounds (*freud.density.CorrelationFunction* attribute), [148](#)
 bounds (*freud.density.RDF* attribute), [153](#)
 bounds (*freud.environment.BondOrder* attribute), [157](#)
 bounds (*freud.pmft.PMFTR12* attribute), [183](#)
 bounds (*freud.pmft.PMFTXY* attribute), [185](#)
 bounds (*freud.pmft.PMFTXYT* attribute), [186](#)
 bounds (*freud.pmft.PMFTXYZ* attribute), [188](#)
 Box (class in *freud.box*), [138](#)
 box (*freud.locality.AABQuery* attribute), [163](#)
 box (*freud.locality.LinkCell* attribute), [165](#)
 box (*freud.locality.NeighborQuery* attribute), [168](#)
 box (*freud.msd.MSD* attribute), [173](#)
 box() (*freud.data.UnitCell* property), [146](#)
 box() (*freud.density.CorrelationFunction* property), [149](#)
 box() (*freud.density.GaussianDensity* property), [150](#)
 box() (*freud.density.LocalDensity* property), [151](#)
 box() (*freud.density.RDF* property), [153](#)
 box() (*freud.environment.BondOrder* property), [157](#)
 box() (*freud.pmft.PMFTR12* property), [183](#)
 box() (*freud.pmft.PMFTXY* property), [185](#)
 box() (*freud.pmft.PMFTXYT* property), [186](#)
 box() (*freud.pmft.PMFTXYZ* property), [188](#)

`buffer_box()` (*freud.locality.PeriodicBuffer* property), 170
`buffer_ids()` (*freud.locality.PeriodicBuffer* property), 170
`buffer_points()` (*freud.locality.PeriodicBuffer* property), 170

C

`cell_width` (*freud.locality.LinkCell* attribute), 165
`center` (*freud.box.Box* attribute), 139
`center_of_mass` (*freud.box.Box* attribute), 139
`centers()` (*freud.cluster.ClusterProperties* property), 145
`Cluster` (class in *freud.cluster*), 144
`cluster_environments()` (*freud.environment.EnvironmentCluster* property), 157
`cluster_idx()` (*freud.cluster.Cluster* property), 144
`cluster_idx()` (*freud.environment.EnvironmentCluster* property), 157
`cluster_idx()` (*freud.order.SolidLiquid* property), 178
`cluster_keys()` (*freud.cluster.Cluster* property), 144
`cluster_sizes()` (*freud.order.SolidLiquid* property), 178
`ClusterProperties` (class in *freud.cluster*), 144
`compute` (*freud.cluster.Cluster* attribute), 144
`compute` (*freud.cluster.ClusterProperties* attribute), 145
`compute` (*freud.density.CorrelationFunction* attribute), 149
`compute` (*freud.density.GaussianDensity* attribute), 150
`compute` (*freud.density.LocalDensity* attribute), 151
`compute` (*freud.density.RDF* attribute), 153
`compute` (*freud.environment.AngularSeparationGlobal* attribute), 154
`compute` (*freud.environment.AngularSeparationNeighbor* attribute), 155
`compute` (*freud.environment.BondOrder* attribute), 157
`compute` (*freud.environment.EnvironmentCluster* attribute), 158
`compute` (*freud.environment.EnvironmentMotifMatch* attribute), 159
`compute` (*freud.environment.LocalBondProjection* attribute), 159
`compute` (*freud.environment.LocalDescriptors* attribute), 160
`compute` (*freud.interface.Interface* attribute), 162
`compute` (*freud.locality.PeriodicBuffer* attribute), 170
`compute` (*freud.locality.Voronoi* attribute), 171
`compute` (*freud.msd.MSD* attribute), 173
`compute` (*freud.order.Cubatic* attribute), 174
`compute` (*freud.order.Hexatic* attribute), 176
`compute` (*freud.order.Nematic* attribute), 176

`compute` (*freud.order.RotationalAutocorrelation* attribute), 177
`compute` (*freud.order.SolidLiquid* attribute), 178
`compute` (*freud.order.Steinhardt* attribute), 180
`compute` (*freud.order.Translational* attribute), 181
`compute` (*freud.pmft.PMFTR12* attribute), 183
`compute` (*freud.pmft.PMFTXY* attribute), 185
`compute` (*freud.pmft.PMFTXYT* attribute), 186
`compute` (*freud.pmft.PMFTXYZ* attribute), 188
`copy` (*freud.locality.NeighborList* attribute), 167
`correlation()` (*freud.density.CorrelationFunction* property), 149
`CorrelationFunction` (class in *freud.density*), 148
`Cubatic` (class in *freud.order*), 174
`cubatic_tensor()` (*freud.order.Cubatic* property), 175
`cube()` (*freud.box.Box* class method), 140

D

`default_query_args` (*freud.cluster.Cluster* attribute), 144
`default_query_args` (*freud.density.CorrelationFunction* attribute), 149
`default_query_args` (*freud.density.LocalDensity* attribute), 151
`default_query_args` (*freud.density.RDF* attribute), 153
`default_query_args` (*freud.environment.AngularSeparationNeighbor* attribute), 155
`default_query_args` (*freud.environment.BondOrder* attribute), 157
`default_query_args` (*freud.environment.EnvironmentCluster* attribute), 158
`default_query_args` (*freud.environment.EnvironmentMotifMatch* attribute), 159
`default_query_args` (*freud.environment.LocalBondProjection* attribute), 160
`default_query_args` (*freud.environment.LocalDescriptors* attribute), 161
`default_query_args` (*freud.interface.Interface* attribute), 162
`default_query_args` (*freud.order.Hexatic* attribute), 176
`default_query_args` (*freud.order.SolidLiquid* attribute), 178
`default_query_args` (*freud.order.Steinhardt* attribute), 180

default_query_args (*freud.order.Translational attribute*), 181
 default_query_args (*freud.pmft.PMFTR12 attribute*), 184
 default_query_args (*freud.pmft.PMFTXY attribute*), 185
 default_query_args (*freud.pmft.PMFTXYT attribute*), 187
 default_query_args (*freud.pmft.PMFTXYZ attribute*), 189
 density() (*freud.density.GaussianDensity property*), 150

density() (*freud.density.LocalDensity property*), 152
 diameter (*freud.density.LocalDensity attribute*), 152
 dimensions (*freud.box.Box attribute*), 140
 dimensions() (*freud.data.UnitCell property*), 146
 director() (*freud.order.Nematic property*), 176
 distances (*freud.locality.NeighborList attribute*), 167

E

EnvironmentCluster (*class in freud.environment*), 157
 EnvironmentMotifMatch (*class in freud.environment*), 158

F

fcc() (*freud.data.UnitCell class method*), 146
 filter (*freud.locality.NeighborList attribute*), 167
 filter_r (*freud.locality.NeighborList attribute*), 167
 find_first_index (*freud.locality.NeighborList attribute*), 167
 freud.box (*module*), 138
 freud.cluster (*module*), 144
 freud.data (*module*), 146
 freud.density (*module*), 148
 freud.environment (*module*), 154
 freud.interface (*module*), 162
 freud.locality (*module*), 163
 freud.msd (*module*), 172
 freud.order (*module*), 174
 freud.parallel (*module*), 182
 freud.pmft (*module*), 182
 from_arrays() (*freud.locality.NeighborList class method*), 167
 from_box() (*freud.box.Box class method*), 140
 from_matrix() (*freud.box.Box class method*), 140
 from_system() (*freud.locality.AABBQuery class method*), 163
 from_system() (*freud.locality.LinkCell class method*), 165
 from_system() (*freud.locality.NeighborQuery class method*), 168

G

GaussianDensity (*class in freud.density*), 149
 generate_system() (*freud.data.UnitCell method*), 147
 get_box_vector (*freud.box.Box attribute*), 140
 get_images (*freud.box.Box attribute*), 141
 get_num_threads (*in module freud.parallel*), 182
 global_tensor() (*freud.order.Cubatic property*), 175
 gyrations() (*freud.cluster.ClusterProperties property*), 145

H

Hexatic (*class in freud.order*), 175

I

Interface (*class in freud.interface*), 162
 is2D (*freud.box.Box attribute*), 141

K

k (*freud.order.Hexatic attribute*), 176
 k (*freud.order.Translational attribute*), 181

L

L (*freud.box.Box attribute*), 138
 l (*freud.order.RotationalAutocorrelation attribute*), 177
 l (*freud.order.SolidLiquid attribute*), 178
 l (*freud.order.Steinhardt attribute*), 180
 L_inv (*freud.box.Box attribute*), 138
 l_max (*freud.environment.LocalDescriptors attribute*), 161
 largest_cluster_size() (*freud.order.SolidLiquid property*), 178
 lattice_vectors() (*freud.data.UnitCell property*), 147
 LinkCell (*class in freud.locality*), 164
 LocalBondProjection (*class in freud.environment*), 159
 LocalDensity (*class in freud.density*), 150
 LocalDescriptors (*class in freud.environment*), 160
 Lx (*freud.box.Box attribute*), 139
 Ly (*freud.box.Box attribute*), 139
 Lz (*freud.box.Box attribute*), 139

M

make_absolute (*freud.box.Box attribute*), 141
 make_fractional (*freud.box.Box attribute*), 141
 make_random_system() (*in module freud.data*), 147
 matches() (*freud.environment.EnvironmentMotifMatch property*), 159
 mode (*freud.environment.BondOrder attribute*), 157

mode (*freud.environment.LocalDescriptors* attribute), 161

MSD (*class in freud.msd*), 172

msd() (*freud.msd.MSD* property), 173

N

n_r() (*freud.density.RDF* property), 153

nbins (*freud.density.CorrelationFunction* attribute), 149

nbins (*freud.density.RDF* attribute), 153

nbins (*freud.environment.BondOrder* attribute), 157

nbins (*freud.pmft.PMFTR12* attribute), 184

nbins (*freud.pmft.PMFTXY* attribute), 185

nbins (*freud.pmft.PMFTXYT* attribute), 187

nbins (*freud.pmft.PMFTXYZ* attribute), 189

negative_m (*freud.environment.LocalDescriptors* attribute), 161

neighbor_counts (*freud.locality.NeighborList* attribute), 168

NeighborList (*class in freud.locality*), 166

NeighborQuery (*class in freud.locality*), 168

NeighborQueryResult (*class in freud.locality*), 170

Nematic (*class in freud.order*), 176

nematic_tensor() (*freud.order.Nematic* property), 176

nlist() (*freud.environment.AngularSeparationNeighbor* property), 155

nlist() (*freud.environment.LocalBondProjection* property), 160

nlist() (*freud.environment.LocalDescriptors* property), 161

nlist() (*freud.locality.Voronoi* property), 171

nlist() (*freud.order.SolidLiquid* property), 178

normalize_q (*freud.order.SolidLiquid* attribute), 178

normed_projections()
(*freud.environment.LocalBondProjection* property), 160

num_clusters() (*freud.cluster.Cluster* property), 144

num_clusters() (*freud.environment.EnvironmentCluster* property), 158

num_connections() (*freud.order.SolidLiquid* property), 178

num_neighbors() (*freud.density.LocalDensity* property), 152

num_sphs() (*freud.environment.LocalDescriptors* property), 161

NumThreads (*class in freud.parallel*), 182

O

order() (*freud.order.Cubatic* property), 175

order() (*freud.order.Nematic* property), 176

order() (*freud.order.RotationalAutocorrelation* property), 177

order() (*freud.order.Steinhardt* property), 180

orientation() (*freud.order.Cubatic* property), 175

P

particle_order() (*freud.order.Cubatic* property), 175

particle_order() (*freud.order.Hexatic* property), 176

particle_order() (*freud.order.RotationalAutocorrelation* property), 177

particle_order() (*freud.order.Steinhardt* property), 180

particle_order() (*freud.order.Translational* property), 181

particle_tensor() (*freud.order.Nematic* property), 176

periodic (*freud.box.Box* attribute), 141

periodic_x (*freud.box.Box* attribute), 141

periodic_y (*freud.box.Box* attribute), 141

periodic_z (*freud.box.Box* attribute), 141

PeriodicBuffer (*class in freud.locality*), 170

plot (*freud.box.Box* attribute), 141

plot (*freud.cluster.Cluster* attribute), 144

plot (*freud.density.CorrelationFunction* attribute), 149

plot (*freud.density.GaussianDensity* attribute), 150

plot (*freud.density.RDF* attribute), 153

plot (*freud.environment.EnvironmentCluster* attribute), 158

plot (*freud.locality.AABBQuery* attribute), 164

plot (*freud.locality.LinkCell* attribute), 165

plot (*freud.locality.NeighborQuery* attribute), 169

plot (*freud.locality.Voronoi* attribute), 171

plot (*freud.msd.MSD* attribute), 173

plot (*freud.order.SolidLiquid* attribute), 179

plot (*freud.order.Steinhardt* attribute), 180

plot (*freud.pmft.PMFTXY* attribute), 185

pmft() (*freud.pmft.PMFTR12* property), 184

pmft() (*freud.pmft.PMFTXY* property), 186

pmft() (*freud.pmft.PMFTXYT* property), 187

pmft() (*freud.pmft.PMFTXYZ* property), 189

PMFTR12 (*class in freud.pmft*), 183

PMFTXY (*class in freud.pmft*), 184

PMFTXYT (*class in freud.pmft*), 186

PMFTXYZ (*class in freud.pmft*), 187

point_count() (*freud.interface.Interface* property), 162

point_environments()
(*freud.environment.EnvironmentCluster* property), 158

point_environments()
(*freud.environment.EnvironmentMotifMatch* property), 159

point_ids() (*freud.interface.Interface* property), 162

point_indices (*freud.locality.NeighborList* attribute), 168

points (*freud.locality.AABBQuery* attribute), 164
 points (*freud.locality.LinkCell* attribute), 166
 points (*freud.locality.NeighborQuery* attribute), 169
 polytopes () (*freud.locality.Voronoi* property), 171
 projections () (*freud.environment.LocalBondProjection* property), 160

Q

q_threshold (*freud.order.SolidLiquid* attribute), 179
 ql () (*freud.order.Steinhardt* property), 180
 ql_ij () (*freud.order.SolidLiquid* property), 179
 query (*freud.locality.AABBQuery* attribute), 164
 query (*freud.locality.LinkCell* attribute), 166
 query (*freud.locality.NeighborQuery* attribute), 169
 query_point_count () (*freud.interface.Interface* property), 162
 query_point_ids () (*freud.interface.Interface* property), 162
 query_point_indices (*freud.locality.NeighborList* attribute), 168

R

r_max (*freud.density.GaussianDensity* attribute), 150
 r_max (*freud.density.LocalDensity* attribute), 152
 radii_of_gyration () (*freud.cluster.ClusterProperties* property), 145
 RDF (class in *freud.density*), 152
 rdf () (*freud.density.RDF* property), 154
 RotationalAutocorrelation (class in *freud.order*), 177

S

sc () (*freud.data.UnitCell* class method), 147
 scale (*freud.order.Cubatic* attribute), 175
 seed (*freud.order.Cubatic* attribute), 175
 segments (*freud.locality.NeighborList* attribute), 168
 set_num_threads (in module *freud.parallel*), 182
 sigma (*freud.density.GaussianDensity* attribute), 150
 sizes () (*freud.cluster.ClusterProperties* property), 145
 solid_threshold (*freud.order.SolidLiquid* attribute), 179
 SolidLiquid (class in *freud.order*), 177
 sph () (*freud.environment.LocalDescriptors* property), 161
 square () (*freud.box.Box* class method), 142
 square () (*freud.data.UnitCell* class method), 147
 Steinhardt (class in *freud.order*), 179

T

t_final (*freud.order.Cubatic* attribute), 175
 t_initial (*freud.order.Cubatic* attribute), 175
 to_dict (*freud.box.Box* attribute), 142

to_matrix (*freud.box.Box* attribute), 142
 toNeighborList (*freud.locality.NeighborQueryResult* attribute), 170
 Translational (class in *freud.order*), 181

U

u (*freud.order.Nematic* attribute), 177
 UnitCell (class in *freud.data*), 146
 unwrap (*freud.box.Box* attribute), 142

V

v1 (*freud.box.Box* attribute), 143
 v2 (*freud.box.Box* attribute), 143
 v3 (*freud.box.Box* attribute), 143
 volume (*freud.box.Box* attribute), 143
 volumes () (*freud.locality.Voronoi* property), 171
 Voronoi (class in *freud.locality*), 171

W

weighted (*freud.order.Steinhardt* attribute), 180
 weights (*freud.locality.NeighborList* attribute), 168
 width (*freud.density.GaussianDensity* attribute), 150
 wl (*freud.order.Steinhardt* attribute), 180
 wrap (*freud.box.Box* attribute), 143

X

xy (*freud.box.Box* attribute), 143
 xz (*freud.box.Box* attribute), 143

Y

yz (*freud.box.Box* attribute), 143